JOINT SCIENTIFIC PROGRAM AND ONE DAY SEMINAR ON: ECOSYSTEM BASED DISASTER RISK REDUCTION

Yogyakarta, Indonesia: 8 December 2012

**Editors : Junun Sartohadi, Jiba Raj Pokarel, Udo Michael Nehren,
Guilherme Fernandez, Simone Sandholz**

ISBN: 978-602-14856-1-5

**MASTER PROGRAM ON PLANNING AND MANAGEMENT
OF COASTAL AREA AND WATERSHED (MPPDAS)
FACULTY OF GEOGRAPHY - UNIVERSITAS GADJAH MADA
IN COOPERATION WITH:
CENTER FOR NATURAL RESOURCES AND DEVELOPMENT (CNRD)
2013**

**JOINT SCIENTIFIC PROGRAM
AND ONE DAY SEMINAR ON:
ECOSYSTEM BASED
DISASTER RISK REDUCTION**

Yogyakarta, Indonesia: 8 December 2012

ISBN: 978-602-14856-1-5

Editors

Prof. Dr. Junun Sartohadi, M.Sc.

Prof. Dr. Jiba Raj Pokharel

Dr. Udo Michael Nehren

Prof. Dr. Guilherme Fernandez

Dipl. Ing. Simone Sandholz M. Eng.

Master Program on Planning
and Management of Coastal Area and Watershed (MPPDAS)
Faculty of Geography - Universitas Gadjah Mada
in Cooperation with:
Center for Natural Resources and Development (CNRD)
2013

**JOINT SCIENTIFIC PROGRAM
AND ONE DAY SEMINAR ON:
ECOSYSTEM BASED
DISASTER RISK REDUCTION**

Yogyakarta, Indonesia: 8 December 2012

Editors :

**Prof. Dr. Junun Sartohadi, M.Sc. (Universitas Gadjah Mada-Indonesia)
Prof. Dr. Jiba Raj Pokharel (Tribhuvan University-Nepal)
Dr. Udo Michael Nehren (Cologne University of Applied Sciences-Germany)
Prof. Dr. Guilherme Fernandez (University of São Paulo-Brazil)
Dipl. Ing. Simone Sandholz M. Eng.(University of Innsbruck-Austria)**

Cover Photograph by:

Ahmad Cahyadi, Andung Bayu Sekaranom

Layout:

Andung Bayu Sekaranom

ISBN:

978-602-14856-1-5

Published by:

**Master Program on Planning and Management of Coastal Area
and Watershed (MPPDAS)
Faculty of Geography - Universitas Gadjah Mada
in Cooperation with:
Center for Natural Resources and Development (CNRD)
January 2013**

Foreword

In the history of the interaction between human and its environment, disaster event is considered as the most unfortunate event to the human live. Although many disaster events are well-documented, the integration into disaster risk reduction action are still insufficient. In addition to the present disaster phenomena, degraded environment can cause or exaberate higher disasters event in the future. Deforestation in the upstream can cause more flooding and landslide, while reclamation in the coastal area can worsen the flooding in the low land area. The projected future phenomena of climate change also possibly make the disaster to be even worse. The additional stress factor due to climate change is predicted to contribute to the negative impacts of water and climate related hazards. such as stroms, heat waves, flood, and drought. The close linkages between environment and disasters also present an opportunity for the appropriate management of the ecosystem and environmental management. By applying appropriate ecosystem and environmental management, it can be harnessed for reducing disaster risk as well as maintain the environmental sustainability. Balanced and well-managed ecosystems, both land and aquatic ecosystem, can act as buffer and natural protection against common hazards. In this joint scientific program (JSP) and one day seminar held by Master program on Planning and Management of Coastal Area and Watershed (MPPDAS) Faculty of Geography-Universitas Gadjah Mada in collaboration with Center for Natural Resource and Management (CNRD), the issues of ecosystem based disaster risk reduction is taken into account. The collaboration of research result from Indonesia, Nepal, and Mozambique related to this topic therefore has been compiled, in which we can compare the ecosystem management related to the disaster risk reduction. We hope this proceeding will contribute to further discussions and researches in academic and institutional needs.

In Yogyakarta, December, 2012

Editors

TABLE OF CONTENTS

STUDY OF LANDSLIDE DYNAMIC WITH SPATIAL-TEMPORAL APPROACH AND ITS RELATION TO THE EXISTING ECO-DRR PROGRAM ON A PART OF DIENG AREA, INDONESIA Fredri Satya Candra Rosaji, Arief Darmawan, Danang Sri Hadmoko, Diana Paola Ordonez Coboz, Johannes Husener, Udo Michael Nehren, Nirmal Raj Harma, Ghanashyam Sapkota, Shreema Rana, Ajay Chandra Lal	1-12
VOLCANIC HAZARD MANAGEMENT IN DIENG PLATEAU AREA Henky Nugraha, Warsini Handatani, Munawaroh, Djati Mardiatno, Susanne Boerner, Corina Nienhaus, Andrea Teran Valdez, Guenther Straub, Ram Prasad Neupane, Jiba Raj Pokharel	13-20
SOIL EROSION REDUCTION: A CASE OF KEJAJAR SUB-DISTRICT, DIENG COMPLEX Nirjana Shrestha, Alzaena Ulya Rusdimi, Andrea Giraldo Arias, Matthias Knuver, Muhammad Rosidi, Ram Mani Ghimire, Aweta Amatya Shrestha	21-31
MANAGING SOIL EROSION THROUGH ECOSYSTEM-BASED APPROACHES: THE CASE OF URUGURU MOUNTAIN RANGES, IN MOROGORO REGION, TANZANIA Tumpale Sakijege	32-38
POLICIES AND CHALLENGES FOR EARTHQUAKE RISK REDUCTION IN MUNICIPALITIES OF NEPAL Ajay Chandra Lal.....	39-54
ENVIRONMENTAL MANAGEMENT AT GENDOL RIVER COURSE - SOUTHERN SLOPE OF MERAPI VOLCANO IN YOGYAKARTA SPECIAL REGION Darmakusuma Darmanto	55-72
GEOINDICATORS RELATED TO COASTAL MORPHODYNAMIC IN MAPUTO AND MACANETA BEACH, MOZAMBIQUE Parana Ari Santi, Aniesa Norma Dantie, Gabriel Spinola, and Wanderson Correa	73-83
INTEGRATED COASTAL ZONE MANAGEMENT PLANNING BASED ON DISASTER RISK MANAGEMENT IN MAPUTO CITY, MOZAMBIQUE Ajeng Larasati, Ahmad Cahyadi, Dhandhun Wacano	84-92

COMMUNITY-BASED DISASTER RISK MANAGEMENT (COMPARATIVE STUDY OF JAKARTA AND SURAKARTA CITY)	
Muh Aris Marfai, Annisa Triyanti	93-102
MANGROVE-COMMUNITY CONTRIBUTION ON DISASTER RISK REDUCTION DUE TO COASTAL FLOOD (A CASE STUDY IN LAWANGREJO VILLAGE, PEMALANG REGENCY)	
Anang Widhi Nirwansyah	103-119
PERCEPTION AND RESPONSE TO TIDAL FLOOD INUNDATION (CASE STUDY: TEGAL MUNICIPALITY)	
Riswan Septriayadi, Muh Aris Marfai, Johannes Hamhaber	119-134
BIODEGRADATION OF SEAGRASS ECOSYSTEM AND ITS IMPLICATION ON COASTAL RESOURCES IN MARATUA ISLAND, EAST KALIMANTAN – INDONESIA	
Bachtiar Wahyu Mutaqin, Fitriyani Nur Rohmah	135-146
IS VULNERABILITY 'A MERE MATTER OF SOCIAL-PHYSICAL PROBLEM' IN URBANAREAS? A CASE STUDY IN BANTUL DISTRICT – INDONESIA	
Dyah Rahmawati Hizbaron, Martin Coy, Mohamad Baiquni, Junun Sartohadi, Raden Rijanta	147-160
AGROCLIMATE CROPPING PATTERN FOR HARVEST FAILURE MITIGATION (CASE STUDY: TINALAH WATERSHED, YOGYAKARTA SPECIAL PROVINCE)	
Fitria Nucifera, Sari Utami	162-169
QUANTIFYING THE POTENTIAL CLIMATE CHANGE DRIVEN HAZARD IN A WATERSHED: CASE STUDY OF UPPER OPAK CATCHMENT AREA	
Andung Bayu Sekaranom	170-179
RIVER MORPHOLOGICAL CHANGE DUE TO PYROCLASTIC FLOW AND LAHAR FROM MERAPI ERUPTION 2010 IN KALI GENDOL, SLEMAN, YOGYAKARTA	
Gilang Arya Dipayana, Aries Dwi Wahyu Rahmadana, Fardyansari Cahyaningtyas, Dhandhun Wacano, Danang Sri Hadmoko	180-191
GEOMORPHOLOGICAL APPROACH FOR THE DISTRIBUTION OF DAMAGE ASSESSMENT OF INFRASTRUCTURE, SETTLEMENT, AND AGRICULTURAL LAND CAUSED BY LAHAR IN 2012-2011 CASE: KALI PUTIH, MAGELANG DISTRICT, CENTRAL JAVA	
Munawaroh, Widiyanto	192-199

RETENTION CAPACITY CHANGES IN OPAK SUB WATERSHED POST-MERAPI VOLCANO ERUPTION 2010	
Ahmad Cahyadi, Anggit Priadmodjo.....	200-206
ANALYSIS OF WATER RESOURCES PROBLEM FOR MERAPI ERUPTION 2010 REFUGESS IN TEMPORARY AND PERMANENT SHELTER (CASE STUDY OF CANGKRINGAN SUB-DISTRICT)	
Muhammad Bayu Hartono, Fitriyani Nur Rohmah, Parana Ari Santi, Olivia Elfatma ...	207-216
LAND DEGRADATION SYMPTOMS IN THE UPPER PART OF SERAYU WATERSHED SOLUTION BASED ON THE LOCAL WISDOM PERSPECTIVE	
Alzaena Ulya Rusdimi, Muhammad Rosidi, Muhammad Anggri Setiawan	217-232
REVEALING THE SOIL EROSION RISK MANAGEMENT IN INDONESIA	
Muhammad Anggri Setiawan, Junun Sartohadi, Djati Mardiatno, Muh Aris Marfai, Danang Sri Hadmoko	233-244
PRELIMINARY STUDY ON FLOOD RISK REDUCTION THROUGH ECO-POLDER SYSTEM MANAGEMENT	
Muh Aris Marfai	245-252

RETENTION CAPACITY CHANGES IN OPAK SUB WATERSHED POST-MERAPI VOLCANO ERUPTION 2010

Ahmad Cahyadi¹ and Anggit Priadmodjo²

¹Master Program on Planning and Management of Coastal Area and Watershed, Faculty of Geography, Universitas Gadjah Mada, Yogyakarta, Indonesia. Email: ahmadcahyadi@geo.ugm.ac.id

²Master Program on Disaster Management, Post-Graduate School, Universitas Gadjah Mada, Yogyakarta, Indonesia. Email: anggit.priadmodjo@mail.ugm.ac.id

Abstract

Merapi Volcano Eruption in 2010 led to physical changes in the Opak Sub Watershed in Sleman Regency. They include changes in land use/cover and soil conditions which consequently change the watershed response to rainfall, as well as the nature of generated flood. This research aimed to (1) determine land use/cover change in the upstream area of Opak Watershed after Merapi Volcano eruption in 2010, and (2) assess the changes in water retention capacity of the soil after the eruption of Merapi Volcano in 2010 and its impact on the environment. Land use change was analyzed with temporal remote sensing imagery with high resolution. Retention capacity was assessed using SCS-CN method. The results of both assessments were, then, used to formulate recommendations for management in Opak Sub Watershed. The analysis showed that Merapi Volcano eruption in 2010 caused 63% of land use/cover to become vacant and changes in surface material and watershed boundaries. In addition, it was determined that the post-eruption retention capacity had been increasing. This indicates that changes in material are likely to affect retention capacity much more than changes in land use/cover.

Keywords: eruption, land use/cover, Merapi Volcano, retention capacity

I. Background

Volcanic eruption in the history of Indonesia is a very common thing because it has approximately 500 volcanoes; 129 of which are active (Tunggal 2011). Significantly disrupting volcanic eruptions are even listed in the history i.e. the eruption of Tambora Volcano in 1815 which killed about 92,000 people and the eruption of Krakatau Volcano in 1883 that caused about 36,000 casualties (Isworo 2011). In addition, currently, the number of people living around the active Volcano in Indonesia is very high. People living in areas susceptible to volcanic eruption on Java island reach 120 million (Damardono 2011).

Merapi Volcano is one of the most active volcanoes in the world. It has a unique type of eruption in the form of *nuée ardente* (Voight et al. 2000). It is formed from lava flows and debris of lava dome with material consisting of elements of gas, rocks and volcanic ash. It is deemed the primary danger of Merapi eruption, which caused casualties in 2010.

The 2010 eruption led to physical changes of Opak Sub Watershed which is located on the southern slope (Figure 1). These changes are in the form of land use/cover change, soil amendments and the sub watershed's physical boundary changes. Land use/cover change certainly affects the hydrological cycle including the water retention capacity of the soil (Butler and Davies 2011; Cahyadi et al. 2012). It, then, effects on watershed response to rainfall followed by changing characteristics of generated flow (flood) (Maryono 2007).

Figure 1. Research location

II. Objective

This research aimed to (1) determine land use/cover change in Opak Sub Watershed after Merapi Volcano eruption in 2010, and (2) assess changes in water retention capacity of the soil after Merapi Volcano eruption in 2010 and its impact on the environment.

III. Methodology

3.1. Data

Data used in this research include RBI (*Rupa Bumi Indonesia*) map, soil map, Ikonos satellite imagery of 2006 and GeoEye satellite imagery recorded on December 15, 2010. RBI map which scale of 1:25,000 published by BAKOSURTANAL was used to delineate the physical boundary of Opak Sub Watershed before the eruption, while post-eruption's acquired from a revision based on the existing ridge of watershed figured in the GeoEye satellite imagery. Land use and soil maps were used to determine the curve number (CN) used in the calculation of maximum water retention capacity of the soil.

3.2. Analysis of Land Use/Cover Change

Land use/cover change was analyzed by comparing the extent of each land use on multi-temporal satellite imagery in which was calculated using geographic information system. Changes in land use were overlaid with the post-eruption soil maps to get the value of CN.

3.4. Calculate The Maximum Water Retention Capacity

SCS method, as developed by the Soil Conservation Services in 1972, was used to calculate maximum water retention capacity of the soil. The effective thickness of rain or the thickness of surface run-off, which is formed on a rainfall, and water retention capacity of the soil in dry, normal and saturated condition can be calculated by this method as long as they are generated by temporary or daily rain, not the monthly or yearly one. Here are the calculations conducted in SCS method:

1. Determining the CN value
CN value was determined according to soil classification in hydrology, which is divided in 4 groups:
 - A → characterized by soil with sandy texture and deep profile, the infiltration rate > 0.75 cm / hour
 - B → characterized by soil with sandy loam texture and shallow profile
 - C → characterized by soil with clay loam texture & low Biochemical Oxygen
 - D → characterized by soil with clay texture and infiltration rate < 0.15 cm / hour.
2. Determining the type of land use based on land use maps
3. Calculating CN value in normal conditions
Normal conditions occur whenever rain falls between 36-53 mm on the previous 5 days.
CN values in normal conditions were determined by arrangements in Table 1.

Table 1. Curve number value on various type of land use and soil type

Land Use / Land Cover		Soil hydrology group			
		A	B	C	D
1. Forest		25	55	70	77
		30	58	72	78
		25	55	70	77
2. Pasture		36	60	73	78
3. Industry and parking area which is impermeable		90	93	94	94
		90	93	94	95
4. Settlement area		60	74	83	87
5. Empty land		72	82	88	90
		77	86	91	94
6. Agricultural area covered by plant		52	68	79	84
7. Agricultural area		64	75	83	87
8. Aquatic area		98	98	98	98

Source: Ragan and Jackson (1980); Slack and Welch (1980); Bondelid et al. (1982)

4. Calculating CN value on dry and wet/saturated condition
Previous step (1 C) provided a CN values in normal condition (CN II), which occurs whenever rain falls between 36-53 mm on the previous 5 days. If rain falls less than 36 mm (dry) or more than 53 mm (wet/saturated), the determination of CN values will be based on arrangements summarized in Table 2 and equations written in Eq. 1 and 2.

Table 2. Determination of dry, normal and wet/saturated condition of the soil

AMC Group	Amount of rain in the previous 5 days (cm)
Group I (dry)	< 3,6
Group II (normal)	3,6 – 5,3
Group III (wet/saturated)	> 5,3

Source: McCuen (1982)

- 1) CN formula on dry condition ($CN(I)$):

$$CN(I) = \frac{4.2 \cdot CN(II)}{10 - 0.058 \cdot CN(II)} \quad (\text{Eq. 1})$$

- 2) CN formula on wet/saturated condition ($CN(III)$):

$$CN(III) = \frac{23 \cdot CN(II)}{10 + 0.13 \cdot CN(II)} \quad (\text{Eq. 2})$$

5. Determining regional CN value

Regional CN value was determined by weighed average calculation method, as seen in Eq. 3, where CN is curve number and A is the extent of each polygon which is represented by one CN value.

$$CN = \frac{CN_1 A_1 + CN_2 A_2 + \dots + CN_n A_n}{A_1 + A_2 + \dots + A_n} \quad (\text{Eq. 3})$$

6. Determining S thickness value

S thickness was calculated by formula written in Eq. 4 where S Thickness is maximum water potential retention thickness by soil (mm) and CN is curve number which was determined according to soil condition (based on the amount of rain on the previous 5 days). CN value which is used adjusted to the soil moisture condition.

$$S \text{ Thickness} = (25,400/CN) - 254 \quad (\text{Eq. 4})$$

7. Determining S value

S value (maximum water retention potential by soil) was calculated by formula written in Eq. 5. S Thickness is measured in m, while the extent of watershed is in m^2 , so that the value achieved for maximum water retention potential by soil is in volume unit (m^3) for each year.

$$S \text{ Value} = S \text{ Thickness} \times \text{Extent of Watershed} \quad (\text{Eq. 5})$$

III. Results and Discussion

3.1. Land Use/Cover Changes in Opak Sub Watershed

Merapi Volcano eruptions have led to land use/cover changes in Opak Sub Watershed. This is due to *nuée ardente* that turned land use/cover, such as settlements, forests, mixed gardens, pastures and shrub, into vacant land (Figure 2). There is approximately 62% of the total extent of the area experiencing land use/cover change, as summarized in Table 3, which is found in the upstream area of Opak Sub Watershed. Not only did it cause land use/cover change but it also changed the material – from material with sandy loam texture to pyroclastic material from sand to boulders, and ridge as the physical boundary of Opak Sub Watershed affecting its extent.

Figure 2. Land use/cover change caused by Merapi Volcano eruption 2010

Table 3. Land use/cover pre- and post-eruption of Merapi Volcano in 2010

Land Use/Cover	Extent of Watershed (km ²)	
	Pre-Eruption	Post-Eruption
Bush	0,412	0,007
Forest	0,002	0,000
Mixed garden	3,526	1,151
Settlement	0,284	0,143
Pasture	0,011	0,000
Irrigated field	0,235	0,235
Dry field	1,728	0,820
Empty land	0,000	3,997
Total	6,199	6,353

Source: Data Analysis

3.2. Retention Capacity Change in Opak Sub Watershed

The results showed that the value of capacity retention post-eruption is greater than it is before the eruption (Table 4). Curve number value of vacant land is actually bigger than forests, grassland, settlements, and dry field. This means that material changes affect retention capacity in the study area.

Table 4. Retention capacity value before and after Merapi Volcano eruption in 2010

	Water Retention Capacity (m ³)		
	Dry	Normal	Wet/Saturated
Before eruption	362,164	480,554	556,643
After eruption	392,837	498,004	560,009

Source: Data Analysis

Increased retention capacity represents the more percolated rain fall in the study area or the less amount of rain becoming effective rainfall. This indicates that lahar flood events occurring post-eruption in the study area is more likely caused by the unstable material so that it is possibly carried as runoff occurs. Lahar flood discharge mainly contents of the material within the lava. The sediment content of debris flow is > 60%, while in hyper-concentrated is 20-60% (Pierson and Costa 1987). Lavigne et al. (2003) also proposed that the content of the sediment in debris flow reaches 73%, while in hyper-concentrated is about 29%.

IV. Conclusions

Based on the results of the analysis conducted on Opak Sub Watershed related to Merapi Volcano eruption in 2012, it can be concluded that:

1. Merapi Volcano Eruption 2010 caused 63% of land use/cover to change into vacant land, and also changes in material and physical boundary of Opak Sub Watershed.

2. Changes in land use/cover and material after the eruption affects water retention capacity in Opak Sub Watershed. This suggests that changes in material affect retention capacity more than those in land use/cover.

V. Reference

- Bondelid TR, McCuen RH and Jackson TJ (1982) Sensitivity of SCS Methods Models to Curve Number Variation. *Journal of the American Water Resources Association*, Vol. 18 (1), pp. 111-116
- Butler D and Davies JW (2011) *Urban Drainage*, Third Edition. Taylor and Francis Group, New York
- Cahyadi A, Yananto A, Wijaya MS and Nugraha H (2012) Analisis Pengaruh Perubahan Penggunaan Lahan terhadap Retensi Potensial Air oleh Tanah pada Kejadian Hujan Sesaat (Studi Kasus Perubahan Penggunaan Lahan di Das Garang Jawa Tengah). *Prosiding Seminar Informatika 2012*. Universitas Pembangunan Veteran, Yogyakarta
- Damardono H (2011) Tata Ruang Masih Disepelekan in Hidayat B (2011) *Bencana Mengancam Indonesia*. Kompas, Jakarta
- Isworo B (2011) Bencana Kebumihan: Kita Tak Semestinya Pasrah in Hidayat B (2011) *Bencana Mengancam Indonesia*. Kompas: Jakarta
- Lavigne L, Tirel A, Le Floch D and Veyrat-Charvillon S (2003) A Real-Time Assessment of Lahar Dynamics and Sediment Load Based On Video-Camera Recording at Semeru Volcano Indonesia in Rickermann and Chen (eds) (2003) *Debris-Flow Hazards Mitigation: Mechanics, Prediction and Assessment*. Millpress, Rotterdam
- Maryono A (2007) *Restorasi Sungai*. Gadjah Mada University Press, Yogyakarta
- McCuen RH (1982) *A Guide to Hydrologic Analysis Using SCS Methods*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey
- Pierson TC and Costa JE (1987) A Rheologic Classification of Subaerial Sediment-Water Flows in Costa JE and Wiczorek GE (eds) (1987) *Debris Flows/ Avalanches: Process, Recognition and Mitigation*. Geological Society of America, USA
- Ragan RM and Jackson TJ (1980) Runoff Synthesis Using Landsat and SCS Model. *Journal of Hydrology, Division. ASCE*, Vol. 106 (HYS5), pp. 667-670
- Slack RB and Welch R (1980) Soil Conservation Service Runoff Curve Number Estimates from Landsat Data. *Bulletin Water Resources*, Vol. 16. pp. 887-893
- Tunggal N (2011) Mengintip Potensi Bencana 2011 in Hidayat B (2011) *Bencana Mengancam Indonesia*. Kompas, Jakarta
- Voight B, Constantine EK, Siswoidjono S, and Torleya R (2000) Historical Eruptions of Merapi Volcano, Central Java, Indonesia, 1768-1998. *Journal of Volcanology and Geothermal Research*. Vol. 100, pp. 69-138