Vernam Encrypted Text in End of File Hiding Steganography Technique

Wirda Fitriani¹, Robbi Rahim², Boni Oktaviana³, Andysah Putera Utama Siahaan⁴

^{1,4}Faculty of Computer Science, Universitas Pembangunan Panca Budi, Medan, Indonesia

²Department of Health Information, Akademi Perrekam Medik dan Infokes Imelda, Medan, Indonesia

³Department of Informatics, Sekolah Tinggi Teknik Harapan, Medan, Indonesia

^{2,4}Student of Universiti Malaysia Perlis, Kangar, Malaysia

Abstract - The concealment of information in the image can be done with some specific techniques. One of the techniques used is End of File. In the insertion of this information, a series of characters will be converted to ASCII code and each byte will be inserted at the end of the RGB image in descending order. The insertion can be done in Red, Green, Blue or on all of them. The downside of this insertion is that if the bits are extracted in sequence, this will produce the original information that has been previously inserted. In large data usage with a limited number of pixels, the stego image will display an oddity. To make the information more secure, an encryption technique needs to be applied. The encryption used is Vernam. This method has very high speed. The data embedded in the image will be more secure.

Keywords - Cryptography, Steganography, End of File

I. INTRODUCTION

End of File is a steganography technique that is often used in color images. This technique has two types of ways, by adding information or byte codes at the end of file or changing the pixel value from the end to the beginning. However, this technique is vulnerable to attack. As long as there are no suspicious signs on the image, the information will remain secure in place. If suspicions arise, the extraction of information sequentially generates byte codes which can then produce the important information. Basically, steganography only aims to hide information from the naked eye [4]. Steganography has absolutely no technique to conceal or encode the information to be incomprehensible. The integration of cryptography and steganography is very important to maintain the balance of information residing in the image. Steganography aims to trick someone's view of certain information. But if the view is already fixed on that information, cryptography will take over to maintain data security [2]. Although the information is successfully extracted, it is hoped that the information remains unintelligible.

II. THEORIES

2.1 End of File

Steganography has many ways to hide information. Steganography takes advantage of the human eye's weakness to process color images [6][7]. Usually, the human eye is not very sensitive to see the color differences in a color image. So the message is invisible or audible [3]. The End of File technique is one of the techniques always used in steganography to store information on color images. Usually, this technique is applied by adding information on end of file or pixel end. The amount of information inserted depends on the size of the image file. The information that can be inserted actually has an unlimited size. However, the image will be easily recognized by someone that there is information in it.

In the End of File technique, there are several methods that can be applied to this model:

- Substitution. Initial data will be replaced with confidential information. This technique does not change the original file size because it only redeems two pieces of data. The downside is the image quality will decrease. The bigger the information, the more visible the image quality difference.
- Transform Domains. In this method, the information will be inserted in the transform space and will be very good if the use of this model is done on the color image
- Spread Spectrum. This is a transmitting technique Information by using pseudo-noise code.

2.2 Vernam Cipher

Cryptography is a method that must be used to secure data. By doing this, important information will be kept confidential [5]. Information can not be avoided from the crime of data theft but information can be secured by messing up its contents so it is difficult to find the contents of the original message [1][8]. Vernam cipher is an encryption method that is done by transforming each bit separately with the other bits. This algorithm uses XOR operation. Every bit in the plaintext will be XOR process with another bit on key. Results from encryption. In the stream cipher, the decryption process is done by re-doing the XOR process between the ciphertext and the key. The key length is the number of bytes on the plaintext row. So the keys are often repeated to produce an equal number of lengths with the number of characters in the plaintext.

Figure 1.XOR process

Figure 1 illustrates the XOR process of the Vernam cipher. Each bit in the plaintext will be transformed to a secret key. To restore, the same process will be done so that it returns plaintext.

III. RESULT AND DISCUSSION

At this stage, it will be tested using a 8 x 8 pixel image. The image will be inserted information that will be first encrypted. Table 1 to 3 show the initial RGB byte.

Table 1. Red byte order

116	48	41	186	180	217	148	212
28	19	215	194	149	170	187	174
51	138	253	68	61	234	165	128
129	228	65	118	102	244	126	216
187	167	185	152	159	216	233	209
160	233	78	163	43	21	9	240
105	104	220	122	157	229	102	161
246	65	181	244	250	253	79	136

Table 2. Green byte order

55	37	203	83	95	0	183	227
159	29	149	170	239	81	85	80
230	4	80	153	19	18	64	209
185	49	208	13	126	120	54	25
100	25	61	213	231	131	159	163
187	118	170	210	194	197	197	120
102	190	243	213	148	11	35	255
238	60	120	174	76	169	190	229

Table 3. Blue byte order

96	158	85	214	122	181	179	165
242	75	241	92	55	110	154	242
143	28	75	167	245	115	216	40
45	176	252	40	235	248	59	38
94	112	242	18	158	240	7	148
48	19	85	212	61	153	9	217
218	207	34	133	172	14	220	2
86	214	225	108	155	141	174	151

Plaintext to be inserted is "UNIVERSE". This text will first be converted to byte code and then encryption process to produce ciphertext. For more, the calculations below will explain everything.

Table 4. Plaintext

U	N	I	V	E	R	S	E
85	78	73	86	69	82	83	69

Table 5. Bit Code of Plaintext

U	85	01010101
N	78	01001110
I	73	01001001
V	86	01010110
E	69	01000101
R	82	01010010
S	83	01010011
E	69	01000101

Table 4 is the byte value of the plaintext while table 5 is the bit value that has been extracted from the plaintext. Every bit will be processed against the secret key. For example, the key is "KEYS". This key only has 4 characters while the number of characters in the plaintext is 8 characters. This resulted in the key being repeated to meet the number of plaintext characters. The key will be "KEYSKEYS" as shown in table 6 and 7.

Table 6. Key

K	E	Y	S	K	E	Y	S
75	69	89	83	75	69	89	83

Table 7. Bit Code of Key

K	75	01001011
E	69	01000101
Y	89	01011001
S	83	01010011
K	75	01001011
E	69	01000101
Y	89	01011001
S	83	01010011

$$\begin{aligned}
 C1 &= P1 \oplus K1 \\
 &= 85 \oplus 75 \\
 &= 01010101 \oplus 01001011 \\
 &= 00011110 \\
 &= 30
 \end{aligned}$$

$$\begin{aligned}
 C2 &= P2 \oplus K2 \\
 &= 78 \oplus 69 \\
 &= 01001110 \oplus 01000101 \\
 &= 00001011 \\
 &= 11
 \end{aligned}$$

$$\begin{aligned}
 C3 &= P3 \oplus K3 \\
 &= 73 \oplus 89 \\
 &= 01001001 \oplus 01011001 \\
 &= 00010000 \\
 &= 16
 \end{aligned}$$

$$\begin{aligned}
 C4 &= P4 \oplus K4 \\
 &= 86 \oplus 83 \\
 &= 01010110 \oplus 01010011 \\
 &= 00000101 \\
 &= 5
 \end{aligned}$$

$$\begin{aligned}
 C5 &= P5 \oplus K5 \\
 &= 69 \oplus 75 \\
 &= 01000101 \oplus 01001011 \\
 &= 00001110 \\
 &= 14
 \end{aligned}$$

$$\begin{aligned}
 C6 &= P6 \oplus K6 \\
 &= 82 \oplus 69 \\
 &= 01010010 \oplus 01000101 \\
 &= 00010111
 \end{aligned}$$

$$= 23$$

$$\begin{aligned} C7 &= P7 \oplus K7 \\ &= 83 \oplus 89 \\ &= 01010011 \oplus 01011001 \\ &= 00001010 \\ &= 10 \end{aligned}$$

$$\begin{aligned} C8 &= P8 \oplus K8 \\ &= 69 \oplus 83 \\ &= 01000101 \oplus 01010011 \\ &= 00010110 \\ &= 22 \end{aligned}$$

The following table is the result of the XOR process performed on both characters. The next process is substituting those values into the pixel table.

Table 8. Encryption result

Byte	Biner
30	00011110
11	00001011
16	00010000
5	00000101
14	00001110
23	00010111
10	00001010
22	00010110

Insertion can be done on Red, Green or Blue. The table below describes the insertion made after the Vernam encryption process is complete.

Table 9. Embedding in Red

116	48	41	186	180	217	148	212
28	19	215	194	149	170	187	174
51	138	253	68	61	234	165	128
129	228	65	118	102	244	126	216
187	167	185	152	159	216	233	209
160	233	78	163	43	21	9	240
105	104	220	122	157	229	102	161
22	10	23	14	5	16	11	30

Table 10. Embedding in Green

55	37	203	83	95	0	183	227
159	29	149	170	239	81	85	80
230	4	80	153	19	18	64	209

185	49	208	13	126	120	54	25
100	25	61	213	231	131	159	163
187	118	170	210	194	197	197	120
102	190	243	213	148	11	35	255
22	10	23	14	5	16	11	30

Table 11. Embedding in Blue

96	158	85	214	122	181	179	165
242	75	241	92	55	110	154	242
143	28	75	167	245	115	216	40
45	176	252	40	235	248	59	38
94	112	242	18	158	240	7	148
48	19	85	212	61	153	9	217
218	207	34	133	172	14	220	2
22	10	23	14	5	16	11	30

Tables 9 to 11 are the result of the End of File steganography process in image pixels. The selection can be done on Red, Green or Blue.

IV. CONCLUSION

The use of cryptography in steganography is very useful to improve data security. The data hidden in the image does not necessarily have protection so that when data can be extracted from the image, very important information will be readable. By applying the Vernam technique, it will create encrypted and incomprehensible messages when successfully retrieved from the image.

REFERENCES

- [1] R. Kumar dan R. C., "Analysis of Diffie Hellman Key Exchange Algorithm with Proposed Key Exchange Algorithm," International Journal of Emerging Trends & Technology in Computer Science, vol. 4, no. 1, pp. 40-43, 2015.
- [2] S. I. Chowdhury, S. A. M. Shohag dan H. Sahid, "A Secured Message Transaction Approach by Dynamic Hill Cipher Generation and Digest Concatenation," International Journal of Computer Applications, vol. 23, no. 9, pp. 25-31, 2011.
- [3] C. Cachin, Digital Steganography, Switzerland: IBM Research, 2005.
- [4] P. K. Y. P. S. M. S. & B. M. Lahane, "Data Security Using Visual Cryptography and Bit Plane Complexity Segmentation," International Journal of Emerging Engineering Research and Technology, vol. 2, no. 8, pp. 40-44, 20 November 2014.
- [5] D. Nofriansyah dan R. Rahim, "Combination of Pixel Value Differencing Algorithm with Caesar Algorithm for Steganography," International Journal of Research In Science & Engineering, vol. 2, no. 6, pp. 153-159, 2016.
- [6] E. Hariyanto dan R. Rahim, "Arnold's Cat Map Algorithm in Digital Image Encryption," International Journal of Science and Research, vol. 5, no. 10, pp. 1363-1365, 2016.
- [7] A. P. U. Siahaan, "RC4 Technique in Visual Cryptography RGB Image Encryption," SSRG International Journal of Computer Science and Engineering, vol. 3, no. 7, pp. 1-6, 2016.
- [8] B. Oktaviana dan A. P. U. Siahaan, "Three-Pass Protocol Implementation in Caesar Cipher Classic Cryptography," IOSR Journal of Computer Engineering, vol. 18, no. 4, pp. 26-29, 2016.