POLARIZATION TRANSFORMER WITH COMBINATION OF DIAPHRAGMS AND PINS

S.I. Piltyay, A.V. Bulashenko, A.P. Saranchuk

Igor Sikorsky Kyiv Polytechnic Institute, Kyiv, Ukraine
 crosspolar@ukr.net, a.bulashenko@kpi.ua, annasaranchuk01@gmail.com

Recently, polarization signal processing has become widespread. It is used in satellite information and telecommunication information processing systems. One of the key elements of such systems are polarization conversion devices. The basic function of such devices is to transform the types of polarization. There are different designs of polarizers. The most common are polarizers in the form of ridged structures [1-2], polarizers with thin metal septum [3-4], polarizers based on irises in the waveguide [5-10] and polarizers based on waveguides with posts [11-12]. There are also designs of polarizers with irises in the form of thin slots [13]. But such constructions are complex. The most broadband and simple design is a waveguide polarizer based on irises.

The 3-D model of the polarizer device is present in Fig. 1.

Figure 1. 3-D model

The design of the waveguide polarizer is shown in Fig. 2. The design contains two irises of height h and thickness w , two posts of height h_p and diameter d , the distance between the iris and the post is l .

Figure 2. Polarizer design

The presented design provides the main polarization characteristics. Cylindrical post provides tuning and matching characteristics by changing the length of the post in the waveguide [14-18].

The matching characteristics of the polarizer are the differential phase shift and the voltage standing wave ratio (VSWR). The polarization characteristics of the polarizer are the axial ratio and the crosspolar discrimination (XPD).

Based on the theory of microwave circuits [19-25], we write the wave matrices of scattering and transmission of our model, breaking it into smaller circuits

$$\begin{aligned} [S_{\Sigma}] &= \begin{bmatrix} S_{\Sigma 11} & S_{\Sigma 12} \\ S_{\Sigma 21} & S_{\Sigma 22} \end{bmatrix} = \frac{1}{T_{\Sigma 11}} \begin{bmatrix} T_{\Sigma 21} & |T| \\ 1 & -T_{\Sigma 12} \end{bmatrix}, \\ [T_{\Sigma}] &= [T_1] \cdot [T_2] \cdot [T_3] \cdot [T_4] \cdot [T_5] = \begin{bmatrix} T_{\Sigma 11} & T_{\Sigma 12} \\ T_{\Sigma 21} & T_{\Sigma 22} \end{bmatrix}, \\ [T_1] &= [T_5] = \begin{bmatrix} T_{11} & T_{12} \\ T_{21} & T_{22} \end{bmatrix}; [T_2] = [T_4] = \begin{bmatrix} e^{j\theta} & 0 \\ 0 & e^{-j\theta} \end{bmatrix}; [T_3] = \frac{1}{2} \begin{bmatrix} 2 + Y_p & -Y_p \\ -Y_p & 2 - Y_p \end{bmatrix}, \end{aligned}$$

where Y_p is the conductivity of the post, θ is electric line length.

Differential phase shift is determined by the expression

$$\Delta\varphi = \varphi_{\Sigma 21.L} - \varphi_{\Sigma 21.C}.$$

VSWR is determined by the formula

$$VSWR = [1 + |S_{11}|] / [1 - |S_{11}|].$$

The axial ratio is determined

$$r = 10 \lg \left(\frac{A^2 + B^2 + \sqrt{A^4 + B^4 + 2A^2B^2 \cos(\Delta\varphi)}}{A^2 + B^2 - \sqrt{A^4 + B^4 + 2A^2B^2 \cos(\Delta\varphi)}} \right),$$

where $A = |S_{\Sigma 21.L}|$, $B = |S_{\Sigma 21.C}|$.

XPD is calculated by the formula

$$XPD = 20 \lg \left(\frac{10^{0.05r} + 1}{10^{0.05r} - 1} \right).$$

Below are the graphs in accordance with the given mathematical model of the polarization device [26-31]. Fig. 3 shows the matching characteristics of the mathematical model, and Fig. 4 shows the polarization characteristics of this model.

Figure 3. Matching characteristics of the mathematical model

Figure 4. Polarization characteristics of the mathematical model

Fig. 3 a demonstrates that the maximum deviation of the differential phase shift from 90° is 2.2° . Fig. 3 b shows that the maximum value of VSWR for both polarizations is 1.41. Fig. 4 a contains the dependence of the axial ratio on the frequency, and Fig. 4 b contains the dependence of the XPD on the frequency. From Fig. 4 we see that at a frequency of 8.5 GHz the axial ratio acquires its maximum value of 0.45 dB. Also at this frequency, the XPD acquires a maximum value of 29 dB.

We will apply software to simulate and optimize the electrodynamic characteristics of the polarizing device [32-37]. Fig. 5 shows the matching characteristics of the polarizer. Fig. 5 a contains the dependence of the differential phase shift on the frequency, and Fig. 5 b contains the dependence of VSWR on the frequency in the operating frequency range from 7.7 GHz to 8.5 GHz of the test prototype.

Figure 5. Matching characteristics of the prototype

Fig. 5a demonstrates that the maximum deviation of the differential phase shift from 90° is 2.2° . Fig. 5 b shows that the maximum value of VSWR for both polarizations is 1.29.

Fig. 6 shows the polarization characteristics of the device in the operating frequency range from 7.7 GHz to 8.5 GHz. Fig. 6 a contains the dependence of the axial ratio on the frequency, and Fig. 6 b contains the dependence of the XPD on the frequency. The figure shows that at a frequency of 8.45 GHz, the axial ratio acquires its maximum value of 0.4 dB. Also at this frequency, the XPD acquires a maximum value of 29 dB.

Figure 6. Polarization characteristics of the prototype

Such characteristics provide the optimal design of the polarizer, which are presented in table 1.

Table 1. Optimal characteristics of the polarizer

<i>a, mm</i>	<i>w, mm</i>	<i>l, mm</i>	<i>h, mm</i>	<i>hp, mm</i>	<i>d, mm</i>
28.9	3.1	5.3	2.60	2.65	2.4

As you can see, the matching and polarization characteristics of the mathematical model and prototype simulated in CST Microwave Studio coincide with the corresponding accuracy.

Thus, the developed device has the following matching and polarization characteristics. The range of change of the differential phase shift is $90^\circ \pm 2.2^\circ$. The polarizer provides VSWR less than 1.29. Axial ratio is less than 0.4 dB. XPD is higher than 29 dB.

References

1. Tribak A. Ultra broadband low axial ratio corrugated quad-ridger polarizer / A. Tribak, A. Mediavilla, J.L. Cano, M. Boussouis, K. Cepero. // *European Microwave Conferences*, Rome, Italy. – October 2009. – pp. 284–287. DOI: <http://doi.org/10.23919/EUMC.2009.5295927>.
2. Pilyay S.I. High performance extended C-band 3.4-4.8 GHz dual circular polarization feed system / S.I. Pilyay. // *XI International Conference on Antenna Theory and Techniques*, Kyiv, Ukraine. – 2017. – pp. 284–287. DOI: <http://doi.org/10.1109/ICATT.2017.7972644>.
3. Dubrovka F.F. Optimum septum polarizer design for various fractional bandwidths / F.F. Dubrovka, S.I. Pilyay, et al. // *Radioelectronics and Communications Systems* – 2020. – Vol. 63, no. 1. – pp. 15-23. <http://doi.org/10.3103/107352720010021>.
4. Dubrovka F. Compact X-band stepped-thickness septum polarizer / F. Dubrovka, S. Pilyay, O. Sushko, et al. // *IEEE Ukrainian Microwave Week*, Kharkiv, Ukraine, September 2020, pp. 135–138. DOI: 10.1109/UkrMW49653.2020.9252583.
5. Pilyay S.I. Waveguide iris polarizers for Ku-band satellite antenna feeds / S.I. Pilyay, A.V. Bulashenko, I.V. Demchenko // *Journal of Nano- and Electronic Physics*. – 2020. – Vol. 12, no. 5. – pp. 05024-1-5. DOI: [http://doi.org/10.21272/jnep.12\(5\).05024](http://doi.org/10.21272/jnep.12(5).05024).
6. Pilyay S.I. Compact polarizers for satellite information systems / S.I. Pilyay, A.V. Bulashenko, I.V. Demchenko // *IEEE International Conference on Problems of Infocommunications. Science and Technology (PIC S&T)*, Kharkiv, Ukraine. – 2020. – pp. 557-562. DOI: 10.1109/PICST51311.2020.9467889.
7. Bulashenko A.V. Waveguide polarizer for radar and satellite systems / A.V. Bulashenko, S.I. Pilyay, Y.I. Kalinichenko, I.V. Zabegalov // *Visnyk NTUU KPI Seriya – Radiotekhnika Radioaparotobuduvannia*. – 2021. – Vol. 86. – pp. 5-13. DOI: 10.20535/RADAP.2021.86.5-13.
8. Pilyay S. I. Analytical synthesis of waveguide iris polarizers / S. I. Pilyay, A. V. Bulashenko, and I. V. Demchenko // *Telecommunications and Radio Engineering*. – 2020. – Vol. 79, no. 18. – pp. 1579–1597. DOI: 10.1615/TelecomRadEng.v79.i18.10.
9. Pilyay S. Development and optimization of microwave guide polarizers using equivalent network method / S. Pilyay, A. Bulashenko, V. Shuliak // *Journal of Electromagnetic Waves and Applications*. – 2021. – Vol. 35, 2021. DOI: 10.1080/09205071.2021.1980913.
10. Pilyay S. Comparative analysis of compact satellite polarizers based on a guide with diaphragms / S. Pilyay, A. Bulashenko, I. Fesyuk, O. Bulashenko // *Advanced Electromagnetics*. – 2021. – Vol. 10, no. 2. – p. 44–55. DOI: 10.7716/aem.v10i2.1713.
11. Zhu Q.C. Reactance of posts in circular waveguide / Q.C. Zhu, A.G. Williamson, M.J. Neve // *IEEE Transactions on Microwave Theory and Techniques*. – 2007. – Vol. 55, No. 8. – pp. 1685-1688. DOI: 10.1109/TMTT.2007.901605.
12. Polishchuk A. Compact posts-based waveguide polarizer for satellite communications and radar systems / A. Polishchuk, A. Bulashenko, S. Pilyay, O. Bulashenko, I. Zabegalov. // *IEEE 3rd Ukraine Conference on Electrical and Computer Engineering*, Lviv, Ukraine, August 2021, pp. 78–83.
13. Kirilenko A.A. A tunable compact polarizer in a circular waveguide / A.A. Kirilenko, S.O. Steshenko, et al. // *IEEE Transactions on Microwave Theory and Techniques*. – 2019. – Vol. 67, No. 2. – pp. 592-596. DOI: [10.1109/TMTT.2018.2881089](https://doi.org/10.1109/TMTT.2018.2881089).

14. Piltay S. Information resources economy in satellite systems based on new microwave polarizers with tunable post / S. Piltay, A. Bulashenko, H. Kushnir, O. Bulashenko // *Path of science*. – 2020. – Vol. 6, no. 11. – pp. 5001-5009. DOI: 10.22178/pos.64-6
15. Bulashenko A.V. Tunable polarizers for X-band radar and telecommunication systems / A.V. Bulashenko, S.I. Piltay, Ye.I. Kalinichenko, O.V. Bulashenko // *KPI Science news*. – 2021. – Vol. 2. – pp. 7–15. DOI: 10.20535/kpissn.2021.2.236953.
16. Bulashenko A.V. Compact waveguide polarizer with three antiphase posts / Bulashenko A.V., Piltay S.I., Kushnir H.S., Bulashenko O.V. // *Visnyk of Vinnytsia Polytechnical Institute*. – 2020. – Vol. 5, pp. 97–104. DOI: 10.31649/1997-9266-2020-152-5-97-104.
17. Bulashenko A.V. Tunable square waveguide polarizer with irises and posts / Bulashenko A.V., Piltay S.I., Kalinichenko Y.I., Bulashenko O.V. // *Technical Engineering*. – 2020. – Vol. 86, No. 2. – pp. 108–116. DOI: 10.26642/ten-2020-2(86)-108-116.
18. Bulashenko A.V. Simulation of compact polarizers for satellite telecommunication systems with the account of thickness of irises / A.V. Bulashenko, S.I. Piltay, I.V. Demchenko // *KPI Science news*. – 2021. – Vol. 1. – pp. 7–15. DOI: 10.20535/kpissn.2021.1.231202.
19. Piltay S. Development and optimization of microwave guide polarizers using equivalent network method / S. Piltay, A. Bulashenko, V. Shuliak // *Journal of Electromagnetic Waves and Applications*. – 2021. – Vol. 35, 2021. DOI: 10.1080/09205071.2021.1980913.
20. Bulashenko A.V. Equivalent microwave circuit technique for waveguide iris polarizers development / A. V. Bulashenko and S. I. Piltay // *Visnyk NTUU KPI Seriya – Radiotekhnika, Radioaparaturbuduvannia*. – Vol. 83, pp. 17–28. – 2020. DOI: 10.20535/RADAP.2020.83.17-28.
21. Bulashenko A. V. Wave matrix technique for waveguide iris polarizers simulation. Theory / A. V. Bulashenko, S. I. Piltay, and I. V. Demchenko // *Journal of Nano- and Electronic Physics*. – 2020. – Vol. 12, no. 6. – pp. 06026-1–06026-5, December 2020. DOI: 10.21272/jnep.12(6).06026.
22. Bulashenko A. Synthesis of waveguide diaphragm polarizers using wave matrix approach / A. Bulashenko, S. Piltay, O. Bykovskiy, O. Bulashenko // *IEEE 3rd Ukraine Conference on Electrical and Computer Engineering*, Lviv, Ukraine, August 2021, pp. 111–116.
23. Piltay S. I. Analytical synthesis of waveguide iris polarizers / S. I. Piltay, A. V. Bulashenko, and I. V. Demchenko // *Telecommunications and Radio Engineering*. – 2020. – Vol. 79, no. 18, pp. 1579–1597, November 2020. DOI: 10.1615/TelecomRadEng.v79.i18.10.
24. Bulashenko A. Analytical technique for iris polarizers development / A. Bulashenko, S. Piltay, and I. Demchenko // *IEEE International Conference on Problems of Infocommunications. Science and Technology (PIC S&T)*, Kharkiv, Ukraine, October 2020, pp. 593–598. DOI: 10.1109/PICST51311.2020.9467981.
25. Dubrovka F.F. Analytical and numerical method of constructive synthesis of optimal polarizers based on three irises in square waveguide / F.F. Dubrovka, A.V. Bulashenko, A.M. Kuprii, S.I. Piltay // *Radioelectronics and Communications Systems*. – 2021. – Vol. 64, no 4. – pp. 204–215. DOI: 10.3103/S073527272104004X.

26. Bulashenko A. Mathematical modeling of iris-post sections for waveguide filters, phase shifters and polarizers / A. Bulashenko, S. Piltyay, Y. Kalinichenko, and O. Bulashenko // IEEE 2nd International Conference on Advanced Trends in Information Theory, Kyiv, Ukraine, November 2020, pp. 330–336. DOI: 10.1109/ATIT50783.2020.9349321.
27. Piltyay S. Analytical modeling and optimization of new Ku-band tunable square waveguide iris-post polarizer / S. Piltyay, A. Bulashenko, O. Sushko, O. Bulashenko, I. Demchenko // International Journal of Numerical Modelling: Electronic Networks, Devices and Fields. – 2021. – Vol. 34, no. 5. – pp. 1–27. DOI: 10.1002/JNM.2890.
28. Bulashenko A.V. Optimization of a polarizer based on a square waveguide with irises / A.V. Bulashenko, S.I. Piltyay, I.V. Demchenko // Science-Based Technologies. – 2020. – Vol. 47, no. 3. – pp. 287–297. DOI: 10.18372/2310-5461.47.14878.
29. Bulashenko A.V. Waveguide polarizer with three irises for antennas of satellite television systems / A.V. Bulashenko, S.I. Piltyay, H.S. Kushnir, O.V. Bulashenko // Science-Based Technologies. – 2021. – Vol. 49, no. 1. – pp. 39–48. DOI: 10.18372/2310-5461.49.15290.
30. Bulashenko A.V. Waveguide polarizer for radar and satellite systems / A.V. Bulashenko, S.I. Piltyay, Y.I. Kalinichenko, I.V. Zabegalov // Visnyk NTUU KPI Seriya – Radiotekhnika Radioaparobuduvannya. – 2021. – Vol. 86. – pp. 5–13. DOI: 10.20535/RADAP.2021.86.5-13.
31. Kushnir H. Multiple reflections method for diaphragms polarizers development / H. Kushnir et al. // IEEE International Conference on Problems of Infocommunications. Science and Technology, Kharkiv, Ukraine, October 2021.
32. S. I. Piltyay, A. V. Bulashenko, and Y. Y. Herhil, “Numerical performance of FEM and FDTD methods for the simulation of waveguide polarizers”, *Visnyk NTUU KPI Seriya – Radiotekhnika Radioaparobuduvannya*, vol. 84, pp. 11–21. March 2021. DOI: 10.20535/RADAP.2021.84.11-21.
33. Piltyay S FDTD and FEM simulation of microwave waveguide polarizers / S. Piltyay, A. Bulashenko, Y. Herhil, O. Bulashenko // IEEE 2nd International Conference on Advanced Trends in Information Theory, Kyiv, Ukraine, November 2020, pp. 357–363. DOI: 10.1109/ATIT50783.2020.9349339.
34. Dubrovka F.F. Optimum septum polarizer design for various fractional bandwidths / F.F. Dubrovka, S.I. Piltyay, et al. // Radioelectronics and Communications Systems – 2020. – Vol. 63, no. 1. – pp. 15–23. <http://doi.org/10.3103/I07352720010021>.
35. Zabegalov I.V. Waveguide feed network for horn antenna with circular polarization / I.V. Zabegalov, Y.E. Sharpan, I.I. Dikhtyaruk, S.I. Piltyay, A.V. Bulashenko // Bulletin of Cherkasy State Technological University. – 2021. – Vol. 1. – pp. 99–113. DOI: 10.24025/2306-4412.1.2021.229924.
36. Piltyay S.I. Compact polarization converter for satellite antenna systems / S.I. Piltyay, A.V. Bulashenko, I.V. Fesyuk, O.V. Bulashenko // Visnyk Cherkaskogo derzhavnogo tehnologichnogo universitetu. – 2021. – Vol. 1. – pp. 86–98. DOI: 10.24025/2306-4412.1.2021.227633.
37. Piltyay S.I. High performance waveguide polarizer for satellite information systems / S.I. Piltyay, A.V. Bulashenko, Ye.I. Kalinichenko, O.V. Bulashenko // Visnyk Cherkaskogo derzhavnogo tehnologichnogo universitetu. – 2020. – Vol. 4. – pp. 14–26. DOI: 10.24025/2306-4412.4.2020.217129.