A Review: Search Visualization with Knuth Morris Pratt Algorithm

Robbi Rahim^{1*}, Iskandar Zulkarnain² and Hendra Jaya³

¹Department of Health Information, Akademi Perekam Medik dan Infokes Imelda, Jl. Bilal Ujung Medan 20116, Indonesia

¹School of Computer and Communication Engineering, Universiti Malaysia Perlis, Malaysia

²Department of Computer System, STMIK Triguna Dharma, Jl. Jenderal Abdul Haris Nasution No.73, Medan 20219, Indonesia

³Department of Computer Engineering, STMIK Triguna Dharma, Jl. Jenderal Abdul Haris Nasution No.73, Medan 20219, Indonesia

*usurobbi85@zoho.com

Abstract. In this research modeled a search process of the Knuth-Morris-Pratt algorithm in the form of easy-to-understand visualization, Knuth-Morris-Pratt algorithm selection because this algorithm is easy to learn and easy to implement into many programming languages.

1. Introduction

Searching is a work that is often performed in everyday life. There are times when we look for something with the purpose of just knowing whether the data is in a set of data or not, while at other times we may want the position of the data sought [1].

A significant difference exists in the string matching algorithm, if in the search process it is not necessary to apply a string matching algorithm to test the data accordingly or not enough using IF logic [1], whereas in the string matching algorithm by default use the search concept to make the process better in terms of string matching [2].

The Knuth-Morris-Pratt (KMP) algorithm is one of the string matching algorithms (pattern) with the examination process from left to right [2] [3] [4] [5], in this research the Knuth-Morris-Pratt algorithm is described in the form of visualization to facilitate the string matching process, Visualization of the Knuth-Morris-Pratt process in this study makes it easy for other researchers to find out how the string matching and searching process works. It is expected that the Knuth-Morris-Pratt algorithm works to facilitate its application to various search processes such as search engines, plagiarism detection and so on.

2. Theory

The Knuth-Morris-Pratt algorithm was developed by D. E. Knuth, along with J. H. Morris and V. R. Pratt [1] [3] [6]. The Knuth-Morris-Pratt algorithm is the development of the previous string search algorithm, the Brute Force algorithm. Brute-Force algorithm is the simplest basic algorithm in solving string matching problem that examines every position in the text between 0 and n-m, where n is the length of text/number of filenames stored on the computer and m is the character length of a pattern (The word to search) [7].

KMP algorithm (Knuth Morris Pratt) is an algorithm used to perform string matching process. This algorithm is a type of Exact String Matching Algorithm which is a precise string

In the KMP algorithm, the information used to do a further shift, not just one character like the Brute Force algorithm. This algorithm performs matching from left to right [5].

Here is the process of applying the Knuth Morris Pratt algorithm to search for a word in a sentence sequence, as for the process as follows:

D	A	E	L	Y	M	M	A	K	R	I	N	A	A	M	R	S	W

R	I	N	A

D	A	E	L	Y	M	M	A	K	R	I	N	A	A	M	R	S	W
R	I	N	A														

D	A	E	L	Y	M	M	A	K	R	I	N	A	A	M	R	S	W
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

R	I	N	A
---	---	---	---

D	A	E	L	Y	M	M	A	K	R	I	N	A	A	M	R	S	W	
			↑															
			R	I	N	A												

Compare pattern P [1] with string S [4], here is the result

Pattern [1] does not match string [4] then the pattern will shift one position to the right.

g. Step Five

Compare pattern P [1] with string S [5], here is the result

Pattern [1] does not match sequence [5] then the pattern will shift one position to the right.

h. Step Six

Compare pattern P [1] with string S [6], here is the result

Pattern [1] does not match sequence [6] then pattern will shift one position to right

i. Step Seven

Compare pattern P [1] with string S [7], here is the result

Pattern [1] does not match string [7] then pattern will move one position to right

j. Step Eight

Compare pattern P [1] with string S [8], here is the result

Pattern [1] does not match sequence [8] then pattern will shift one position to right

k. Step Nine

Compare pattern P [1] with string S [9], here is the result

Pattern [1] does not match string [9] then pattern will move one position to right

1. Step Ten

Compare pattern P [1] with string S [10], here is the result

Pattern [1] matches the string [10]. Because there is a match, the Knuth Morris Pratt algorithm will store this information, and the pattern will not shift and continue matching pattern [2] with string [11].

Pattern [1, 2] matches the string [10, 11]. Because there is a match, the Knuth Morris Pratt algorithm will store this information, and the pattern will not shift and continue matching pattern [3] with string [12].

Pattern [1, 2, and 3] matches the string [10, 11, and 12]. Because there is a match, the Knuth Morris Pratt algorithm will store this information, and the pattern will not shift and continue matching pattern [4] with string [13].

Pattern [4] matches the string [13]. Because there is a match, the Knuth Morris Pratt algorithm will store this information, and the pattern will not shift and continue matching pattern [5] with string [14]. However, since the number of patterns is only four letters, the search will be stopped and the result is that the P pattern matches S-string by 100 percent.

4. Conclusion

The process visualization of the Knuth-Morris-Pratt (KMP) algorithm allows researchers or scholars to learn how the KMP algorithm works, and in the application development it will be easier to create a function for word search and can be implemented into many search processes.

References

- [1] N. R. Dalal and P. Jadhav, "A Composite Algorithm for String Matching," *International Journal of Modern Trends in Engineering and Research (IJMTER)*, vol. 2, no. 7, pp. 68-73, 2015.
- [2] R. Y. Tsarev, A. S. Chernigovskiy, E. A. Tsareva, V. V. Brezitskay, A. Y. Nikiforov and N. A. Smirnov, "Combined string searching algorithm based on Knuth-morris-pratt and Boyer-Moore algorithms," in *XIX International Scientific Conference Reshetnev Readings*, Rusia, 2015.
- [3] I. M. Abu-Zaid and E. K. El-Rayyes, "Parallel Search Using KMP Algorithm in Arabic String," *International Journal of Science and Technology*, vol. 2, no. 7, pp. 427-431, 2012.
- [4] R. Janani and S. Vijayarani, "An Efficient Text Pattern Matching Algorithm for Retrieving Information from Desktop," *Indian Journal of Science and Technology*, vol. 9, no. 43, pp. 1-11, 2016.
- [5] C. S. Rao, K. B. Raju, and S. V. Raju, "Parallel String Matching with Multi-Core Processors - A Comparative Study for Gene Sequences," *Global Journal of Computer Science and Technology Hardware & Computation*, vol. 13, no. 1, pp. 26-41, 2013.
- [6] G. Pandey and G. L. Prajapati, "Applying Bi-Directional Search Strategy in Selected String Matching Algorithms," *International Journal of Computer Applications*, vol. 143, no. 11, pp. 40-43, 2016.
- [7] D. Shapira and A. Daptardar, "Adapting the Knuth–Morris–Pratt algorithm for pattern matching in Huffman encoded texts," *Elsevier: Information Processing and Management*, vol. 42, pp. 429-439, 2006.