QPoweredTarget2DeNovoDrugPropMax : a novel programmatic tool incorporating deep learning and *in silico* methods for automated *de novo* drug design for any target of interest

Ben Geoffrey^{*a}, Rafal Madaj^b, Akhil Sanker^c, Pavan Preetham Valluri^d

^a *Independent Researcher*

^b *Centre of Molecular and Macromolecular Studies, Polish Academy of Sciences, Poland*

^c *SRM University, Tamil Nadu 603203, India*

^d *PSG College of Technology, Coimbatore, India*

*Corresponding author email : bengeof@gmail.com

Abstract

The past decade has seen a surge in the range of application data science, machine learning, deep learning, and AI methods to drug discovery. The presented work involves an assemblage of a variety of AI methods for drug discovery along with the incorporation of *in silico* techniques to provide a holistic tool for automated drug discovery. When drug candidates are required to be identified for a particular drug target of interest, the user is required to provide the tool target signatures in the form of an amino acid sequence or its corresponding nucleotide sequence. The tool collects data registered on PubChem required to perform an automated QSAR and with the validated QSAR model, prediction and drug lead generation are carried out. This protocol we call Target2Drug. This is followed by a protocol we call Target2DeNovoDrug wherein novel molecules with likely activity against the target are generated *de novo* using a generative LSTM model. It is often required in drug discovery that the generated molecules possess certain properties like drug-likeness, and therefore to optimize the generated *de novo* molecules toward the required drug-like property we use a deep learning model called DeepFMPO, and this protocol we call Target2DeNovoDrugPropMax. This is followed by the fast automated AutoDock-Vina based *in silico* modeling and profiling of the interaction of optimized drug leads and the drug target. This is followed by an automated execution of the Molecular Dynamics protocol that is also carried out for the complex identified with the best protein-ligand interaction from the AutoDock- Vina based virtual screening. The results are stored in the working folder of the user. The code is maintained, supported, and provide for use in the following GitHub repository

<https://github.com/bengeof/Target2DeNovoDrugPropMax>

Anticipating the rise in the use of quantum computing and quantum machine learning in drug discovery we use the Penny-lane interface to quantum hardware to turn classical Keras layers used in our machine/deep learning models into a quantum layer and introduce quantum layers into our classical models to produce a quantum-classical machine/deep learning hybrid model of our tool and the code corresponding to the same is provided below

<https://github.com/bengeof/QPoweredTarget2DeNovoDrugPropMax>

Introduction

The past decade has seen a surge in the range of application data science, machine learning, deep learning, and AI methods to drug discovery[1-12]. This greatly enhances the tool set already in offer from the computational era of drug discovery such as in silico modeling [13- 18] and therefore a tool that incorporates the best of what both worlds of computational modeling and AI can offer to drug discovery can greatly help researchers in identifying new drug candidates. The presented work involves an assemblage of a variety of AI methods for drug discovery along with incorporation of in silico techniques to provide a holistic tool for automated drug discovery. When drug candidates are required to be identified for a particular drug target of interest, the user is required to provide the tool target signatures in the form of an amino acid sequence or its corresponding nucleotide sequence. The tool collects PubChem data registered against the target involving experimental activity value(pIC50) of compounds against the target and the molecular descriptors of the compound. With the collected data, the tool performs an automated QSAR and with the validated QSAR model, prediction and drug lead generation are carried out. This is followed by an automated in silico modeling and interaction profiling of the protein-ligand interaction involving the drug target and compounds generated as drug leads. This protocol we call Target2Drug. This is followed by a protocol we call Target2DeNovoDrug. We train a generative recurrent neural network called LSTM Chem with SMILES of compounds with activity against the target. The generative model generates novel molecules that are likely to be active against the target by virtue of the training dataset of the generative model being compounds that are active against the target. This is again followed by an automated fast virtual screen and in silico modeling protocol involving AutoDock-Vina and interaction profiling of the protein-ligand interaction involving the drug target and compounds generated de novo. Further in small drug molecule discovery, it is required that the generated molecules possess certain properties like drug-likeness, and therefore to optimize the generated molecules toward the required property we use a deep learning model called DeepFMPO [21], and this protocol we call Target2DeNovoDrugPropMax. This is followed by the fast automated AutoDock-Vina based in silico modeling and profiling of the interaction of optimized drug leads and the drug target. This is followed by an automated execution of a computationally more expensive Molecular Dynamics protocol that is also carried out for the complex identified with the best protein- ligand from the AutoDock-Vina based virtual screen. The results are stored in the working folder of the user. A demonstrated use of the tool has been shown with the target signatures of Tumor Necrosis Factor-Alpha, an important therapeutic target in the case of anti-

inflammatory treatment. The future scope of the tool involves, running the tool on a High-Performance Cluster for all known target signatures to generate data that will be useful to drive AI and Big data-driven drug discovery

Methods

The algorithmic workflow and architecture of Target2DeNovoDrugPropMax are shown Fig.1 below. The workflow begins with the collection of target signatures in the form of the amino acid sequence of the target or its corresponding nucleotide sequence. The BLAST protocol of Target2Drug identifies targets with identity with the user given target to collect data with linked PubChem data required to perform AutoQSAR(Quantitative Structure-Activity Relationship) based drug lead generation. The data involving the experimental activity (IC₅₀) reported against the target of interest and the molecular descriptors of the active compounds is fetched from PubChem by the program to perform QSAR modeling and prediction. QSAR protocol followed by the program is as follows. It involves establishing a linear and non- linear statistical correlation between experimental activity(pIC₅₀) and molecular descriptors of active compounds. A total of 8 molecular descriptors for each active compound against a target is downloaded from PubChem and a QSAR model is built with all possible combinations and selections of descriptors where $nCr = 256$, $n = 8$ and $r = 2,3,4,5,6,7$. The QSAR model with high statistical quality is chosen for prediction by choosing the QSAR model with R^2 value being close to 1. With the validated QSAR model, the prediction is carried out on all PubChem compounds that are structurally associative to the active compounds and the top 50 compounds are chosen as drug leads. The predicted compounds satisfy the Lipinski's drug likeness criteria. In this way, drug leads from the existing compound library for a given target of interest is generated. To generate drug leads that are novel compounds not present in present ligand libraries we follow the approach of Gupta et. al. [22] that uses a generative LSTM neural network to design drugs *de novo* for a particular target of interest. The SMILES of the PubChem compounds with reported activity against the target is used to train a generative LSTM neural network of Gupta, Anvita et al [22] to generate SMILES of new compounds that are not presently known and registered on PubChem. The newly generated compounds by the generative LSTM neural network are likely to be active against the target of interest as the neural network was trained with SMILES of compounds that are active against the target of interest. Further in small drug molecule discovery, it is required that the generated molecules possess certain properties like

drug-likeness, and therefore to optimize the generated molecules toward the required property we use a deep learning model called DeepFMPO [21]. The de novo generated lead compounds generated from the generative LSTM model of Anvita et al are used as input for the DeepFMPO model. The DeepFMPO model uses an actor-critic reinforcement based learning policy to optimize the structures of the compounds towards drug-likeness. PAINS, BRENK, NIH and ZINC filters are also added to the optimization protocol [23-26]. This is followed by an automated in silico modeling protocol in used to further assess the interaction of the de novo generated drug like molecules and the drug target of interest. To assess the interaction of the target and the lead compounds, the tool performs a fast and computationally cheap and efficient *In Silico* modeling and analysis of the protein-ligand interaction using AutoDock-Vina and stores the results in the working folder. Following this, a computationally more expensive molecular dynamics approach using GROMACS is used to study the protein-ligand interaction and complex formation for the protein-ligand complex associated with the lowest binding energy score from the AutoDock-Vina based virtual screening protocol. Our main program through the 'runGromacs.sh' bash script initiates an automated MD protocol which first identifies the complex with best protein-ligand interaction from the autodock-vina virtual screening using the 'find_best_affinity.py' and generates RMSD(Root Mean Square Deviation), RoG(Radius of Gyration), RMSF(Root Mean Square Fluctuation) plots which reveal the stability of the protein-ligand system based on the Molecular Dynamics simulation carried out for the protein-ligand system using the bash script 'runGromacs.sh'. The ligand parameterization used in the automated MD protocol follows Bernardi et. al. [27] To demonstrate the use of the tool, a demonstrated use has been carried out with the target signatures of Tumor Necrosis Factor-Alpha, a drug target of importance for the anti-inflammatory disease [28]. The code is hosted, maintained, and supported at the GitHub repository given in the link below

<https://github.com/bengeof/Target2DeNovoDrugPropMax>

Anticipating the rise in the use of quantum computing and quantum machine learning in drug discovery [29-31] we use the Penny-lane [32] interface to quantum hardware to turn classical Keras layers used in our machine/deep learning models into a quantum layer and introduce quantum layers into classical models to produce a quantum-classical machine/deep learning hybrid model of our tool and the code corresponding to the same is provided below

<https://github.com/bengeof/QPoweredTarget2DeNovoDrugPropMax>

Fig. 1 – Block diagrammatic representation of the algorithm of the tool

Results and Discussion

The target signature of Tumour Necrosis Factor Alpha was given as input to the tool. The target signature can be identified with NCBI protein ID P01375. The Target2Drug protocol identified data linked with the target on PubChem required to perform AutoQSAR based drug lead generation. The SMILES of the compounds generated as drug leads were used to train the generative LSTM neural network which was used to generate new compounds currently not known and registered on PubChem but are likely to be active against the target. 500 novel SMILES were generated out of which 182 were chemically valid SMILES. The newly Generated SMILES is shown in Fig.2. A computationally cheap and efficient *In Silico* modeling was carried out to model the interaction of the target and PubChem compounds generated as drug leads by the Target2Drug protocol and *de novo* generated SMILES by the deep learning-based *de novo* drug design protocol.

The results of the *In Silico* modelling is given the link below

<https://drive.google.com/drive/folders/1FFXQWPczR5hQfbruTF4YTb7K89wXcY9l?usp=sharing>

The screenshot shows a Jupyter Notebook titled 'Target2DeNovoDrug' with a last checkpoint of 17 hours ago. The interface includes a menu bar (File, Edit, View, Insert, Cell, Kernel, Widgets, Help) and a toolbar with icons for file operations, running cells, and markdown editing. The notebook is running Python 3. The output of cell 42 is a list of 25 SMILES strings, each enclosed in single quotes. These strings represent various chemical structures generated by the model. Below the output, a text label reads: 'Automated In Silico modelling of interaction of the drug target and compounds not registered on PubChem, generated as drug leads by the generative LSTM model'. Cell 34 contains a code block that sets up a docking procedure using MGLTools, specifying a custom SMILES file and a protein preparation path.

```
Print('The Generated SMILES of compounds with drug lead potential')
Generated_Smiles

Out[42]: ['O=C(Cc1ccc(Cl)cn1)c1ccc(Cl)c(S(=O)(=O)N2CCOCC2)c1',
          'COC(=O)c1cccc1C(=O)N1CCN(C2CCc3cccc3S2)CC1',
          'CCC1CCCCC1C(=O)CSC1=NC2=CC=C(C(=O)C3CCCC3)C2=C1',
          'Cc1cccc1NC(=S)NNc1ncc(C(F)(F)F)cc1Cl',
          'COC(=O)c1cccc1C(=O)c1cccc1C(F)(F)F',
          'C0c1ccc(CC(=O)c2cc(C)n(Cc3cccc3)c2C)cc1',
          'C0c1ccc(C(=O)c2cc(C)n(Cc3cccc3)c2)cc1',
          'C0c1cc(-c2cc3cccc3sc2=O)ccc1NC(=O)c1cccc10C',
          'CC(C)(C)c1nn(CCC(=O)Nc2cccc2)c2cccc12',
          'Cc1ccc(C(=O)CNc2ncc(-c3cccc3)s2)cc1',
          'CC(=O)Nc1ccc(C(=O)Nc2ccc(C(F)(F)F)cc2)cc1',
          'Cn1c(=O)c2c(nc(N3CCCC(=O)C3)n2Cc2cccc2)n(C)c1=O',
          'Cc1ccc(S(=O)(=O)Nc2ccc(C(=O)Nc3cccc3C)cc2)cc1',
          'C=CCN1Sc2cc(C(C)C)nnc2NC(=O)c2cccc2S1(=O)=O',
          'CCCCCCC(=O)Nc1cc(-c2ccc(Cl)cc2)cs1',
          'C0c1ccc(NC(=O)c2cccc20c2ccc(C)cc2)cc1',
          'CC(C)(C)Cc1ccc(-c2csc(NC(=O)c3ccc(C(=O)O)cc3)n2)cc1',
          'CC(=O)c1ccc(NC(=O)c2cccc([N+](=O)[O-])c2)cc1',
          'CCN(c1cccc1)S(=O)(=O)c1ccc(C(=O)Nc2ccc3c(c2)OCCO3)cc1',
          'Cc1ccc(-c2ccc(NC(=O)C3CCCC3)cc2)cc1']

Automated In Silico modelling of interaction of the drug target and compounds not registered on PubChem, generated as drug leads by the generative LSTM model

In [34]: """Repeated & modified docking procedure for generated, custom smiles"""
#set preparation pathways
prepare_protein_path = '~/MGLTools-1.5.6/bin/pythonsh ~/MGLTools-1.5.6/MGLToolsPckgs/AutoDockTools/Utilities24/prep'
```

Fig. 2 – *de novo* generated SMILES

A selection of drug lead compounds with Binding Affinity lower than -8 kcal/mol is tabulated and the pymol visualization of the target-compound interaction is shown in Fig.3a, b, c, d, e, 4a, 4b, 4c, 4d & 4e. The binding affinity of the target and PubChem compounds generated as drug leads is tabulated in Table 1 and the *de novo* generated compounds as drug leads are shown in Table 2 and drug like optimized lead compounds are shown in Table 3.

Table 1 – *In Silico* Modelling Target2Drug

S.No.	Ligand (PubChem CIDs)	Target	Binding Energy (Kcal/mol)
1	356283	1a8m	-8.4
2	11547797		-8.1
3	70681601		-8.6
4	129780132		-8.3
5	144048489		-8.4

Table 2 – *In Silico* Modelling Target2DeNovoDrug

S.No.	Ligand (<i>de novo</i> generated SMILES)	Target	Binding Energy (Kcal/mol)
1-SMI	<chem>Cc1cccc(NC(=O)Nc2nc3ccccc3nc2NS(=O)(=O)c2ccccc2)c1</chem>	1a8m	-8.1
2-SMI	<chem>Cc1ccc(NS(=O)(=O)c2ccc(C(=O)NC(=O)c3ccc(C)cc3)cc2)cc1</chem>		-8.1
3-SMI	<chem>Cc1ccc(S(=O)(=O)Nc2cccc(C(F)(F)F)c2)cc1</chem>		-8
4-SMI	<chem>CC(C)CNC(=O)c1ccccc1C(=O)c1ccccc1C(=O)c1cccs1</chem>		-8.3
5-SMI	<chem>O=C(Nc1cccc2cccn12)Nc1cccc2cccn12</chem>		-8

Table 3 – *In Silico* Modelling Target2DeNovoDrugPropMax

S.No.	Ligand (<i>de novo</i> generated SMILES)	Target	Binding Energy (Kcal/mol)
1-SMI OPT	<chem>CSc1cc(N)cnc1-c1cnc(C2CCCCC2)cc1-c1cn2CCN(NC(=O)c3cnccn3)Cc2n1</chem>	1a8m	-8.5
2-SMI OPT	<chem>Cc1cc2ccccc2nc1OC(=O)c1ccc[n+](Br)c1</chem>		-8.3
3-SMI OPT	<chem>Cc1cccc(NC(=O)C(C#N)=Cc2csc(-c3ccc(S(=O)(=O)N4CCNCC4)cc3)n2)c1C</chem>		-8.0
4-SMI OPT	<chem>[C-]#[N+]c1ccc(Sn2c(C)nnc2N)nc1</chem>		-8.0
5-SMI OPT	<chem>[C-]#[N+]c1c(N)ncnc1Nc1cc(O)ccc1C</chem>		-8.1

Fig.3a - Target-compound interaction of the *de novo* generated SMILES 1-SMI

Fig.3b - Target-compound interaction of the *de novo* generated SMILES 2-SMI

Fig.3c - Target-compound interaction of the *de novo* generated SMILES 3-SMI

Fig.3d - Target-compound interaction of the *de novo* generated SMILES 4-SMI

Fig.3e - Target-compound interaction of the *de novo* generated SMILES 5-SMI

Fig.4a - Target-compound interaction of the *de novo* generated SMILES 1-OPT-SMI

Fig.4b - Target-compound interaction of the *de novo* generated SMILES 2-OPT-SMI

Fig.4c - Target-compound interaction of the *de novo* generated SMILES 3-OPT-SMI

Fig.4d - Target-compound interaction of the *de novo* generated SMILES 4-OPT-SMI

Fig.4e - Target-compound interaction of the *de novo* generated SMILES 5-OPT-SMI

The RMSD plot generated from the automated MD protocol of the 'runGromacs.sh' bash script of our tool revealing the stability of complex formation involving the protein-ligand complex associated with the complex with the lowest binding energy value from the virtual screening corresponding to Table 2 and 3 is presented below in Fig.5a and Fig.5b.

Fig.5a – RMSD stabilization of protein-ligand complex associated with the complex of lowest binding energy value

Fig.5b – RMSD stabilization of protein-ligand complex associated with the complex of lowest binding energy value

Thus a demonstrated use of the tool *in silico*-deep learning based *de novo* drug design for a target has been shown.

Conclusion and future outlook

The past decade has seen a surge in the range of application data science, machine learning, deep learning and AI methods to drug discovery. This greatly enhances the tool set already in offer from the computational era of drug discovery such as *in silico* modeling and therefore a tool which incorporates the best of what both worlds of computational modeling and AI can offer to drug discovery can greatly help researchers in identifying new drug candidates. The presented work involves an assemblage of a variety of AI methods for drug discovery along with an incorporation of *in silico* techniques to provide a holistic tool for automated drug discovery. A demonstrated use of the tool has been shown with the target signatures of Tumor Necrosis Factor-Alpha, an important therapeutic target in the case of anti-inflammatory treatment. The future scope of the tool involves, running the tool on a High Performance Cluster for all known target signatures to generate data that will be useful to drive AI and Big data driven drug discovery

References

1. Bajorath, Jürgen, Steven Kearnes, W. Patrick Walters, Nicholas A. Meanwell, Gunda I. Georg, and Shaomeng Wang. "Artificial intelligence in drug discovery: Into the great wide open." (2020): 8651-8652
2. David, Laurianne, Amol Thakkar, Rocío Mercado, and Ola Engkvist. "Molecular representations in AI-driven drug discovery: a review and practical guide." *Journal of Cheminformatics* 12, no. 1 (2020): 1-22.
3. Baskin, Igor I. "The power of deep learning to ligand-based novel drug discovery." *Expert Opinion on Drug Discovery* (2020): 1-10.
4. Smalley, Eric. "AI-powered drug discovery captures pharma interest." (2017): 604.
5. Chan, HC Stephen, Hanbin Shan, Thamani Dahoun, Horst Vogel, and Shuguang Yuan. "Advancing drug discovery via artificial intelligence." *Trends in pharmacological sciences* 40, no. 8 (2019): 592-604.
6. Batool, Maria, Bilal Ahmad, and Sangdun Choi. "A structure-based drug discovery paradigm." *International journal of molecular sciences* 20, no. 11 (2019): 2783.

7. Sellwood, Matthew A., Mohamed Ahmed, Marwin HS Segler, and Nathan Brown. "Artificial intelligence in drug discovery." (2018): 2025-2028.
8. Yang, Xin, Yifei Wang, Ryan Byrne, Gisbert Schneider, and Shengyong Yang. "Concepts of artificial intelligence for computer-assisted drug discovery." *Chemical reviews* 119, no. 18 (2019): 10520-10594.
9. Mak, Kit-Kay, and Mallikarjuna Rao Pichika. "Artificial intelligence in drug development: present status and future prospects." *Drug discovery today* 24, no. 3 (2019): 773-780.
10. Stephenson, Natalie, Emily Shane, Jessica Chase, Jason Rowland, David Ries, Nicola Justice, Jie Zhang, Leong Chan, and Renzhi Cao. "Survey of machine learning techniques in drug discovery." *Current drug metabolism* 20, no. 3 (2019): 185-193.
11. Yang, Yongliang, S. James Adelstein, and Amin I. Kassis. "Target discovery from data mining approaches." *Drug discovery today* 17 (2012): S16-S23.
12. Song, Chun Meng, Shen Jean Lim, and Joo Chuan Tong. "Recent advances in computer-aided drug design." *Briefings in bioinformatics* 10, no. 5 (2009): 579-591.
13. Macalino, Stephani Joy Y., Vijayakumar Gosu, Sunhye Hong, and Sun Choi. "Role of computer-aided drug design in modern drug discovery." *Archives of pharmacal research* 38, no. 9 (2015): 1686-1701.
14. Yu, Wenbo, and Alexander D. MacKerell. "Computer-aided drug design methods." In *Antibiotics*, pp. 85-106. Humana Press, New York, NY, 2017.
15. Taft, Carlton A., and Vinicius Barreto Da Silva. "Current topics in computer-aided drug design." *Journal of pharmaceutical sciences* 97, no. 3 (2008): 1089-1098.
16. Van Drie, John H. "Computer-aided drug design: the next 20 years." *Journal of computer-aided molecular design* 21, no. 10-11 (2007): 591-601.
17. Huang, Hung-Jin, Hsin Wei Yu, Chien-Yu Chen, Chih-Ho Hsu, Hsin-Yi Chen, Kuei-Jen Lee, Fuu-Jen Tsai, and Calvin Yu-Chian Chen. "Current developments of computer-aided drug design." *Journal of the Taiwan Institute of Chemical Engineers* 41, no. 6 (2010): 623-635.
18. Brown, Nathan, Jean Cambruzzi, Peter J. Cox, Mark Davies, James Dunbar, Dean Plumbley, Matthew A. Sellwood et al. "Big data in drug discovery." In *Progress in medicinal chemistry*, vol. 57, pp. 277-356. Elsevier, 2018.
19. Chen, Hongming, Ola Engkvist, Yinhai Wang, Marcus Olivecrona, and Thomas Blaschke. "The rise of deep learning in drug discovery." *Drug discovery today* 23, no. 6 (2018): 1241-1250.

20. Barrett, S. J., and W. B. Langdon. "Advances in the application of machine learning techniques in drug discovery, design and development." In *Applications of Soft Computing*, pp. 99-110. Springer, Berlin, Heidelberg, 2006.
21. Ståhl, Niclas, Goran Falkman, Alexander Karlsson, Gunnar Mathiason, and Jonas Bostrom. "Deep reinforcement learning for multiparameter optimization in de novo drug design." *Journal of chemical information and modeling* 59, no. 7 (2019): 3166-3176.
22. Gupta, Anvita, Alex T. Müller, Berend JH Huisman, Jens A. Fuchs, Petra Schneider, and Gisbert Schneider. "Generative recurrent networks for de novo drug design." *Molecular informatics* 37, no. 1-2 (2018): 1700111.
23. Baell, Jonathan B., and Georgina A. Holloway. "New substructure filters for removal of pan assay interference compounds (PAINS) from screening libraries and for their exclusion in bioassays." *Journal of medicinal chemistry* 53, no. 7 (2010): 2719-2740.
24. Brenk, Ruth, Alessandro Schipani, Daniel James, Agata Krasowski, Ian Hugh Gilbert, Julie Frearson, and Paul Graham Wyatt. "Lessons learnt from assembling screening libraries for drug discovery for neglected diseases." *ChemMedChem* 3, no. 3 (2008): 435.
25. Doveston, Richard G., Paolo Tosatti, Mark Dow, Daniel J. Foley, Ho Yin Li, Amanda J. Campbell, David House, Ian Churcher, Stephen P. Marsden, and Adam Nelson. "A unified lead-oriented synthesis of over fifty molecular scaffolds." *Organic & biomolecular chemistry* 13, no. 3 (2015): 859-865.
26. Zuegg, Johannes, and Matthew A Cooper. "Drug-likeness and increased hydrophobicity of commercially available compound libraries for drug screening." *Current topics in medicinal chemistry* 12, no. 14 (2012): 1500-1513.
27. Bernardi, Austen, Roland Faller, Dirk Reith, and Karl N. Kirschner. "ACPYPE update for nonuniform 1–4 scale factors: Conversion of the GLYCAM06 force field from AMBER to GROMACS." *SoftwareX* 10 (2019): 100241.
28. Strieter, Robert M., STEVEN L. Kunkel, and ROGER C. Bone. "Role of tumor necrosis factor- α in disease states and inflammation." *Critical care medicine* 21, no. 10 Suppl (1993): S447-63.
29. Cross, A., 2018. The IBM Q experience and QISKit open-source quantum computing software. In *APS March Meeting Abstracts* (Vol. 2018, pp. L58-003).
30. Cao, Yudong, Jhonathan Romero, and Alán Aspuru-Guzik. "Potential of quantum computing for drug discovery." *IBM Journal of Research and Development* 62, no. 6 (2018): 6-1.

31. Von Lilienfeld, O. Anatole. "Quantum machine learning in chemical compound space." *Angewandte Chemie International Edition* 57, no. 16 (2018): 4164-4169.
32. Bergholm, V., Izaac, J., Schuld, M., Gogolin, C., Alam, M.S., Ahmed, S., Arrazola, J.M., Blank, C., Delgado, A., Jahangiri, S. and McKiernan, K., 2018. PennyLane: Automatic differentiation of hybrid quantum-classical computations. arXiv preprint arXiv:1811.04968