Traffic accidents and delays present contrasting pictures of traffic resilience to coastal flooding in the San Francisco Bay Area

Indraneel Kasmalkar^{1,*} and Jenny Suckale^{1,2,3}

¹Institute for Computational and Mathematical Engineering, Stanford University, Stanford, California, USA – 94305.

²Department of Geophysics, Stanford University, Stanford, California, USA – 94305.

³Department of Civil and Environmental Engineering, Stanford University, Stanford, California, USA – 94305.

*Corresponding author (ineel@stanford.edu)

Keywords: coastal flooding, transportation, resilience, traffic accidents, sea level rise

Abstract

Climate change is intensifying coastal floods and increasing the risks of traffic disruption in low-lying, coastal communities. Efforts to understand the differential impacts of traffic disruption on communities have led to the concept of traffic resilience which captures the degree to which a traffic system can recover from disruption. Existing proxies of traffic resilience are focused on quantifying travel time delays but lack the important dimension of road safety. In this study, we quantify traffic resilience in terms of the change in non-highway car and pedestrian accident rates during the 5–10 am period as a result of coastal flooding in the San Francisco Bay Area for the 2020–2040 period. We use a regional traffic model to simulate traffic patterns under a range of coastal flood water levels. We use regressions that relate traffic volumes to historical accident rates to estimate accidents rates in the presence of flooding. Our results show that the flooding of highways forces commuters onto local roads passing through residential communities, causing a spike in accident rates. Unlike delays which increase sharply at the higher water levels considered in this study, we project that region-wide peak-hour accident rates may increase substantially at lower water levels.

1 Introduction

A rising sea level and intensifying storms are causing more frequent and more intense coastal flood events, impacting communities in low-lying coastal regions [1]. The disruptions associated with coastal flooding come at a time of unprecedented population growth and wide-spread urbanization, especially in coastal regions [2, 3, 4]. As a result, coastal flooding can trigger spatially extensive impacts on dense, urban regions by disrupting highly interdependent and interconnected urban systems such as transportation [5].

Many metropolitan areas across the world experience high traffic congestion, indicating that urban transportation systems are already stressed [6]. Under these conditions, a relatively small change in traffic flow can trigger spatially extensive disruption because traffic systems are highly non-linear [7]. As demonstrated in prior studies, the closure of even a small percentage of roads, from flooding or otherwise, can propagate congestion throughout the network, leading to region-wide travel time delays [8, 5].

Traffic resilience is defined as the ability of the system to withstand traffic disruption, and has been previously estimated in terms of travel time delays [8, 5]. In particular, the study by Kasmalkar et al. [5]

suggests that areas with dense road networks are more resilient to flood-related travel time delays because they have sufficient alternate road capacity to offset potential increases in traffic volumes. However, solely using the metric of travel time delay for estimating traffic resilience could impart a bias toward travel efficiency rather than road safety into planning efforts. For example, residential communities, especially traditionally disadvantaged communities with limited road-safety measures such as speed bumps, might be more concerned about the risk of accidents on local streets rather than travel time delays.

In this study, we quantify traffic resilience in terms of the change in the rates of non-highway car and pedestrian accidents during the morning commute hours as a result of coastal flooding in the San Francisco Bay Area for the 2020–2040 period. A coastal flood event is defined as an extreme water level that can result from multiple potential combinations of storm surges, tides, seasonal cycles, inter-annual anomalies driven by large-scale climate variability such as the El Niño Southern Oscillation, and near-future sea level rise. Our study is the result of an ongoing stakeholder-engagement process as part of the Stanford Future Bay Initiative and inspired specifically by community members of North Fair Oaks, California, who have highlighted concerns around road safety arising from the large volume of traffic that cuts through their neighborhoods when the nearby highway US-101 is congested. Given these concerns, we choose non-highway car and pedestrian accident rates as proxies for road safety since these two types of accidents pose direct risks to individuals and property within a specific community.

Prior studies show that socioeconomic characteristics have a substantial influence on accident rate [9, 10, 11, 12]. The San Francisco Bay Area is highly spatially heterogeneous in its socioeconomic characteristics, suggesting that accident rates might be spatially heterogeneous, too. For example, the neighboring cities of Palo Alto and East Palo Alto have markedly different median household incomes, ethnic composition, and educational levels [13]. To represent the role of socioeconomic characteristics on accident rates, prior studies use regressions with a variety of socioeconomic variables [9, 10, 11, 12], but this approach may overfit data since many socioeconomic variables such as education and income are correlated. Our study, on the other hand, precedes the regression analysis with a clustering approach [14, 15] to aggregate proximal census blocks with similar median household incomes and free flow travel speeds into contiguous areas, called communities. Clustering reduces the variability in the socioeconomic and road variables within individual communities, allowing us to relate accident rate to the average values of the variables for each community.

Socioeconomic characteristics are not the only variables that affect the accident rates of communities. Traffic volume is important as well, especially in dynamic metropolitan areas where traffic conditions change substantially from hour to hour [16]. A majority of highway accident studies show either a linearly increasing or a U-shaped profile for the relationship between accident rate and traffic volume [17, 18, 16]. The relationship has not been studied as extensively for car accidents in urban and suburban settings. One observational study monitoring 120 signal intersections in Adelaide, Australia found that car accident counts increase with hourly traffic volumes, with an especially sharp increase at very high traffic volumes [19]. For pedestrian accidents, empirical studies have limited temporal resolution, but existing work suggests that annual accident rates correlate with average annual traffic volumes in an approximately linear way [20, 9].

Accident rates may depend on multiple factors other than traffic volume and socioeconomic characteristics, including road safety precautions, driver age, and pedestrian volume [20, 21, 9, 16]. However, we assume that over the hourly time scales at which we conduct our analysis of flood-related accident rates and at the spatial scale of communities, variables other than traffic volume remain constant. Our analysis, therefore, estimates accident rate as a function of traffic volume for each community, and assumes that the underlying relationship is approximately representative of the near-future, defined here as the 2020-2040 period.

Given the relationship between accident rate and traffic volume, our study characterizes the impacts of coastal flooding on accident rate as follows: coastal floodwater inundates low-lying roads and makes them inaccessible, which alters regional traffic volumes by forcing commuters onto alternate roads, subsequently changing accident rates for communities. Flooding, however, also alters accident rates more directly by forcing some commuters to drive in wet road conditions, putting them at risk of hydroplaning [22]. Our study does not consider accidents caused by driving in wet road conditions because a very small proportion of road segments in the San Francisco Bay Area are projected to be flooded in a coastal flood event [5], indicating that the exposure to wet road conditions is geographically limited. Thus, our study complements

previous studies of accidents caused by wet road conditions [23, 24, 25] by estimating the spatially extensive changes in traffic volumes and the subsequent changes in accident rates resulting from flooding.

To estimate flood-related accident rates, we use historical accident data over the period 2013–2019 from the Statewide Integrated Traffic Records System (SWITRS) [26] to derive hourly non-highway car and pedestrian accident rates for each community for the five time periods 5–6 am, 6–7 am, 7–8 am, 8–9 am, and 9–10 am. We then simulate morning traffic patterns in the San Francisco Bay Area, both in the presence and absence of flooding, using an incremental traffic assignment model [5]. We derive regressions from the hourly trends in modeled traffic volumes and historical accident rates over the weekday 5–10 am time period, and use the regressions to estimate accidents rates in the presence of flooding.

2 Model

2.1 Dividing the region into communities

Census blocks provide an initial basis for partitioning the San Francisco Bay Area [27]. However, many census blocks have zero reported accidents for the 5–10 am time period studied here, because of their relatively small sizes. We use k-means clustering to aggregate geographically proximal census blocks with similar median household incomes and mean free flow travel speeds into larger contiguous areas, called communities. Free flow travel refers to the condition of a car traveling on a road segment in the absence of congestion or other adverse driving conditions. We estimate free flow travel speeds over road segments from the San Francisco Bay Area Metropolitan Transportation Commission’s regional road network [28] and average them at the scale of census blocks. We obtain the median household income values for census blocks from the American Community Survey [13]. By clustering census blocks, we partition the San Francisco Bay Area into a total of 72 communities, shown in Fig. 1. The spatial extents of communities are large enough to have non-zero car and pedestrian accident counts, yet small enough to reflect the spatial heterogeneity in socioeconomic and road characteristics of the region.

2.2 Simulating traffic patterns with flooding

We use the traffic model developed by Kasmalkar et al. [5] to simulate traffic patterns in the San Francisco Bay Area. The traffic model uses two inputs, namely, the San Francisco Bay Area Metropolitan Transportation Commission’s road network, shown in Fig. 1B [29], and the Longitudinal Employer–Household Dynamics Origin–Destination Employment Statistics (LODES) dataset [30] which provides home–work location pairs for commuters at the census block level. To assign commuters to their home-to-work routes, the model uses an incremental traffic assignment algorithm which partitions the set of commuters in the LODES dataset uniformly and proportionally into batches of size 40%, 30%, 20%, and 10%, and sequentially assigns the commuters to their shortest routes one batch at a time [31, 32].

The traffic model uses an empirical function which estimates how travel time changes with traffic volumes for individual road segments [33, 34],

$$t = t_0 (1 + \alpha(V/C)^\beta), \quad (1)$$

where t is the travel time for a given road segment, t_0 is the free flow travel time for the road segment, V and C are the traffic volume and capacity of the road segment, measured in cars/hr, and α and β are parameters. In this study, we set these parameters to $\alpha = 0.2$ and $\beta = 6.0$, as suggested by the Metropolitan Transportation Commission [29]. We impose 80 miles/hr and 5 miles/hr as the respective upper and lower bounds on the travel speeds for each road segment. We only consider private cars and do not account for public transit [5]. We also neglect traffic signals, stop signs, tolls, or carpool lanes, and do not account for travel time delays resulting from accidents.

The traffic model by Kasmalkar et al. [5] simulates traffic patterns over the time period of a single hour, but our analysis of accident rates requires traffic simulations that span the entire time period of 5–10 am. Traffic flow over multiple hours may exhibit the potential temporal spillover of traffic, where, for example, traffic congestion during the 8–9 am time period may impact the traffic patterns over the 9–10 am

Figure 1: The San Francisco Bay Area. (A) We divide the San Francisco Bay Area into 72 communities. The cities of Napa, Oakland, San Francisco (labeled SF), San Jose, and Santa Rosa are shown for reference. (B) The regional road network with highways shown in brown. We consider any numbered road to be a highway. (C, D) The flood map and projected road closures for the 12- and 36-inch water levels, respectively.

time period. To capture the temporal spillover of traffic, we modify the model so that commuters whose travel times exceed one hour are retained in the simulation over the successive hour. For example, if 1000 commuters traveling on a particular road segment in the 7–8 am time period have travel times that exceed one hour, then the simulation for the 8–9 am time period is initiated with a traffic volume of 1000 on that road segment. We estimate the number of commuters initiating their commute in each hour of the 5–10 am

time period from the American Community Survey (see Table 1).

To identify roads within the traffic system that may be closed as a result of coastal flooding, we use the method of Kasmalkar et al. [5] where we overlay coastal flood maps on the road network, correct for potential biases in road geometry, elevation, and representations of road-creek crossings, and close down road segments with more than 3 inches of water at any point along their extents. Similar to [5], we use the San Francisco Bay Department of Conservation and Development Commission’s Adapting to Rising Tides (ART) flood maps, which represent extreme water levels resulting from multiple potential combinations of storm surges, tides, seasonal cycles, inter-annual anomalies driven by large-scale climate variability such as the El Niño Southern Oscillation, and near-future sea level rise [35]. For example, the 36-inch water level flood map can represent both a 50-yr return period coastal flood at present-day sea level, as well as a 20-yr coastal flood on top of 6 inches of sea level rise [35, 5]. Our study considers the ART flood maps corresponding to the 12-, 24-, and 36-inch water levels. The 12- and 36-inch flood maps are shown in Figs. 1C and D.

2.3 Deriving the statistical relationship between traffic volume and accident rate

The Statewide Integrated Traffic Records System is a standardized platform used by the California Highway Patrol and its allied agencies for collecting and storing geolocated car and pedestrian collision reports across the State of California [26]. From the records system, we select non-highway car and pedestrian accidents within the nine counties of the San Francisco Bay Area and during the weekday 5–10 am period over January 2013–December 2019. Highways are defined as roads with officially designated numbers (see Fig. 1B). We map the accident locations to the respective communities in which they occur, sum over the number of accidents, and divide by the total number of working days over the 2013–2019 period to get the historical hourly non-highway car and pedestrian accident rates for each community for each of the five hours. We only consider communities with accident data in at least four out of the five individual hours in the 5–10 am period to ensure at least four data points for our regression analysis. Therefore, we remove communities where accident data is unavailable for more than one out of the five hours from our analysis. Of the 72 original communities, 64 communities have sufficient data for our analysis of non-highway car accidents (Fig. 1A) and 45 communities have sufficient data for our analysis of pedestrian accidents.

We compute the average non-highway traffic volume of a community by averaging the traffic volumes of all the non-numbered road segments intersecting the geographical extent of the community while weighting each road segment by its length. Since our analysis does not include accidents caused directly by wet road conditions, we only include non-flooded road segments when computing average traffic volumes. For each community, and for both non-highway car and pedestrian accidents, we use linear and quadratic regressions to fit curves through the points determined by average non-highway traffic volumes and the hourly non-highway accident rates without flooding for each of the five hours in the 5–10 am period. The choice of linear and quadratic regressions is motivated by their relative simplicity, as well as prior empirical studies that find these two relationships most commonly between accident rates and traffic volumes [16]. Between the linear and quadratic regression curves, we select the one with the higher adjusted R^2 coefficient. We then use the selected regression curve for each community to estimate the likely accident rate based on the traffic volumes projected for the 12-, 24-, and 36-inch water levels.

Since our model does not analyze highway accidents, we use the term “accidents” to refer to non-highway accidents from this point onward. Similarly, we use the term “traffic volumes” to refer to traffic volumes on non-highway roads only.

3 Validation of model travel times

In our regression analysis, we relate historical accident rates to computed traffic volumes. The validity of this approach hinges on the accuracy of the model and raises the question of potential biases that could be introduced by the model being more accurate in some time periods than in others. We compare computed travel times in the absence of flooding against historical travel times provided by the TomTom routing

Figure 2: Comparing model travel times against TomTom estimates. (A, B) Histograms over all segments in the model road network for differences in TomTom and model travel times for 6–7 am and 8–9 am, respectively. (C, D) Histograms over all 72 communities for differences in average TomTom and model travel times for 6–7 am and 8–9 am, respectively.

system [36]. The TomTom routing system uses historical Geographical Positioning System–based travel data to estimate the average travel time for a given origin–destination pair at a given time of departure [36]. In Figs. 2A and B, we plot histograms of the differences in travel times computed by our traffic model and those estimated by TomTom over all road segments in our road network. We present the results for the 6–7 am time period, which is representative of the non-peak hour traffic (5–7 am), and the 8–9 am time period, which is representative of peak hour traffic (7–10 am). The histograms for both the 6–7 am and 8–9 am time periods have means less than 2.5 minutes and standard deviations less than 3.5 minutes. The histograms show skewed distributions, indicating larger travel times for TomTom than for our traffic model. The histograms for the other three hours show similar results (see Fig. C.1).

While Figs. 2A and B compare TomTom and model travel times at the scale of individual road segments, the focus of our study lies at the scale of communities. To identify potential systematic biases in travel times at the community scale, we plot the histograms of the differences in TomTom and model travel times averaged across communities in Figs. 2C and D. We compute the average travel time for a given community by summing the travel times of all the road segments intersecting the community and dividing by the sum of the lengths of the road segments. The normalization by road segment length provides a meaningful comparison across communities of different sizes. The panels C and D show single-peak distributions of average travel times for the 6–7 am and 8–9 am time periods respectively, where the latter has a more pronounced peak. Both the distributions have averages of approximately 3.2 minutes per mile, and standard distributions of approximately 1.4 minutes per mile.

All the histograms in Fig. 2 show larger travel times for TomTom than for our model, a consequence of the optimal travel conditions assumed in our model. Our road network contains simplified road segments that do not correspond to real roads [29], thus providing slightly shorter routes for commutes. Our model also does not consider travel time delays caused by adverse road conditions such as constructions sites or accident locations.

To demonstrate that the difference between TomTom and model travel times has a small, uniform, and systematic bias, we subtract 3 minutes per mile for each road segment from the TomTom travel times and plot the altered histograms in Fig. 3. The histograms show approximately symmetric distributions centered at 0, indicating a reduction of the bias. We do not make any adjustments for the bias when performing the regression analyses in this study.

Figure 3: Adjusted histograms for the differences in TomTom and model travel times. The differences are adjusted by 3 mins/mile. (A, B) Histograms over all segments in the model road network for differences in TomTom and model travel times for 6–7 am and 8–9 am, respectively. (C, D) Histograms over all 72 communities for differences in average TomTom and model travel times for 6–7 am and 8–9 am, respectively.

Figure 4: The relative standard deviation of traffic volumes for communities over each time period. Each point corresponds to a community for a given hour.

4 Aleatoric uncertainty in modeled traffic volumes

Incremental traffic models compute traffic volumes by optimizing travel times across the road network [33, 34]. Our model relates travel time to traffic volume using power-law functions involving two parameters, α and β , as seen in Eqn. (1). There is, however, considerable uncertainty in the parameters. Our model follows the choices of the San Francisco Bay Area Metropolitan Transportation Commission, $\alpha = 0.2$ and $\beta = 6.0$ [29]. Prior studies of hazard-related traffic disruption have used different values, e.g., $\alpha = 0.15$ and $\beta = 4.0$ [37, 5]. Some studies report a range of values, with $0.1 < \alpha < 0.4$ and $4.0 < \beta < 6.0$ [34, 38], while others present even wider ranges [39].

To estimate the aleatoric uncertainty in modeled traffic volumes, we conduct 20 traffic simulations, with $\alpha = 0.15, 0.3, 0.5, 0.7$ and $\beta = 4.0, 4.5, 5.0, 5.5, 6.0$. For each of the 72 communities, we compute the relative standard deviation of the average traffic volumes computed for the range of values of α and β for a given hour. We plot the results in Fig. 4, where each point represents the relative standard deviation of traffic volume for a given community over a given hour. The figure show that the relative standard deviation values of the communities range from 0–80%. For each community, the relative standard deviation is the smallest for the 5–6 am time period, when congestion is relatively low and most cars travel under free flow conditions. On the other hand, the relative standard deviation is largest for the 9–10 am time period for almost all communities. Most of the traffic in the 9–10 am time period consists of the congested traffic that initiated its commute in the prior time periods (see Table 1). Our results suggest that the modeled volumes of the congested traffic from prior time periods are highly sensitive to the choice of parameters, resulting in large standard deviation values during the 9–10 am time period.

We account for the aleatoric uncertainty in traffic volumes by using the relative standard deviation values to construct 95% confidence intervals around the modeled traffic volumes ($\alpha = 0.2, \beta = 6.0$) for each community.

Figure 5: Regression curves of traffic volumes and non-highway car accident rates for 4 communities, shown in panels A, B, C and D. Black dots indicate historical car accident rates with modeled traffic volumes. The blue curves represent the best-fitting linear regressions and the orange curves represent the best-fitting quadratic regressions. The adjusted R^2 coefficients for the respective regressions are shown in parentheses in the legend. (E) Locations of the four communities.

5 Results

5.1 Accident rates increase with traffic volumes for most communities

To constrain the relationship between accident rates and traffic volumes, we compute the corresponding linear and quadratic regression curves for each community. We estimate the average traffic volumes from the model described in Section 2 and obtain the accident rates from the accident records system [26]. We show the regression curves of four example communities in Fig. 5. We compute the vertical errors bands

representing the 95% confidence intervals from the standard errors of the underlying least squares regressions. We compute the horizontal error bars representing the 95% confidence intervals from the relative standard deviations of the modeled traffic volumes (Fig. 4). The largest traffic volumes correspond to the 8–9 am time period (Table 1). The largest confidence intervals for traffic volumes correspond to the 9–10 am time period, a consequence of the high uncertainty in modeled traffic volumes for the relatively large temporal spillover of traffic from prior time periods (Fig. 4).

For each community, we choose either the linear or the quadratic regression based on the higher adjusted R^2 coefficient. Panel A of Fig. 5 shows a community near the city of Hayward, California with five data points of car accident rates and traffic volumes. We choose the linear regression because it has a higher adjusted R^2 coefficient (adj. $R^2 = 0.89$) than for the quadratic regression (adj. $R^2 = 0.88$). In panel B, which shows a community near the city of Santa Rosa, the quadratic regression is chosen instead. Panel C, representing a community in San Francisco City shows near-identical linear and quadratic regression curves. The latter has a lower adjusted R^2 coefficient since it provides a similar fit despite using a higher degree polynomial. In panel D, which shows a community in the city of San Jose, the linear regression has an increasing trend while the quadratic regression has the shape of an inverted U, where we select the latter for its higher adjusted R^2 coefficient.

Figure 6: Spatial distribution of the regression curves for non-highway car accident rates and traffic volumes. (A) Profile of the quadratic regression, either U-shaped, inverted U-shaped, or linearly increasing. (B) The R^2 coefficients. We remove the 3 striped communities from the analysis because of their low R^2 coefficients.

Fig. 6A summarizes our model choices of regression curves for all communities in the San Francisco Bay Area. Among the 64 communities with sufficient car accident data, 40 have increasing linear profiles, 10 have U-shaped quadratic profiles and 14 have inverted U-shaped profiles. Although linear and U-shaped profiles are found most commonly in prior studies [18, 16], there is some evidence for inverted U-shaped profiles in prior studies [40, 41]. Overall, our results suggest that most communities have an increasing relationship between car accident rates and traffic volumes.

The fit between the chosen regression curves and the relationship between observed car accident rates

and modeled traffic volumes also vary spatially, as demonstrated by the R^2 coefficients for each community in Fig. 6B. Of the 64 communities with sufficient car accident data, 34 have R^2 coefficients of 0.9 or higher, and 3 have coefficients lower than 0.5. We discard the 3 communities with R^2 coefficients lower than 0.5 from our car accident analysis, because we are unable to identify a relationship between car accident rates and traffic volumes for these.

The spatial distributions of the profiles and the R^2 coefficients depend on the clustering used to partition the region into communities. To understand the degree to which clustering affects the distributions in Fig. 6, we present results for two alternate clusters in the Appendix, Fig. D.1. The two alternate clusters represent opposing end members of clustering, where one prioritizes the proximity of census blocks, while the other prioritizes similar median household incomes and free flow travel speeds over proximity. Comparing Figs. 6 and D.1, we note that most communities have linearly increasing relationships between accident rates and traffic volumes for both the original and alternate clustering approaches. For the majority of communities, the different clustering approaches suggest similar profiles, but there are prominent exceptions. For example, communities around San Francisco City have a mix of linearly increasing and inverted U-shaped profiles which change with the specific clustering approach. The choice of the clustering approach affects the profiles assigned to communities on the cusp of different behavior, such as a switching a linear profile to either a mildly U-shaped or inverted U-shaped profile. The spatial distributions of R^2 coefficients are also approximately similar at the regional scale for the various clustering approaches. Overall, our analysis suggests that the choice of the clustering approach may alter our results at the community scale, particularly in places like San Francisco City, but has limited impact on our results at larger spatial scales.

Figure 7: Regression curves of traffic volumes and pedestrian accident rates for the 4 communities shown in Fig. 5E. The adjusted R^2 coefficients for the respective regressions are shown in parentheses in the legend.

We perform a similar analysis for pedestrian accident rates. In Fig. 7, we show the regression curves between pedestrian accident rates and traffic volumes for the four communities shown in Fig. 7E. Similar to the case for car accident rates, the linear regression curves for pedestrian accidents are increasing in all four panels. We choose a regression model based on the same rationale of higher adjusted R^2 coefficients as for car accidents. We find that the selected regression profiles for the car accident rates, linear versus quadratic, do not necessarily resemble the regression profiles for the pedestrian accident rates. Our results suggest that the dynamics for car accidents are notably different from those of pedestrian accidents in the San Francisco Bay Area.

Figure 8: Spatial distribution of the regression curves for pedestrian accident rates and traffic volumes. (A) Profile of the quadratic regression, either U-shaped, inverted U-shaped, or linearly increasing. (B) The R^2 coefficients. We remove the 7 striped communities from the analysis because of their low R^2 coefficients.

We present the distributions of the profiles and R^2 coefficients of the regression curves for the pedestrian accident rates in Fig. 8. Out of the 45 communities which have sufficient pedestrian accident data, 24 have a linearly increasing profile, 10 have a quadratic U-shaped profile, and 11 has an inverted U-shaped profile (panel A). There are 16 communities with R^2 coefficients greater than 0.9. There are 7 communities with R^2 coefficients lower than 0.5, which we remove from our pedestrian accident analysis.

The Figs. 6 and 8 show that most communities have increasing relationships between accident rates and traffic volumes, which is consistent with prior studies [16]. The figures also show that there is considerable variability between the regression curves across the various communities. The underlying heterogeneity of the region contributes to the variability in the regression curves between accident rates and traffic volumes. Communities may differ substantially in socioeconomic conditions, driving norms, traffic infrastructure, and accident reporting, all of which influence car and pedestrian accident rates [9, 11, 16].

5.2 Flooding exacerbates peak-hour accident rates

Coastal flood events have the potential to prompt the closure of low-lying roads in the San Francisco Bay Area, subsequently disrupting regional traffic patterns. To estimate changes in accident rates as a consequence of flood-related changes in traffic volumes, we use the regression curves from Section 5.1 with modeled traffic volumes in the presence of flooding.

To establish baseline accident rates, we first compute the car accidents rates without flooding for each community and plot the results for the 6–7 am and 8–9 am time periods in Fig. 9. An accident rate of 0.05 accidents/hr in the 6–7 am time period means that there is one accident approximately every 20 days in the 6–7 am time period. Panels A and B are representative of the spatial distribution of non-peak hour (5–7 am) and peak hour (7–10 am) accident rates, respectively. During the 6–7 am time period, most of the communities with relatively high car accident rates are located in the southern Bay (0.05 – 0.1 accidents/hr).

Figure 9: Computed non-highway car accident rates without flooding, by community. (A) 6–7 am time period. (B) 8–9 am time period. Of the 72 communities, 8 are removed for lack of accident data, and 3 are removed for having R^2 regression coefficients less than 0.5.

With the exception of one community near the city of Santa Rosa, the northern communities have relatively low accident rates (< 0.01 accidents/hr). Most communities have higher car accident rates in the 8–9 am time period than in the 6–7 am time period (Fig. 9B). Communities in the eastern and southwestern region (Fig. 1A), especially those around the cities of Oakland and San Jose, have the highest increases in accident rates during peak hours.

To estimate how accident rates change with flooding, we assume that flooded roads are closed to traffic (Fig. 1), simulate traffic patterns, and use the regression curves to estimate accident rates for communities. Our results in Fig. 10 show that, for most communities, car accident rates with flooding are higher than those without flooding (Fig. 9). Relative to the baseline, the 6–7 am car accident rates increase the most for southwestern and eastern communities, especially those around the cities of Oakland and San Jose. The 6–7 am accident rates are approximately similar for the two water levels, 12 and 36 inches (Figs. 10A and C).

For the 8–9 am time period, the car accident rates for both the 12– (Fig. 10B) and 36–inch water levels (Fig. 10D) increase substantially as compared to the 6–7 am time period. The increases are higher for the 36–inch water level, especially in communities around the cities of Napa, San Jose, and Santa Rosa. The increase in car accident rates from 6–7 am to 8–9 am is substantially greater in the presence of flooding (Fig. 10) than in the absence (Fig. 9), suggesting that flooding exacerbates peak-hour accident rates.

We conduct a similar analysis for pedestrian accident rates. In Fig. 11, we plot the pedestrian accident rates without flooding. The pedestrian accident rates are very low (< 0.01 accidents/hr) for most communities. Most of the pedestrian accidents are concentrated in the communities around the cities of Oakland, San Francisco, and San Jose. We show the pedestrian accident rates with flooding in Fig. 12. Relative to the baseline rates, the 6–7 am rates increase slightly with flooding, where the increases occur in the communities around the cities of Oakland, San Francisco, and San Jose. Similar to the case of car accidents, the 8–9 am pedestrian accident rates are substantially higher than the 6–7 am accident rates during flooding (Fig. 12)

Figure 10: Model estimates of the non-highway car accident rates with flooding, by community. (A, B) 6–7 am and 8–9 am respectively, for the 12-inch water level. (C, D) Same as (A, B), for the 36-inch water level.

as compared to the baseline (Fig. 11). Most of the 8–9 am pedestrian accidents are concentrated around the cities of Santa Rosa, Napa, Oakland, San Jose, and San Francisco.

Figure 11: Computed pedestrian accident rates without flooding, by community. (A) 6–7 am time period. (B) 8–9 am time period. Of the 72 communities, 27 are removed for lack of accident data, and 7 are removed for having R^2 coefficients less than 0.5.

The potential errors in historical accident data and modeled traffic volumes (Figs. 5 and 7) create corresponding uncertainty in the regressions used estimate accident rates. To demonstrate that our results are sufficiently insensitive to the uncertainty in the regression, we present car and pedestrian accident rates using only linear regressions in Figs. E.1 and E.2, respectively. The results show very similar distributions of accident rates to Figs. 10 and Figs. 12. The largest differences in accident rates are seen for communities with inverted U-shaped regression profiles, but these communities are limited in number. Overall, our results suggest that small variations in the regressions do not notably alter our model estimates of accident rates.

5.3 The region-wide accident rates increase substantially at low water levels

While Section 5.2 presents accident rates at the scale of individual communities, the current Section aggregates the accident rates at a regional scale. We compute the region-wide car and pedestrian accident rates for various water levels and for each of the five time periods by summing over the accident rates of all communities, and present the results in Fig. 13.

The region-wide car accident rate without flooding is smallest for the 5–6 am time period (0.5 accidents/hr). The accident rate then increases gradually until the 8–9 am time period (3.0 accidents/hr), after which it dips slightly for the 9–10 am time period (2.0 accidents/hr). The accident rate for the 12-inch water level follows a similar pattern as that without flooding for the different time periods, but the magnitudes of the accident rates are higher. The accident rate is smallest for the 5–6 am time period (0.9 accidents/hr), increasing up to 7.5 accidents/hr for the 8–9 am time period, and dipping back to 6.0 accidents/hr for the 9–10 am time period. While the magnitude of the accident rate increases with the water level rising to 24 and 36 inches, the increase in the accident rate decreases with each successive water level, suggesting that the biggest increase in the region-wide car accident rate occurs at the 12-inch water level, especially during peak hours.

Figure 12: Model estimates of pedestrian accident rates with flooding, by community. (A, B) 6–7 am and 8–9 am respectively, for the 12–inch water level. (C, D) Same as (A, B), for the 36–inch water level.

The region-wide pedestrian accident rates, shown in Fig. 13B, exhibit similar trends as the non-highway car accidents rates. The magnitudes of the pedestrian accident rates are substantially lower than those of the

Figure 13: Cumulative accident rates for the region, estimated for various water levels and hourly time periods. (a) Non-highway car accidents rates. (b) Pedestrian accident rates.

non-highway car accident rates because of lower baseline numbers. The total number of recorded pedestrian accidents in the San Francisco Bay Area during the weekday 5–10 am time period are approximately one-fifth of the non-highway car accidents (see Table 2).

6 Discussion

The urban traffic system, which is central to the functioning of metropolitan regions, is at risk of disruption from a rising sea level and intensifying coastal floods [42, 43, 5]. The traffic system is interconnected and non-linear, with disruptions propagating rapidly and extensively throughout the network [7, 44, 8, 5]. To quantify the ability of a traffic system to withstand disruption, prior studies [45, 8] have developed the concept of traffic resilience. Quantifying traffic resilience, however, remains a challenge given the complex nature of traffic systems.

Previous studies have quantified traffic resilience in terms of travel time delay [8, 5]. These studies simulate regional traffic patterns and estimate the changes in travel time for commuters resulting from road closures [8, 5]. Using the metric of travel time delay, however, provides only a partial picture of resilience, one that is focused toward travel efficiency. Our study presents an alternate picture of traffic resilience, one that is focused on road safety. We quantify changes in road safety for communities in the San Francisco Bay Area by estimating the rates of non-highway car and pedestrian accident rates in the presence of coastal flooding.

Accident rates versus travel time delays present differing pictures of traffic resilience for communities in the San Francisco Bay Area. One of the central results of Kasmalkar et al. [5] is that communities with high road network density are resilient to flood-related delays, because they have sufficient alternate road capacity to offset road closures or unexpected increases in traffic volumes. As a result, southwestern communities, especially those around the city of San Jose that have dense road networks, have relatively low projected delays despite the flooding of segments of major highways such as the US-101 [5].

However, when cars on flooded highways are rerouted onto local roads that pass through residential communities, the potential increase in traffic volumes may cause spikes in car and pedestrian accident rates. Thus, the availability of alternate roads may reduce the road safety of communities by accommodating an increase in traffic volumes. Our results in Figs. 10 and 12 suggest large increases in accident rates with flooding in communities around the major cities of Napa, Oakland, San Francisco, San Jose and Santa Rosa, where road network density is relatively high. The increase in pedestrian accident rates is almost exclusively concentrated around the major cities – a consequence of the high pedestrian volumes within the cities [9]. The increase in accident rates with flooding is largest during peak-hour traffic because a relatively large number of peak-hour commuters are rerouted off of flooded highways. Accident rates do not increase to the same degree during non-peak hours because the disrupted traffic volumes are relatively small.

Flood-related changes in accident rates and travel times also differ at the regional level. Travel time delays increase with water level in steps, where the delays are relatively low up to the 24-inch water level but are substantially higher for the 36-inch water level [5]. The step-like behavior is likely related to the successive closures of key nexus points at specific water levels, causing substantial region-wide changes in traffic patterns [5]. For example, the Dumbarton bridge, a major low-lying traffic corridor which runs across the Bay, remains open up to the 24-inch water level but is projected to be closed at the 36-inch water level. Upon closure, a large number of commuters are forced to travel either across a different bridge or along the entire southern shoreline of the Bay, causing substantial travel time delays at that water level [5].

Similar to delays, our study suggests that peak-hour accident rates also increase with water level. However, the rate of increase diminishes with water level (Fig. 13). As a result, the largest increase in accident rates occurs when the water level increases from 0 to 12 inches. One potential reason for the greater increase in accident rates at low water levels is that rerouted traffic may already saturate the local roads of certain communities. Additional increase in water level may then only marginally increase the traffic volumes in the saturated communities while slowing down traffic instead, causing a negligible increase in accident rates. Additionally, at high water levels, the previously described region-wide changes in traffic patterns reroute commuters onto alternate traffic corridors, such as from the Dumbarton Bridge to the San Mateo Bridge, rather than onto local roads in the vicinity of their usual routes. As a result, traffic volumes on local roads and the corresponding accident rates tends to increase only minimally at high water levels.

Overall, the contrasting changes in accident rates and delays with water level suggest that, at low-to-moderate water levels, the risk of accidents may pose at very least a similar, if not a greater concern than travel time delays for communities in the San Francisco Bay Area. The increase in projected accident rates

for the 12-inch water level also demonstrates the immediacy of the problem. Coastal flood events building up to a water level of 12 inches are to be expected in the 2020–2040 period, even at the present-day sea level [35]. Particularly affected could be densely populated communities adjacent to major traffic corridors, such as the US-101 which lines the western shore of the inner San Francisco Bay and is only slightly elevated above sea level for wide stretches. The densely populated communities such as those in San Francisco City tend to have dense road networks, allowing for greater rerouting of traffic from potentially flooded highways to local roads, and a correspondingly greater increase in accident rates.

We emphasize that our estimates of accident rates for the San Francisco Bay Area under flooding conditions are computed from regressions between historical accident rates and modeled traffic volumes. The validity of our estimates is limited both by the applicability of historic data and by the validity of our modeled traffic volumes. The ability to work remotely and the advent of autonomous vehicles are just two factors which may alter the representativeness of historic data in estimating future accident rates. Similarly, our model introduces both aleatoric uncertainty (see Fig. 4), arising from the ill-constrained parameters relating travel times and traffic volumes [34, 38, 29, 37, 5], and systematic uncertainty, arising from potential changes in commuter behavior in response to technological innovation.

Our traffic model applies only to an average commute and does not capture day-to-day variability in traffic volumes. Assuming average commutes, our model estimates the hourly trends in traffic volumes over the 5–10 am time period, which introduces time as a confounding factor in our analysis. For example, the increase in pedestrian accident rates during the 8–9 am time period relative to the 6–7 am time period may be a consequence of increased school-related pedestrian activity within that hour, rather than a result of increased traffic volumes. Also, adverse road conditions such as temporary construction work, special events, and even accidents themselves, may cause accidents. These dynamics are not considered here.

Despite the multiple uncertainties, we argue that the main value of our work lies in identifying the biases associated with quantifying traffic resilience primarily, or even exclusively, from an efficiency point of view as done in several previous studies [45, 8, 5]. It is important to keep in mind that the flood-related closure of highways displaces traffic into nearby residential communities, potentially elevating the risk of accidents in those communities. This dynamic is probably not unique to the San Francisco Bay Area, and could be relevant for other urban areas where some of the major traffic corridors are low-lying and prone to flooding.

7 Conclusion

This study quantifies the traffic resilience of communities to flood-related traffic disruption by estimating the increases in non-highway car and pedestrian accident rates as a result of traffic being displaced onto local roads. We use regression models to develop statistical relationships between traffic volumes and historical accident rates, and project accident rates for a range of water levels using simulated traffic patterns. Our study shows that the flooding of highways forces a large number of commuters onto local roads, thus increasing the accident rates for the nearby communities, especially during peak-hour traffic.

Our analysis shows that quantifying traffic resilience in terms of the rate of accidents rather than travel time delays changes the classification of the relative resilience of communities in the San Francisco Bay Area. As sea level rises, delays increase in communities where the road network lacks sufficient alternate road capacity to offset flood-related traffic disruption. In contrast, accident rates increase the most around major cities, where the high availability of alternate roads brings in displaced traffic. Region-wide accident rates increase the most at low water levels, while delays increase sharply at higher water levels, suggesting that accidents may be a greater concern than delays at low-to-moderate water levels.

8 Acknowledgements

Our work is the product of the Stanford Future Bay Initiative, a research- education-practice-partnership committed to co-production of actionable intelligence with San Francisco Bay Area communities, to shape a more equitable, resilient, and sustainable urban future. This research was shaped by stakeholder meetings

with residents of North Fair Oaks, who highlighted local concerns around road safety. We thank Aditya Medury for insightful conversations regarding the development of accident models. We also thank Eric Dunham and Jack Baker for thoughtful comments on our work. We thank the University of California at Berkeley Transportation Injury Mapping System team for curating accident records from SWITRS into a query database.

9 Funding

This research was primarily funded by the UPS Endowment Fund and Stanford’s Bill Lane Center for the American West. This research was partially inspired and funded by the NSF through the Office of Polar Programs awards PLR-1744758 and PLR-1739027. We also acknowledge support from the following organizations that are part of, or affiliated with, Stanford University: the Haas Center for Public Service; the School of Earth, Energy and Environmental Sciences; the Department of Civil and Environmental Engineering; the Institute for Computational and Mathematical Engineering; the Center for Sustainable Development and Global Competitiveness; and the Woods Institute for the Environment.

10 Author contributions

I.K. developed the model, conducted the simulations and analysis, and drafted the manuscript. J.S. framed the research question, advised model development and analysis, and provided feedback on the text.

11 Data availability

The code for the incremental traffic model is available at <http://cees-gitlab.stanford.edu/sigma/flood-related-traffic-disruption>. The code will be repackaged into a new repository upon publication of the manuscript.

References

- [1] P. P. Wong, I. J. Losada, J. P. Gattuso, J. Hinkel, A. Khattabi, K. L. McInnes, Y. Saito, and A. Sallenger. *Chapter 5. Coastal systems and low-lying areas*. Ed. by C. B. Field, V. R. Barros, D. J. Dokken, K. J. Mach, M. D. Mastrandrea, T. E. Bilir, M. Chatterjee, K. L. Ebi, Y. O. Estrada, R. C. Genova, B. Girma, E. S. Kissel, A. N. Levy, S. MacCracken, P. R. Mastrandrea, and L. L. White. 2014.
- [2] B. Neumann, A. T. Vafeidis, J. Zimmermann, and R. J. Nicholls. “Future Coastal Population Growth and Exposure to Sea-Level Rise and Coastal Flooding - A Global Assessment”. In: *PLOS ONE* 10.3 (Mar. 2015), e0118571. URL: <https://doi.org/10.1371/journal.pone.0118571>.
- [3] J.-L. Merkens, L. Reimann, J. Hinkel, and A. T. Vafeidis. “Gridded population projections for the coastal zone under the Shared Socioeconomic Pathways”. In: *Global and Planetary Change* 145 (2016), pp. 57–66. ISSN: 0921-8181. DOI: <https://doi.org/10.1016/j.gloplacha.2016.08.009>. URL: <http://www.sciencedirect.com/science/article/pii/S0921818116301473>.
- [4] United Nations Population Division. *World Urbanization Prospects: The 2018 Revision*. Tech. rep. United Nations Population Division, 2018.
- [5] I. G. Kasmalkar, K. A. Serafin, Y. Miao, I. A. Bick, L. Ortolano, D. Ouyang, and J. Suckale. “When floods hit the road: Resilience to flood-related traffic disruption in the San Francisco Bay Area and beyond”. In: *Science Advances* 6.32 (Aug. 2020), eaba2423. ISSN: 2375-2548. DOI: [10.1126/sciadv.aba2423](https://doi.org/10.1126/sciadv.aba2423). URL: <https://advances.sciencemag.org/lookup/doi/10.1126/sciadv.aba2423>.
- [6] J. C. Falcocchio and H. S. Levinson. *Road traffic congestion: a concise guide*. Vol. 7. Springer, 2015.

- [7] B. S. Kerner. *The physics of traffic: empirical freeway pattern features, engineering applications, and theory*. Tampa, Florida: Springer-Verlag Berlin Heidelberg, 2012.
- [8] A. A. Ganin, M. Kitsak, D. Marchese, J. M. Keisler, T. Seager, and I. Linkov. “Resilience and efficiency in transportation networks”. In: *Science Advances* 3.12 (Dec. 2017), e1701079. DOI: 10.1126/sciadv.1701079. URL: <http://advances.sciencemag.org/content/3/12/e1701079.abstract>.
- [9] C. Lee and M. Abdel-Aty. “Comprehensive analysis of vehicle–pedestrian crashes at intersections in Florida”. In: *Accident Analysis & Prevention* 37.4 (2005), pp. 775–786. ISSN: 0001-4575. DOI: <https://doi.org/10.1016/j.aap.2005.03.019>. URL: <http://www.sciencedirect.com/science/article/pii/S0001457505000564>.
- [10] M. A. Quddus. “Modelling area-wide count outcomes with spatial correlation and heterogeneity: An analysis of London crash data”. In: *Accident Analysis & Prevention* 40.4 (2008), pp. 1486–1497. ISSN: 0001-4575. DOI: <https://doi.org/10.1016/j.aap.2008.03.009>. URL: <http://www.sciencedirect.com/science/article/pii/S0001457508000523>.
- [11] D. Lord and F. Mannering. “The statistical analysis of crash-frequency data: A review and assessment of methodological alternatives”. In: *Transportation Research Part A: Policy and Practice* 44.5 (2010), pp. 291–305. ISSN: 09658564. DOI: 10.1016/j.tra.2010.02.001. URL: <http://www.sciencedirect.com/science/article/pii/S0965856410000376>.
- [12] C. Wang, M. Quddus, and S. Ison. “A spatio-temporal analysis of the impact of congestion on traffic safety on major roads in the UK”. In: *Transportmetrica A: Transport Science* 9.2 (2013), pp. 124–148.
- [13] United States Census Bureau. *American Community Survey 5-Year Estimates — Geodatabase Format: 2013-2017 Detailed Tables*. 2017. URL: <https://www.census.gov/geographies/mapping-files/time-series/geo/tiger-data.html>.
- [14] N. J. Wood, J. Jones, S. Spielman, and M. C. Schmidtlein. “Community clusters of tsunami vulnerability in the US Pacific Northwest”. In: *Proceedings of the National Academy of Sciences* 112.17 (Apr. 2015), 5354 LP–5359. DOI: 10.1073/pnas.1420309112. URL: <http://www.pnas.org/content/112/17/5354.abstract>.
- [15] M. A. Hummel, N. J. Wood, A. Schweikert, M. T. Stacey, J. Jones, P. L. Barnard, and L. Erikson. “Clusters of community exposure to coastal flooding hazards based on storm and sea level rise scenarios—implications for adaptation networks in the San Francisco Bay region”. In: *Regional environmental change* 18.5 (2018), pp. 1343–1355.
- [16] A. E. Retallack and B. Ostendorf. “Current Understanding of the Effects of Congestion on Traffic Accidents.” eng. In: *International journal of environmental research and public health* 16.18 (Sept. 2019). ISSN: 1660-4601 (Electronic). DOI: 10.3390/ijerph16183400.
- [17] D. W. Gwynn. “Relationship of accident rates and accident involvements with hourly volumes”. In: *Traffic Quarterly* 21.3 (1967).
- [18] J.-L. Martin. “Relationship between crash rate and hourly traffic flow on interurban motorways”. In: *Accident Analysis & Prevention* 34.5 (2002), pp. 619–629.
- [19] A. E. Retallack and B. Ostendorf. “Relationship Between Traffic Volume and Accident Frequency at Intersections”. eng. In: *International journal of environmental research and public health* 17.4 (Feb. 2020), p. 1393. ISSN: 1660-4601. DOI: 10.3390/ijerph17041393. URL: <https://pubmed.ncbi.nlm.nih.gov/32098180https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7068508/>.
- [20] G Maycock and R. D. Hall. *Accidents at 4-arm roundabouts*. Tech. rep. 1984.
- [21] U. Brüde, J. Larsson, and K.-O. Hedman. “Design of Major Urban Junctions: Accident Prediction Models and Empirical Comparisons”. In: *VTI EC RESEARCH* 3 (1998).
- [22] M. Pregnotato, A. Ford, S. M. Wilkinson, and R. J. Dawson. “The impact of flooding on road transport: A depth-disruption function”. In: *Transportation Research Part D: Transport and Environment* 55 (2017), pp. 67–81. ISSN: 1361-9209. DOI: <https://doi.org/10.1016/j.trd.2017.06.020>. URL: <http://www.sciencedirect.com/science/article/pii/S1361920916308367>.

- [23] H. Brodsky and A. Hakkert. “Risk of a road accident in rainy weather”. In: *Accident Analysis & Prevention* 20.3 (1988), pp. 161–176. ISSN: 0001-4575. DOI: [https://doi.org/10.1016/0001-4575\(88\)90001-2](https://doi.org/10.1016/0001-4575(88)90001-2). URL: <http://www.sciencedirect.com/science/article/pii/0001457588900012>.
- [24] L. Qiu and W. A. Nixon. “Effects of Adverse Weather on Traffic Crashes: Systematic Review and Meta-Analysis”. In: *Transportation Research Record* 2055.1 (Jan. 2008), pp. 139–146. ISSN: 0361-1981. DOI: [10.3141/2055-16](https://doi.org/10.3141/2055-16). URL: <https://doi.org/10.3141/2055-16>.
- [25] C. Xu, W. Wang, and P. Liu. “Identifying crash-prone traffic conditions under different weather on freeways”. In: *Journal of Safety Research* 46 (2013), pp. 135–144. ISSN: 0022-4375. DOI: <https://doi.org/10.1016/j.jsr.2013.04.007>. URL: <http://www.sciencedirect.com/science/article/pii/S0022437513000510>.
- [26] California Highway Patrol. *Statewide Integrated Traffic Records System (SWITRS) - Dataset*. 2019.
- [27] United States Census Bureau. *TIGER/Line Shapefile, California, Census Blocks — Shapefile format: 2018*. 2018.
- [28] Metropolitan Transportation Commission / Association of Bay Area Governments (MTC/ABAG). *Regional Road Network — Shapefile Format: 2015*. 2017. URL: <http://analytics.mtc.ca.gov/foswiki/bin/view/Main/DataRepository>.
- [29] G. Erhardt, P. Brinckerhoff, D. Ory, A. Sarvepalli, J. Freedman, J. Hood, and B. Stabler. *MTC’s Travel Model One: Applications of an Activity-Based Model in its First Year*. Tampa, Florida, 2012.
- [30] United States Census Bureau. *Longitudinal Employer-Household Dynamics Origin Destination Employment Statistics — Geodatabase Format: 2017*. 2017. URL: <https://lehd.ces.census.gov/data/>.
- [31] M. Chen and A. S. Alfa. “A Network Design Algorithm Using a Stochastic Incremental Traffic Assignment Approach”. In: *Transportation Science* 25.3 (Aug. 1991), pp. 215–224. ISSN: 0041-1655. DOI: [10.1287/trsc.25.3.215](https://doi.org/10.1287/trsc.25.3.215). URL: <https://doi.org/10.1287/trsc.25.3.215>.
- [32] P. Wang, T. Hunter, A. M. Bayen, K. Schechtner, and M. C. González. “Understanding Road Usage Patterns in Urban Areas”. In: *Scientific Reports* 2 (Dec. 2012), p. 1001. URL: <http://dx.doi.org/10.1038/srep01001>.
- [33] United States Bureau of Public Roads. *Traffic assignment manual for application with a large, high speed computer*. Vol. 2. United States Department of Transportation, Federal Highway Administration, Bureau of Public Roads, 1964.
- [34] D. Branston. “Link capacity functions: A review”. In: *Transportation research* 10.4 (1976), pp. 223–236.
- [35] J. Vandever, M. Lightner, S. Kassem, J. Guyenet, M. Mak, and C. Bonham-Carter. *Adapting to Rising Tides Bay Area Sea Level Rise Analysis and Mapping Project*. 2017. URL: <http://www.adaptingtorisingtides.org/wp-content/uploads/2018/07/BATA-ART-SLR-Analysis-and-Mapping-Report-Final-20170908.pdf>.
- [36] TomTom. *Routing API and Extended Routing API*. 2020.
- [37] M. Miller and J. W. Baker. “Coupling mode-destination accessibility with seismic risk assessment to identify at-risk communities”. In: *Reliability Engineering & System Safety* 147 (2016), pp. 60–71.
- [38] Y. G. Kim and H. S. Mahmassani. *Link Performance Functions for Urban Freeways With Asymmetric Car-Truck Interactions*. 1987, pp. 32–39.
- [39] E. T. Mtoi and R. Moses. “Calibration and evaluation of link congestion functions: applying intrinsic sensitivity of link speed as a practical consideration to heterogeneous facility types within urban network”. In: *Journal of Transportation Technologies* (2014).
- [40] A Veh. “Improvements to Reduce Traffic Accidents”. In: *Meeting of the Highway Division: New York, NY, USA*. 1937, pp. 1775–1785.

- [41] M. S. Raff. “Interstate highway - accident study”. en. In: *Highway Research Board bulletin* 74 (1953), pp. 18–45. ISSN: 0073-2206. URL: <http://dx.doi.org/>.
- [42] P. Suarez, W. Anderson, V. Mahal, and T. R. Lakshmanan. “Impacts of flooding and climate change on urban transportation: A systemwide performance assessment of the Boston Metro Area”. In: *Transportation Research Part D: Transport and Environment* 10.3 (May 2005), pp. 231–244. ISSN: 1361-9209. URL: <http://www.sciencedirect.com/science/article/pii/S1361920905000155>.
- [43] M. J. Koetse and P. Rietveld. “The impact of climate change and weather on transport: An overview of empirical findings”. In: *Transportation Research Part D: Transport and Environment* 14.3 (2009), pp. 205–221. ISSN: 1361-9209. DOI: <https://doi.org/10.1016/j.trd.2008.12.004>. URL: <http://www.sciencedirect.com/science/article/pii/S136192090800165X>.
- [44] G. Pescaroli and D. Alexander. “Critical infrastructure, panarchies and the vulnerability paths of cascading disasters”. In: *Natural Hazards* 82.1 (May 2016), pp. 175–192. ISSN: 1573-0840. DOI: 10.1007/s11069-016-2186-3. URL: <https://doi.org/10.1007/s11069-016-2186-3>.
- [45] D. Freckleton, K. Heaslip, W. Louisell, and J. Collura. “Evaluation of Resiliency of Transportation Networks after Disasters”. In: *Transportation Research Record* 2284.1 (Jan. 2012), pp. 109–116. ISSN: 0361-1981. DOI: 10.3141/2284-13. URL: <https://doi.org/10.3141/2284-13>.

A Commuters by time of leaving for work

Table 1: Region-wide percentages of commuters by time of leaving for work. Values derived from ACS 2013–2017 survey data [13].

	5–6 am	6–7 am	7–8 am	8–9 am	9–10 am
Percentage of commuters leaving for work in this time period.	9%	18%	31%	28%	13%

B Accidents by type and time of morning

Table 2: Accidents in the San Francisco Bay Area by type and time of morning, curated from [26].

Time Period	Accidents		
	Pedestrian	Non-highway Car	Highway Car
5–6 am	201	856	1523
6–7 am	449	1755	2349
7–8 am	900	4224	3433
8–9 am	1085	5688	3975
9–10 am	645	4229	2806
Total	3280	16752	14086

C Validation of travel times

Figure C.1: Histograms over all segments in the model road network for differences in TomTom and model travel times. Travel times differences for (a) 5–6 am, (b) 7–8 am, and (c) 9–10 am. The results are similar to Fig. 2.

D Alternate partitions of San Francisco Bay Area

Figure D.1: Spatial distribution of the regression curves for non-highway car accident rates and traffic volumes for alternate clusters of San Francisco Bay Area census blocks. The panels are organized similar to Fig. 6. Panels A and B represent a clustering which optimizes for proximity, while Panel C and D represents a clustering which optimizes for similarity of median household income and mean free flow travel speeds. In the latter, not all communities may be contiguous areas.

Figure D.2: Spatial distribution of the regression curves for pedestrian accident rates and traffic volumes for alternate clusters of San Francisco Bay Area census blocks. The panels are organized similar to Fig. 6. Panels A and B represent a clustering which optimizes for proximity, while Panel C and D represents a clustering which optimizes for similarity of median household income and mean free flow travel speeds. In the latter, not all communities may be contiguous areas.

E Accidents rates for the San Francisco Bay Area estimated purely from linear regression

Figure E.1: Model estimates of non-highway car accident rates with flooding, obtained purely from linear regressions. (A, B) 6–7 am and 8–9 am respectively, for the 12-inch water level. (C, D) Same as (A, B), for the 36-inch water level. Communities with insufficient accident data and low R^2 regression coefficients are removed.

Figure E.2: Model estimates of pedestrian accident rates with flooding, obtained purely from linear regressions. (A, B) 6–7 am and 8–9 am respectively, for the 12-inch water level. (C, D) Same as (A, B), for the 36-inch water level. Communities with insufficient accident data and low R^2 regression coefficients are removed.