Neuroergonomics on the go. An evaluation of the potential of mobile EEG for work-place assessment and design

Wascher, E.*¹, Julian Reiser*¹, Gerhard Rinkenauer¹, Mauro Larrá¹, Felix A. Dreger¹, Daniel
Schneider¹, Melanie Karthaus¹, Stephan Getzmann¹, Marie Gutberlet², & Stefan Arnau¹

* shared first-authorship

¹IfADo – Leibniz Research Centre for Working Environment and Human Factors, Dortmund,
Dept. Ergonomics

²Blindsight GmbH, Schlitz, Germany

Correspondence:

Edmund Wascher

wascher@ifado.de

Running Head: Neuroergonomics with mobile EEG

Manuscript type: Review

Word count of the core text: 8419

Abstract

Objective — We demonstrate and discuss the use of mobile EEG for neuroergonomics. Both technical state of the art, measures and cognitive concepts are systematically addressed.

Background — Modern work is increasingly characterized by information processing. Therefore, the examination of mental states, mental load or cognitive processing during work is becoming increasingly important for ergonomics.

Results — Mobile EEG allows to measure mental states and processes under real live conditions. It can be used for various research questions in cognitive neuroergonomics. Besides measures in the frequency domain that have a long tradition in the investigation of mental fatigue, task load and task engagement, new approaches – like blink-evoked potentials – render event-related analyses of the EEG possible also during unrestricted behavior.

Conclusion — Mobile EEG has become a valuable tool for evaluating mental states and mental processes on a highly objective level during work. The main advantage of this technique is that working environments don't have to be changed while systematically measuring brain functions at work. Moreover, the work flow is unaffected by such neuroergonomic approaches.

Keywords: Mobile EEG, Neuroergonomics, Mental States, Information processing

Précis: Modern work is increasingly characterized by information processing. Measuring mental aspects of work is becoming increasingly important for ergonomics. Mobile EEG can represent cognition in an objectifiable way without affecting the worker. We give an overview of available technologies, problems of measurement, but also of cognitive factors that can be addressed with this new technique.

Introduction

“The guiding principle of neuroergonomics is that understanding how the brain carries out the complex tasks of everyday life - and not just the simple, artificial tasks of the research laboratory - can provide important benefits for both ergonomics research and practice” (Parasuraman, 2003)

Information processing is a central aspect of modern work life. In piloting, monitoring or any other task that requires the intake and processing of (as well as adequate responses to) information, fluctuations in task engagement or mental resources may lead to fatal accidents or mental strain that might end up in stress related diseases. Thus, the evaluation or even the continuous monitoring of mental states and/or cognitive processing may help to improve work safety and well-being (Parasuraman, 2011). The measurement of neurophysiological parameters in work environments can help to understand the neural basis of cognitive processing during common activities and actions (Hancock, 2019; McKeown, 2014; Mehta & Parasuraman, 2013; Rahman, Karwowski, Fafrowicz, & Hancock, 2019). Furthermore, neurophysiological measures do not only unveil cognitive aspects (i.e. mental load) of modern work. They bear the potential to improve safety and efficiency of work environments and thus to raise motivation and productivity (Cinel, Valeriani, & Poli, 2019; Giraudet, Imbert, Berenger, Tremblay, & Causse, 2015).

So far, the main approach of neuroergonomic work place analysis has been to (1) derive cognitive construct entities of interest (e.g. motivation or mental load) and (2) to transfer these constructs to controlled settings in the laboratory where neurophysiological measurements can be conducted in a highly controlled, artificial environment (Arnau, Wascher, & Kuper, 2019; Kramer, Wickens, & Donchin, 1985). In other studies, work-related situations or tasks were partially reconstructed to investigate, e.g., the impact of light upon fatigue (Baek & Min, 2015), adaptive automation in flight control (Arico et al., 2016; Freeman, Mikulka, Prinzl, & Scerbo, 1999), or high mental demands that should evoke a stress response (J. W. Ahn, Ku, & Kim, 2019). These work-related studies varied in the realism of the settings, even incorporating real-life experimentation (F. Dehais et al., 2018; F. Dehais, Somon, Mullen, & Callan, 2020; McKendrick et al., 2016; Shamay-Tsoory & Mendelsohn, 2019). Over the years, the impact of the complex interaction of countless (and so far

even hardly identified) mental factors upon information processing within real-life environments has been addressed in neuroscience related studies (Gramann, Ferris, Gwin, & Makeig, 2014), especially in the field of automobile driving research (c.f. Borghini, Astolfi, Vecchiato, Mattia, & Babiloni, 2014; Lohani, Payne, & Strayer, 2019; Perrier et al., 2016). Thereby, the application of neurophysiological methods in truly natural working environments – such as the cockpit of an airplane (F. Dehais et al., 2018; Gateau, Ayaz, & Dehais, 2018) – intends to generate a valid description of mental processing during work. No situational characteristics should be changed for the worker, neither the workflow, nor the self-perception or social interactions that are inherent to many working environments. Therefore, the measurement equipment used must be unobtrusive and should not interfere with any of the wearer's actions.

What method is best suited to map these requirements? First of all, it should reflect cognitive processing and mental states reliably, which excludes any methods that uses peripheral parameters. An important tool to investigate cognitive processes non-invasively and with high temporal resolution is the electroencephalogram (EEG). This measurement technique records voltage changes over the scalp – generated by cortical and non-cortical sources – using small electrodes. Despite its sensitivity to movement and other workplace related sources of interference (e.g. electromagnetic intrusions from electronics equipment, engines, and generators), it appears to also fulfill other requirements for a suitable system. Since evaluating the time course of mental states is one core objective of this approach, the measures used should remain sensitive over time in order to reflect e.g. increasing fatigue of the worker. Also, the equipment used should be able to record a participant's mental activity in a measurement lasting for hours and should not become uncomfortable to wear in this time. Remote access to the data might enable its use for controlling or even adapting work situations. Besides measurement reliability, the measurement validity of the mental aspects of work needs to be ensured as well.

The EEG's selection as the measurement technique of choice is based on several objective reasons. Firstly, it promises high mobility due to its sensors' properties; electrodes are lightweight, small, and can be positioned to one's liking without interfering with other electrodes. Also, EEG systems are quite inexpensive in comparison to other types of neurocognitive measurement devices (e.g. fNIRS), especially nowadays with an increasing number of devices marketed to end-

consumers. The last advantage lies within the EEG's temporal resolution with up to more than 1 kHz which boosts its practicability for many use-cases that need to be analyzed in the time domain (Makeig, Gramann, Jung, Sejnowski, & Poizner, 2009; for an overview of the many available devices see Mehta & Parasuraman, 2013).

The present paper gives an overview of the development and current trends in the use of mobile systems for the acquisition of EEG parameters in situations that are close to real life behavior. Requirements, limitations and possible approaches to overcome limitations are addressed and current EEG measurement systems are presented. Common EEG measures in the frequency and time domains are discussed in detail. Finally, conceptual questions and future goals and challenges are addressed.

Going mobile

Rationale, Prerequisites and Restrictions

Cognitive neuroergonomics intends to investigate cognitive states and their impact on information processing in the workplace based on neurophysiological data. While it is also possible to infer on cognitive states by assessing peripheral psychophysiological measures (e.g. heart rate variability or electrodermal activity), cognitive states and mental processing can be addressed most accurately with the use of high temporal resolution measurements by means of EEG (c.f. Hogervorst, Brouwer, & van Erp, 2014; St John, Kobus, Morrison, & Schmorrow, 2004). Modulations of information processing, e.g. due to cognitive load, can then be described in a temporally specific way and with a high signal sensitivity. However, these measures have seldomly been applied in uncontrolled environments – e.g. real-life or high-fidelity simulated driving or aircraft maneuvering (for a review see Borghini et al., 2014) – that provide reliable information about both the environment and the action of the participant (Gramann, Fairclough, Zander, & Ayaz, 2017). Thus, most neurophysiological research was conducted in sparsely lit chambers where the participant sat inertly in a chair and responded mostly with button presses. The tasks used were simplified experimental approaches towards single cognitive mechanisms. To circumvent this artificiality, realistic work settings were either combined with experimental tasks (Mijovic et al., 2016), or behavioral restrictions (i.e. participants were seated on a sofa and asked to minimize body motion to avoid movement

artifacts), in order to guarantee proper processing of incoming information and high quality EEG measurements (Chang & Chen, 2005). These studies were the first steps towards more ecologically valid settings (Ladouce, Donaldson, Dudchenko, & Ietswaart, 2016). In later studies, the simulation of work places came closer to real world situations (Funke et al., 2017; Matthews, Reinerman-Jones, Barber, & Abich, 2015; Mijovic et al., 2016; Wascher, Heppner, & Hoffmann, 2014a; Wascher et al., 2016), while maintaining experimental control, e.g. in virtual reality settings (Banaei, Hatami, Yazdanfar, & Gramann, 2017) or high-fidelity simulations of military applications (Wilson & Russell, 2007), driving (Getzmann, Arnau, Karthaus, Reiser, & Wascher, 2018), or piloting (Wilson & Hankins, 1994).

Neurocognitive studies in work-place simulations that come close to real environments are still rare in spite of their relevance. Considering the psychological strain imposed by certain tasks and environments on the worker without relying on overt behavior (e.g. units produced per hour, deviations from the optimal route), wellbeing and safety could be enhanced significantly (Parasuraman, 2011). The use-cases are manifold, as a sociotechnical system could be extended by a passive brain-computer interface that regulates the distribution of demand adaptively between the operator and the machine depending on the individual's attentional state. Another vision for future applications of neuroergonomic measures could lead in the direction of neurophysiological workload quantification using a mobile device and a lightweight set of electrodes. Still, in order to be able to quantify cognitive constructs, one needs to understand how brain correlates are related to cognitive states.

Besides the experimental restrictions outlined above, one main restriction in the past were the problems inherent to the measurement of EEG during ongoing bodily motion. When work places are considered that do not only comprise seated task execution like driving or air traffic management, both the restricted availability of truly mobile recording equipment and the detrimental influence of motion artifacts (Gale, Signal, Garden, & Gander, 2007) rendered reliable measurements of cognitive processing almost impossible. However, recent technical advances, in particular the miniaturization of EEG amplifiers, created new possibilities and therefore enabled neuroscientific research to enter the real workplace without changing the naturalness of the environment. This includes that workers are neither restricted by the measurement

equipment in their work, nor with respect to their ability to move or during social interactions.

State of the art

Research interest in mobile EEG has increased enormously over the last decade. A systematic search in Web of Science (August 2019) revealed 305 studies employing mobile EEG (Search topics: “mobile EEG“, “portable EEG”, “wearable EEG”, “wireless EEG”) starting from 1998 (duplicates were discarded). However, it took until 2014 before a substantial number of studies (> 10) was published per year. About 18% of these studies reported the application of mobile EEG in clinical contexts, applying this method to patient monitoring or diagnostic procedures (Dash, Hernandez-Ronquillo, Moien-Afshari, & Tellez-Zenteno, 2012). Ten studies (3.3%) reported on sleep staging. As would be expected in such a new field, a substantial part of the publications dealt with hardware development and evaluation (17%). Another 17% of studies report the evaluation of methods, in particular regarding the removal of EEG artifacts that arise with mobile application (Blum, Jacobsen, Bleichner, & Debener, 2019; Snyder, Kline, Huang, & Ferris, 2015).

The amount of neuroergonomic literature (i.e. studies with a clear focus on workplace related issues) that incorporates mobile EEG remained relatively sparse with 28 published studies until late 2019. As expected, (mental) fatigue and drowsiness constituted a high fraction of these studies, in particular for different aspects of aircraft piloting (Guo, Pan, Zhao, Cao, & Zhang, 2018; Hankins & Wilson, 1998; Lin et al., 2014; Rohit et al., 2017; Wilson, 2002; X. L. Zhang et al., 2017; Zhou et al., 2018), manual assembly processes (Xiao, Duan, Zhang, & Li, 2018), or in the context of a logistics workplace (Wascher, Heppner, et al., 2014a; Wascher et al., 2016). These studies included user state examinations, the development of countermeasures to critical aspects of safety in the workplace (Zhou et al., 2018), or a brain-computer interface (BCI) based control of driving speed (Z. T. Zhang et al., 2016).

Mental workload is another core construct of cognitive ergonomics. Studies investigating mental workload applied well-established cognitive paradigms in order to reliably manipulate the construct of task load while using mobile EEG, for example during walking movements, using machine-learning algorithms and phase-locked

information (S. Y. Wang, Gwizdka, & Chaovalitwongse, 2016; Yokota, Tanaka, Miyamoto, & Naruse, 2017). As an approach towards studying even more natural situations, at least one study investigated acute stress in construction workers with the help of features in the time and frequency domain (Jebelli, Hwang, & Lee, 2018), while another study looked more generally into the emotional state in construction workers as an important factor affecting safety in the workplace using feature extraction and classification techniques (Hwang, Jebelli, Choi, Choi, & Lee, 2018).

Until now, only a few cognitive aspects of work have been investigated with the help of mobile EEG, despite its large potential for doing so. Liu and co-workers (2013) investigated to what degree alertness could be modulated by music. More directly geared at basic cognitive mechanisms, some studies have investigated the allocation of attention in the work process (N. H. Liu et al., 2013; Mijovic et al., 2017; D. Wang et al., 2017). Beside these basic cognitive aspects of work, another group of studies addressed the question of user experience in cognitive neuroergonomics. They deal with economic decisions or more generally with consumer behavior (Khushaba et al., 2013; Munoz, Gallego, Salazar, & Rodriguez, 2019; Roberts et al., 2018), user interaction (Sargent, Watson, Ye, Suri, & Ayaz, 2020) or user satisfaction (Keum, Lee, Lee, & In, 2018). On a more macroscopic level, several studies dealt with spatial cognition and sensation in real life situations in urban environments (Al-Barrak, Kanjo, & Younis, 2017; Djebbara, Fich, Petrini, & Gramann, 2019; Mavros, Austwick, & Smith, 2016) or while walking through an art museum (Cruz-Garza et al., 2017).

In conclusion, the above studies aimed to use brain activity measurement in natural environments to investigate neural aspects of work-related behavior. The technical prerequisites to establish these methods on a larger scale in the field of neuroergonomics seem to be fulfilled. However, further development is still needed.

Measurement equipment

The possibility to record EEG-signals from a few single electrodes with portable amplifiers has existed since decades (e.g. Vitaport, TEMEC Technologies B.V., Netherlands; Biopac, BIOPAC Systems, Inc., USA). These single electrode systems still exist, but are either restricted with respect of the number of channels available for the EEG, lacking the possibilities to record exactly timed trigger signals or are not as

portable as recent EEG systems specifically designed for mobile EEG. They are predominantly used for the measurement of peripheral electrophysiology in connection with some isolated EEG measures.

Problems of early systems were solved by introducing wireless transmission of EEG signals. This wireless EEG signal transmission allowed to collect data from a regular electrode cap (up to 128 channels) in mobile settings. The recorded signal was transmitted to amplifiers that were implemented in a regular laboratory setting and allowed for the integration of stimulus presentation and exact temporal triggering. Given the possibility to evenly cover the entire head surface with electrodes, motion artifacts (in particular neck muscle artifacts) could be identified to clean the data (Gramann, Gwin, Bigdely-Shamlo, Ferris, & Makeig, 2010; Gramann, Jung, Ferris, Lin, & Makeig, 2014; Jungnickel & Gramann, 2016; Thompson, Steffert, Ros, Leach, & Gruzelier, 2008).

Another major step in mobile EEG system development (Bateson, Baseler, Paulson, Ahmed, & Asghar, 2017) was the introduction of miniaturized mobile amplifiers that can be attached to the back of the head (Smarting, mBrainTrain, Serbia; LiveAmp, Brain Products GmbH, Germany; B-Alert X, Advanced Brain Monitoring, USA). Due to the fact that these amplifiers have integrated gyro-sensors, gait parameters can be recorded to identify movement patterns and motion-induced artifacts. These systems differ particularly in the way the data is stored. The first kind of systems is able to stream the data wirelessly to a mobile device (i.e. smartphone), while other systems provide the possibility to store the data on an SD card that is inserted into the amplifier itself or they even combine the two. Both ways to store data have their advantages: While wireless transmission allows direct access to the data, e.g. for BCI, on-board storage provides the participant with higher range of movement and eliminates problems concerning transmission errors.

With respect to neuroergonomics, these systems face two main problems: 1) EEG caps are obtrusive, since the electrode caps cannot easily be hidden. 2) The use of cables induces electro-magnetic noise by induction, which is an issue especially when the participants' activity requires full body motion. It has to be mentioned here that in contrast to walking experiments, in which the walking movements are more or less regular, movements during varying work tasks are neither rhythmic nor repetitive and cannot be corrected for as easily as for walking.

279 A step towards less obtrusive measurements was achieved by applying
280 adhesive film electrodes affixed behind the ear (Bleichner & Debener, 2017) and by
281 using in-ear electrodes (Bleichner et al., 2015). The amplifiers can be hidden by a
282 headband or a base cap. This way, the participant can act without attracting
283 unwanted attention even in social situations. Still, this method comes with some
284 shortcomings. First, skin texture can vary substantially with age, often resulting in
285 lower signal quality and impaired contact retention of the adhesives for elderly
286 persons. However, the main problem with this type of electrodes is the restricted
287 scalp surface area covered by the implemented electrodes. This makes cortical
288 activity distant to the covered area hard to capture. The same holds true for integrated
289 systems that were developed either for rapid research application, or end-consumer
290 use (e.g. for meditation or gaming). These systems mainly consist of a head mount or
291 headband with dry electrodes and an amplifier integrated into the cap. While
292 integrated systems reduce the risk of artifacts due to cable motions, both the
293 restricted number of channels and the poor technical specifications of the amplifiers
294 limit their value for research. Nevertheless, they may still provide reliable data (Barham
295 et al., 2017). [Dry electrodes don't make contact to the scalp surface using electrolyte
296 gel like regularly used wet EEG electrodes. The montage is faster but they are
297 potentially less comfortable compared to wet electrodes and there is not much
298 experience with respect to long term testing \(Di Flumeri et al., 2019\).](#)

299
300 To sum up, finding the right recording method and devices can be quite
301 daunting, but with a clear research question, the choice of the apparatus can be
302 narrowed down. Table 1 lists most of the currently available mobile EEG systems
303 along with their specifications. Still, this is not an exhaustive collection of all systems
304 available and new systems are being developed and brought to market continuously
305 (Brouwer, Zander, van Erp, Korteling, & Bronkhorst, 2015).

Table 1. List of available mobile EEG systems and their specifications

Research Systems							
System Name Manufacturer	Size (mm) and Weight (g)	Online Transfer Local Storage	Channel (Uni-, Bipolar, Other)	Triggers	Max Rate Max Range	Operating Time (hrs)	Comment
Smarting mBrainTrain	82 x 51 x 12 60 g	BT v2.1+EDR No local storage	24 uni., 0 bipolar, 3D Gyroscope	PC Based	500 Hz +/- 100 mV	5 h	
LifeAmp Brain Products GmbH	83 x 51 x 14 60 g	Wifi, 2.4 GHz SD Card	up to 64 uni., 8 bip., 3D Gyroscope	3 bit	1000 Hz +/- 341.6 mV	4.5 h	
B-Alert X24 Advanced Brain Monitoring	127 x 57,15 x 25,4 110 g	BT v2 SD Card	up to 20 uni, optional ECG 3D Gyroscope	?	256 Hz +/- 1000 mV	6 h	
eego™ sports 32/64 ANT Neuro	160 x 205 x 22 500 g	No wireless USB3 based	up to 64 uni., 24 bip., None	8 bit	2048 Hz +/-1000 mV	5 h	Active Shielding
Enobio 8/20/32 Neuroelectronics	89 x 61 x 24 82, 81, 97 g	Wifi, 2.4 GHz SD Card	8/20/32 unip., 0 bip.,	PC based	500 Hz +/- 419 mV	6.5 h WiFi 24 h SD	
Saga 32/64+ TMSi	179 x 41 (oval) 700 g	Wifi 2.4 GHz Dock based	32/64 uni., 4 bipolar, 3D Accel., 9x AUX	Trig. Btn., Sync Out	4096 Hz +/- 150 mV	6/12 h (1/2 batteries)	Active Shielding, Dock base, 16 bit triggers
Quick-30 CGX, Cognionics	20 x 18 x 19 610 g	Bluetooth LE SD Card	30 unip., 0 bipolar 3D Acceleration	None	1000 Hz n.a.	8 h WiFi 16 h SD	
Mobile-64/128CGX, Cognionics	cap based 460 g	Bluetooth LE SD Card	64/128 unip., 0 bip. 9D Gyro+Accel.	None	1000 Hz n.a.	6 h WiFi 8 h SD	
g.Nautilus 64 g.tec	78 x 60 x 36 140 g	Wifi, 2.4 GHz No local storage	64 unip., 32 shared bip.	8 bit Base Station	250 Hz +/- 2250 mV	6 h	
Versatile EEG 32 BitBrain	n.a. 450 g	BT v2.1+EDR SD Card	32, 2 bipolar 9D Gyro+Acc+Mag.	1x digital, 1x optical	256 Hz +/- 100 unip. +/- 400 bip.	8 h	
Emotiv EPOCflex Emotiv	Cap size based n.a.	BT 5.0, USB key No local storage	14, 0 bipolar 9D Gyro+Acc+Mag.	None	128 Hz +/- 4.12 mV	9 h	Flexible montage, DRL
Consumer Systems							
eego™ sports 8 ANT Neuro	86 x 100 x 162 100 g	No wireless USB3 based	8 uni., 0 bipolar, None	2 bit	2048 Hz +/- 1000 mV	host bat- tery dep.	Active shielding
Quick-8r/20r CGX, Cognionics	20 x 18 x 19 596 g	Bluetooth LE No local storage	8/20 unip., 0 bipolar 3D Accelerometer	None	500 Hz unknown	6 h	
g.Nautilus 8/16/32 g.tec	78 x 60 x 26 110 g	Wifi, 2.4 GHz No local storage	8/16/32 unip., 4/8/16 bip (shared)	8 bit (base station)	500 Hz +/- 2250 mV	10 h	
Versatile EEG 8/16 BitBrain	n.a. 192/290 g	BT v2.1+DER SD Card	8 unip., 0 bipolar 9D Gyro+Acc+Mag.	1x digital, 1x optical	256 Hz +/- 100 unip. +/- 400 bip.	8 h	
Air BitBrain	Head cap sized 212g (cap+amp)	BT v2.1+DER SD Card	12 unip., 0 bipolar 9D Gyro+Acc+Mag.	1x digital, 1x optical	256 Hz +/- 100 mV	8 h	Preset montage, active shielding, DRL
Diadem BitBrain	Head cap sized 307g (cap+amp)	BT v2.1+DER SD Card	12 unip., 0 bipolar 9D Gyro+Acc+Mag.	1x digital, 1x optical	256 Hz +/- 100 mV	3 h	Preset montage, active shielding, DRL
Hero BitBrain	Width 13.4- 16.5 cm, 250 g	BT v2.1+DER SD Card	12 unip., 0 bipolar 9D Gyro+Acc+Mag.	1x digital, 1x optical	256 Hz +/- 100 mV	3 h	Preset montage, active shielding, DRL
Emotiv EPOC+ Emotiv	90 x 150 x 150 170 g	BT LE, USB key No local storage	14 unip., 0 bipolar 9D Gyro+Acc+Mag.	None	256 Hz +/- 4.2 mV	6 h (BLE) 12 h (USB)	Preset montage, DRL
Emotiv EPOCx Emotiv	90 x 150 x 150 170 g	BT 5.0, USB key No local storage	14 unip., 0 bipolar 9D Gyro+Acc+Mag.	None	256 Hz +/- 4.2 mV	6 h (BLE) 12 h (USB)	Preset montage, DRL

Emotiv INSIGHT Emotiv	n.a. n.a.	BT LE, USB key No local storage	5 uni., 0 bipolar, 9D Gyro+Acc+Mag	None	128 Hz +/- 4.2 mV	4 h (BLE) 8 h (USB)	Preset montage, DRL
--------------------------	--------------	------------------------------------	---------------------------------------	------	----------------------	------------------------	------------------------

As can be deduced from the previous paragraphs, there are many sources of artefacts that can interfere with the cortical signal. These artefacts may be inherent to the individual – e.g. eye or bodily movements, ECG signal, or sweat – or due to external sources – e.g. line noise, magnetic fields, or electrode movement. The artefacts inherent to the subject can hardly be prevented when recording in out-of-the-laboratory environments, but there are numerous ways to clean the signal. Using statistical procedures and threshold values during the offline preprocessing, artefactual segments can be detected and excluded from the signal. With the help of more sophisticated statistical procedures like the independent component analysis (ICA), certain artifacts with prototypical features (topography, spectral or temporal properties) can be identified and excluded from the signal without having to discard parts of the data. Contributions of such noisy components can be subtracted from the signal. External noise sources should be avoided generally. Therefore, electrodes should be tightly fixed to the cap to avoid current induction in the cables and disconnection from the scalp (Symeonidou, Nordin, Hairston, & Ferris, 2018). Also, newly developed dual-electrode systems are able to reduce motion-induced noise in the recorded signal (Nordin, Hairston, & Ferris, 2018).

Besides choosing appropriate sensors and amplifiers, a proper setup and a well-controlled experimental framework are also crucial for integrating neurophysiological and behavioral data in studies of information processing. To clarify the framework of a project, it must be clear which parameters are of interest. Before measuring, an a-priori roadmap should define which mental states are under investigation and how those states relate to neurophysiology (for some useful guidance see (Brouwer et al., 2015)). In case the exact timing of events is not crucial – for example when longer lasting mental states are considered – an approximate assignment of time codes to a time period is sufficient for data analyses. In order to implement any temporally more critical external stimulation, trigger signals have to be embedded into the experimental scenario using lightweight electronic stimulus presentation devices like a Raspberry Pi (Kuziek, Shienh, & Mathewson, 2017) or Smartphones (e.g. “Presentation Mobile”, Neurobehavioral Systems, Inc., USA). Integration of experimental information into a more complex laboratory setting with multiple measurement devices can be done by

embedding the environment into the lab streaming layer (LSL) framework that collects and synchronizes information from multiple sources (see, for example <https://github.com/sccn/labstreaminglayer>).

Available physiological parameters

Measures in the frequency domain: Spectral Power

The analysis of spectral power of the EEG (for a review see Al-Fahoum & Al-Fraihat, 2014), most times via Fast Fourier Transform (FFT), has proven to provide meaningful information with respect to human cognition and mental states (Borghini et al., 2014; Wascher, Rasch, et al., 2014). Recent research identified functionally distinct frequency bands, namely the Delta (~0 – 2 Hz), Theta (~3 – 7 Hz), Alpha (~8 – 12 Hz), Beta (~15 – 30 Hz), and Gamma (~30 – 100 Hz) bands.

The phenomenon of mental fatigue has been investigated extensively by means of EEG spectral analysis. Most studies report a shift of spectral power towards lower frequency bands, that is towards Delta, Theta, and Alpha, with increasing time on task (e.g. Fan, Zhou, Liu, & Xie, 2015; Wascher, Rasch, et al., 2014). However, power increases in the Beta band have also been reported (e.g. Craig, Tran, Wijesuriya, & Nguyen, 2012). A recent review by Tran et al. (2020), found Theta and Alpha power increases to be reported most consistently. Thus, alpha power has been proposed as a biomarker for mental fatigue and the associated risk of human error (Lal & Craig, 2001). However, the nature of mental fatigue is still under debate. A depletion of resources due to task demands (e.g. Helton & Warm, 2008) as well as cognitive underload (e.g. Pattyn, Neyt, Henderickx, & Soetens, 2008; Smallwood & Schooler, 2006) were proposed as causal factors. The latter is supported by findings that linked an increase of Alpha power to low vs. high task demands (Gevins, Smith, McEvoy, & Yu, 1997; Wascher et al., 2019), to reactive rather than proactive task engagement (Karthaus, Wascher, & Getzmann, 2018), to phases of mind wandering (Arnau et al., 2020; Compton, Gearinger, & Wild, 2019), and to an internally oriented focus of attention (c.f. Cooper, Croft, Dominey, Burgess, & Gruzelier, 2003; Hanslmayr, Gross, Klimesch, & Shapiro, 2011).

The construct of cognitive workload is also highly relevant for human performance (c.f. Frédéric Dehais, Lafont, Roy, & Fairclough, 2020) as attentional

resources are limited (Just & Carpenter, 1992; Kahnemann, 1973). Executive functioning and working memory capacity constitute a bottleneck in human information processing (Cowan, 2000). For executive functioning, the prefrontal cortex (PFC) and the anterior cingulate cortex (ACC) act as a hub to orchestrate brain areas involved in a given task via inter-area communication (Botvinick, 2007; Helfrich & Knight, 2016; Hopfinger, Buonocore, & Mangun, 2000). Theta band activity, in particular frontal midline Theta, has been linked to the exertion of executive control (Cavanagh & Frank, 2014; Cavanagh & Shackman, 2015; Cavanagh, Zambrano-Vazquez, & Allen, 2012). Theta activity assessed via FFT has been reported to be sensitive to task demands (Gevins et al., 1997; Zakrzewska & Brzezicka, 2014) as well as to cognitive effort (e.g. Smit, Eling, Hopman, & Coenen, 2005). Cognitive effort is crucial for the overall workload, since it determines the amount of resources allocated to a task (c.f. Shenhav et al., 2017).

Measures in the time domain: Event-related potentials

Event-related potentials (ERPs) in the EEG reflect temporally specific and systematic voltage changes evoked by a temporally well-defined event. The basic principle of ERPs is that every act of information processing changes brain-electric activity in a specific way, which can be broken down into temporally distinct cognitive processes (Luck, 2014). The main advantage of using the ERP technique compared to all other neurocognitive approaches is the high temporal resolution which is only limited by the sampling frequency. Positive and negative voltage deflections are interpreted as indicators of particular stages in cognitive processing.

Negative (N1, N2) and positive deflections (P1, P2, P3) give insights into specific aspects of information processing, such as sensory and attentional processes (Kramer, Trejo, & Humphrey, 1995; Pratt, Willoughby, & Swick, 2011; Ullsperger, Freude, & Erdmann, 2001), aspects of subjective and objective stimulus signal intensity (Kramer et al., 1995) and of stimulus probability or relevance (P3) as well as general resource availability. In the applied context, the P3 component (approx. 300-500 ms post-stimulus) is of high interest, as it is correlated with cognitive workload (Allison & Polich, 2008; Kok, 2001).

So far, research on event-related EEG activity is mainly restricted to laboratory settings, testing distinct cognitive factors such as working memory or skill acquisition

that might be important for real world applications. This has been done in highly restricted workplace simulations, for example by Mijovic and colleagues (Mijovic et al., 2017) but also, in a realistic logistics workplace simulation (Wascher, Heppner, et al., 2014a). Wascher and co-workers (2014b) showed distinct changes in ERP-component amplitudes while participants had to deal with different load-inducing situations. The main reason for the sparse use of these EEG measures in realistic environments is the fact that the signal of interest (namely the modulations of EEG activity) is embedded in stochastic noise and spontaneous oscillatory activity. Movement and other high voltage fluctuations make it hard to extract reliable and meaningful ERP measures to evaluate underlying cognitive processes in naturalistic environments.

To obtain a proper evoked signal, many time-distinctive repetitions of equivalent events are needed to perform averaging. In doing so, the afore-mentioned random, task-unrelated noise is removed through the averaging process, leaving only the task-related variability of the event-related signal. Unfortunately, natural environments and tasks lack such repeating events. Thus, there are certain fields of research where it seems necessary to focus on laboratory experiments, especially when considering the research on finely-grained cognitive processing. However, there are possibilities to overcome these shortcomings that will be discussed later in this review.

With amplifiers becoming much smaller and more mobile than just some years ago, study designs were enabled that allowed participants to move in full-body motion, either in laboratory facilities (Gramann et al., 2010; Shaw et al., 2018) or in real-life environments (Ladouce et al., 2016; Ladouce, Donaldson, Dudchenko, & Ietswaart, 2019; Reiser, Wascher, & Arnau, 2019; Reiser, Wascher, Rinkenauer, & Arnau, 2020; Scanlon, Townsend, Cormier, Kuziek, & Mathewson, 2019). Studying the influence of real-world motion on cognitive processes, these studies found that even locomotion impairs the availability of cognitive resources.

And finally, while ERPs are a valid tool for evaluating cognitive processes in high temporal resolution, they may lack some informative content of the frequency domain. There are certain task-related processes that are indicated by modulations of oscillatory activity in the Theta or Alpha frequency range explained earlier, that ERPs simply cannot reveal.

Measures in the time-frequency space: Time-Frequency analyses

Time-frequency analysis allows for analyzing temporal and spectral properties of the EEG simultaneously. The most commonly used methods to perform time-frequency decomposition of the signal are 1) convolving the data with complex Morlet wavelets, 2) the filter-Hilbert-transform, and 3) the short-time FFT (Cohen, 2014). The result of such a signal decomposition is a set of frequency specific time-series of oscillatory power from which event-related spectral perturbations (ERSPs) may be calculated. The ERSP reflects event-related variance in the signal in time-frequency space. Several correlates of psychological constructs and cognitive processes that are relevant to the field of neuroergonomics have been identified using time-frequency analysis.

Event-related frontal Theta activity has been described as indicating stimulus- or response-related cognitive control functioning (Cavanagh & Frank, 2014). It was consequently found to reflect cognitive interference (Nigbur, Ivanova, & Sturmer, 2011), dynamic changes in mental workload in motor and cognitive tasks with varying difficulty (So, Wong, Mak, & Chan, 2017), or cognitive effort (Onton, Delorme, & Makeig, 2005). Furthermore, frontal midline Theta was found to be modulated by task load, multi-tasking, and prolonged focused attention in several basic research and workplace simulation tasks (for an overview see Borghini et al., 2014). In mobile EEG recordings different patterns of Theta activation were found for experimental conditions in which participants were in motion compared to standing, all while performing a cognitive task (Pizzamiglio, Naeem, Abdalla, & Turner, 2017; Reiser et al., 2019; Reiser et al., 2020; Shaw et al., 2018). These results highlight the role of frontal midline Theta as a correlate of central executive mechanism during locomotion that controls resource allocation in situations of cognitive-motor interference.

Modulations in the Alpha band (~8-12 Hz) have been assigned to the orientation of attention and working memory processes. Changes in Alpha power in posterior (visual) brain areas were already observed at the very beginning of EEG research when it was found that Alpha power was suppressed in mental states of open vs. closed eyes (cf. Berger, 1929). This suggests that the oscillatory response of large (visual) neuronal populations were desynchronized. Importantly, the effect is not limited to the bottom-up processing of sensory signals, but can also be used in a top-down way. As proposed by Klimesch, Sauseng, and Hanslmayr (2007), the top-down

synchronization of Alpha oscillations is important for the inhibitory control and timing of information processing. In contrast, a relative desynchronization of Alpha power can be seen as a release from the cortical inhibition and thus promotes goal-oriented processes (Haegens, Handel, & Jensen, 2011; Rosner, Arnau, Skiba, Wascher, & Schneider, 2020; Wöstmann, Herrmann, Maess, & Obleser, 2016).

Finally, central and centro-parietal Mu (~8-12 Hz) and accompanying Beta (~15-30 Hz) oscillations are related to motor planning and the body-centered shifting of attention (see Hari & Salmelin, 1997). When planning an action or awaiting a somatosensation, a desynchronization of Mu/Beta power can be observed in the sensorimotor cortical areas coding for the respective body part (Llanos, Rodriguez, Rodriguez-Sabate, Morales, & Sabate, 2013; Neuper, Wörtz, & Pfurtscheller, 2006; van Ede, de Lange, Jensen, & Maris, 2011). Thus, while changes in the topography of Alpha oscillations over parietal and parieto-occipital brain areas are linked to the orienting of attention in external space, modulations of Mu oscillations over central and centro-parietal regions might be linked to the body-centered focusing of attention. Measuring modulations of Mu and Beta oscillations with mobile EEG setups could thus prove a valuable approach for assessing the planning and execution of actions or the focusing of attention to certain body regions, since the respective oscillatory effects should not significantly be affected by changing environmental conditions. For example, the measurement of topographic distributions of Mu and Beta oscillations via mobile EEG has recently been shown to be a reliable indicator for motor asymmetries in a realistic environment (Packheiser et al., 2020).

The findings reported above indicate that there are reliable electrophysiological correlates of constructs relevant for the field of neuroergonomics in time-frequency space, and that time-frequency decomposition constitutes a valuable tool in mobile EEG research. In the context of driving, for example, mental states could already be categorized with the help of Alpha- and Theta-band activity using small around-the-ear electrode arrays (Wascher et al., 2019). In future studies, these methods could also be deployed to improve interactive and collaborative human-robot or human-machine scenarios, for example, by using a brain-computer interface (e.g. Berka et al., 2005; Blankertz et al., 2010; Dorneich, Ververs, Mathan, & Whitlow, 2005; Dorneich et al., 2007).

Measures using machine learning and artificial intelligence

All of the introduced measures dealt with univariate approaches: a single electrode, or an averaged electrode batch, always concentrating on a narrow topographical field (e.g. frontal midline theta, parietal P3). With advances in computational power, multivariate approaches were made possible so that information about whole scalp activations could be taken into consideration to explain human cognition. Machine learning algorithms have been used to decode multi-dimensional spatial and/or temporal data series. For example, EEG microstates have been used to decipher cognitive states by integrating the information from all electrodes to generate prototypical quasi-steady patterns, giving way to the analysis of cortical interaction activity (Michel & Koenig, 2018). These prototypical states have been used to successfully categorize functionally useful attentional states of individuals (c.f. Brechet et al., 2019; Milz et al., 2016).

Methodological restrictions and work arounds: Event-related analysis in realistic settings

When addressing EEG measurements at workplaces, the core problem for the event-related analysis is the absence of precisely timed repetitive stimulation. In a workplace simulation, probe stimuli might be added to the scenery as noticeable, reappearing events. When presenting task irrelevant probe tones, for example, event-related activity of the EEG indicates whether the tone was attended to or not (Allison & Polich, 2008; Scheer, Bulthoff, & Chuang, 2016). The same applies to the visual domain as EEG activity indicates the spatial distribution of attention (e.g. Luck). Attention to a particular part of a scene should be reflected in modulated ERP responses to randomly presented light flashes at different locations of a scene. With the help of augmented reality via data glasses and the use of scene cameras (e.g. implemented into a mobile eye tracker) such an approach could also be applied to realistic settings. However, the processing of the probe stimulus may exacerbate the assessment of the work-related cognitive processes of interest.

An alternative approach to get precise timing in natural settings might be to use events that are inherent to the environment or to the behavior of the participant.

Systematic external events with a high number of repetitions are hardly ever found in a natural environment and often lack a sudden onset needed for exact time-locked averaging. Visual events normally build up as smoothly arising changes in the scene, at least when the observer is moving. A solution to this problem that relies on the inherent behavior of the acting person is the measurement of eye movement parameters. Eye movements are strongly connected to visual information processing and temporally well-defined. This holds true both for saccadic eye movements and for eye blinks.

Saccades (see Viviani, 1990) are brief, fast movements of the eyes that change the point of fixation towards an object of interest. They reflect the overt orienting of attention. Using this behavior for EEG research, fixation-related potentials (FRPs) have repeatedly been reported in studies that investigate visual search (Hiebel et al., 2018; Kamienkowski, Ison, Quiroga, & Sigman, 2012; Kamienkowski, Varatharajah, Sigman, & Ison, 2018; Kaunitz et al., 2014). Kaunitz et al. (2014) demonstrated that sensory and cognitive FRP components were similar to stimulus driven ERPs when time-locked to the onset of a fixation. Moreover, effects of task load are reflected in FRPs in a similar manner as in ERPs (Ries, Touryan, Ahrens, & Connolly, 2016)

Modulations in fixation related potentials may predict whether fixated content will be encoded or not. This could be shown for pictorial content (Nikolaev, Nakatani, Plomp, Jurica, & van Leeuwen, 2011) as well as the meaning of words during reading (A. Frey, Lemaire, Vercueil, & Guerin-Dugue, 2018; Sato & Mizuhara, 2018). Furthermore, the decoding of emotional expressions has been studied in regular lab settings (Guerin-Dugue et al., 2018; Simola, Le Fevre, Torniainen, & Baccino, 2015) and with mobile EEG in natural settings (Soto et al., 2018).

However, there is a substantial problem of saccade-related EEG analyses outside of the laboratory, namely motion. Humans are not able to move their eyes voluntarily in a slow, continuous, and steady motion. Saccades are discrete events that occur when information processing is finished at a particular spatial location and new content is attended to. When motion is involved, our eyes follow moving objects smoothly, even for longer time intervals, when aspects of this object are relevant to the task (Robinson, 1965). Thus, when motion is part of participants' behavior or the scene, re-orienting of attention is not necessarily a discrete shift of gaze.

Consequently, saccades are losing their temporal information with respect to attention allocation.

Blinking appears to be more interesting for real life evaluations for several reasons. Beside saccades, blinking and eye closure play a large role in mental state detection. In fatigue detection for example, average blink duration has been shown to correlate with operator state (Funke et al., 2017; Papadelis et al., 2007; Rohit et al., 2017).

Besides being a measure on its own, eye blinks can also be useful to create events inherent to the experimental situation without further stimulation. It is generally accepted that blinks may occur either voluntarily, due to startling signals (in order to protect the eye), or occur stochastically distributed in order to maintain the tear film on the cornea. The latter, however, is to be questioned. First of all, blink frequency strongly varies with the neurotransmitter dopamine (Karson, 1983) and thus also with motivational characteristics (Colzato, Slagter, SCAPE, & Hommel, 2008). Secondly, blinks occur predominantly at the end of an information stream, e.g. at the end of scenes when watching movies, or at the end of a sentence when reading (Fogarty & Stern, 1989; Nakano, Yamamoto, Kitajo, Takahashi, & Kitazawa, 2009). In laboratory settings, blinks have been observed after a decision was made or at the end of an experimental trial, when information processing is finished (Wascher, Heppner, Mockel, Kobald, & Getzmann, 2015). Even when auditory information is processed, the same timing of eye blinks occurs (Kobald, Wascher, Heppner, & Getzmann, 2019). Thus, eye blinks may be reliable markers of information segmentation.

This assumption can be supported by event-related activity of the brain. Following the eye blink, an N1-like component can be observed, but this only happened when blinking in an illuminated surrounding – in darkness no ERP occurred (Heuser-Link, Dirlich, Berg, Vogl, & Scherg, 1992). The same can be observed for the cognitive P3 component of the ERP (Berg & Davies, 1988). MEG studies showed that eye blinks activate the precuneus regions, indicating increased environmental monitoring and awareness (C. C. Liu, Ghosh Hajra, Cheung, Song, & D'Arcy, 2017). Additionally, blink evoked modulations have been reported in the context of ERSPs (Bonfiglio et al., 2013; Bonfiglio et al., 2009). In a more applied setting, namely the simulation of a logistics work-place, Wascher et al. (2014b; 2016) have shown that

both blink-evoked ERSPs and ERPs provide valuable information about cognitive load measured with mobile EEG.

Hands-on neuroergonomics

As can be deduced from the previous sections, (mobile) EEG is a viable and cost-effective method to get a grasp of cognitive processes underlying many aspects of working life. When no overt behavior is available to make assumptions about an individual's cognitive state, EEG has the potential to elucidate processes unknown to the distant observer. Attention- and fatigue-related EEG investigations have proven the measurement's usefulness in many areas of life, such as driving (e.g. Borghini et al., 2014; Getzmann et al., 2018; Lin et al., 2014) or operating a machine (Arico et al., 2016). By decoding cognitive states of individuals, adaptive technological procedures can be regulated either to boost the individual's attentional focus towards the task or to intercept decreasing wakefulness by enhancing aid by the system. The EEG can also be used to determine aspects of higher-order constructs such as situational awareness to be used in the previously mentioned interventions.

Besides the pure attentional state, there are plenty of psychological constructs relevant for the positive outcome in sociotechnical systems, e.g. emotion and affect (for a short overview see (J. Frey, Mühl, Lotte, & Hachet, 2014) that can also be classified by using neurophysiological measures (Zander & Jatzev, 2009). This is crucial for situations that could entail hazardous results in case a system user is not able to respond to situational requirements due to maladjusted states of arousal or affect, as for example during driving (Thirunavukkarasu, Abdi, & Mohajer, 2016). It is also possible to improve usability evaluations using EEG emotion classification during the interaction with everyday utensils (Sargent et al., 2020).

With the increasing mobility of EEG devices, these use-cases can be extended from seated conditions, such as driving or static machine interaction, to naturalistic scenarios. Several correlates could be classified in such environments, e.g. workload and cognitive processing while riding a bike (McLean, Scanlon, Singhal, & Mathewson, 2017; Scanlon et al., 2019), or affective and recreational states while walking through three different urban areas (Aspinall, Mavros, Coyne, & Roe, 2015). By using a mobile phone running a software to synchronize data-streams of motion-tracking, EEG, and eye-tracking (e.g. Lab Streaming LayerKothe, 2014), it would be

possible to get insights into everyday interaction in socio-technical systems without social, environmental, or behavioral constraints, of course while minding the pitfalls of the involved techniques (Brouwer et al., 2015).

Discussion

The aim of cognitive neuroergonomics is to improve safety and well-being in workplaces or everyday environments with the help of neurophysiological measures that allow to understand mental mechanisms of workers under specific work requirements (Mehta & Parasuraman, 2013; Parasuraman, 2011). Based on this knowledge, working and everyday environments can be modified for enhanced safety and work efficiency (Berka et al., 2004; Dorneich et al., 2005; Dorneich et al., 2007; Wilson & Russell, 2007). To this end, the following issues need to be addressed – in convergence and addition to those points made by Brouwer and colleagues (2015):

- 1) Concepts and measures of cognitive neuroergonomics should allow to track mental states in order to evaluate specifics of a particular workplace.
- 2) The continuous tracking of worker states should allow the identification of individual load in specific work situations, i.e. detecting moments of mental strain.
- 3) Cognitive neuroergonomics aims at the evaluation of information processing in regular and ambulatory working situations under consideration of the aspects mentioned in 1) and 2).
- 4) Based on this approach, countermeasures can be developed that protect the worker from adverse health issues and ensure work quality in safety-critical work places (e.g. Huang, Jung, Chuang, Ko, & Lin, 2012).

Along this path, the first steps have been taken since mobile EEG measurement became feasible and the extracted parameters demonstrated high reliability despite the challenges that come with mobile EEG recordings. Technically, the online evaluation of the data is now possible in conjunction with closed loop systems that feed mental state related parameters back to the worker. However, the data base of mobile EEG evaluations in free body motion is sparse. Data from driving or flight simulations cannot be considered, because these data are recorded in rather static

environments under highly controlled environmental conditions. Also, regular gait studies have limited explanatory power, since treadmill walking is a rather rhythmic movement that represents a well-learned and automated motion and is assumed to not consume many cognitive resources. Unpredictable movement behavior, as is inherent to many workplaces or walking in nature, may interact with cognition in a differential manner and, with respect to the measure, provoke a yet unknown pattern of artifacts.

So far, most neuroergonomics studies addressed a description of the subject's state. In particular measures in the frequency domain provide reliable access to cognitive constructs such as mental fatigue, attention allocation, or mental load. These measures form the basis of neuroergonomics research since they are relatively robust against singular artifacts, that are unavoidable when participants are moving freely. Results from previous simulator and laboratory studies show a high similarity to the results in natural settings and therefore allow to transfer the existing knowledge to the field. In addition to the rather objective access to user states in almost any environment by using response times or measures of primary task performance, mobile EEG allows to establish neuronal models in order to gain an understanding of the implementation of worker states into neural interactions in a broader sense. Based on these neuronal models, well-founded countermeasures to avoid undesired worker states can be developed.

Neurophysiological measures of cognitive processing, i.e. the entire cascade of information processing from signal input to action execution become accessible with mobile EEG. However, work-related environments that require unrestricted movement need the design and evaluation of new study approaches (such as eye blink or fixation-related analyses) to enhance mobile EEG measurements. In this way, all parameters that have previously been established in the laboratory or in restricted simulation environments may be accessible. The application of mobile EEG methods in real workplaces, however, still faces some unresolved problems. It would be recommended that the equipment used for recording the EEG should be unobtrusive and (almost) invisible to others to not hinder the worker to behave normally. This can be achieved with headband-based systems or with the use of adhesive electrodes (e.g. cEEGrids, University of Oldenburg, Germany). However, these systems cover only a small area of the skull and therefore do not allow for a clear separation of

cortical sources or more specifically, of the sources' origins. Thus, a validation of such constrained measures with data that is collected with extended multi-channel systems in a realistic simulation appears necessary. In general, all the psychological constructs outlined above need to be evaluated systematically in real life environments in order to understand how the human brain processes information in working situations. For the validation, other physiological measures with a longer history of mobile measurements of mental states need to be considered (e.g. HRV, EDA, or salivary cortisol) (Dirican & Göktürk, 2011; Fairclough & Venables, 2006).

Conclusion

Building on decades of knowledge about cognitive functioning obtained using EEG in laboratory conditions, the application in real-world paradigms in order to bridge the gap between behavior and mind is very compelling as recording technologies become smaller and smaller. Studies in workplace and real-life simulations have already shown that the EEG is suitable to quantify mental workload with very high accuracy – maybe higher than the accuracy of other physiological measures, for example the electrocardiogram or eye movements (S. Ahn, Nguyen, Jang, Kim, & Jun, 2016; Hankins & Wilson, 1998; Hogervorst et al., 2014; Wilson, 2002). With recent technical developments allowing increasingly smaller recording devices, mobile EEG can be applied in many fields. In particular, considering the field of ergonomics, mobile EEG can be downsized to the point of being almost unobtrusive in regular working environments. Thus, it provides the potential to track mental aspects of diverse workplaces. Neurophysiological correlates of cognitive processes during work can be assessed in a depth comparable to laboratory studies. And while there still may be some shortcomings of mobile EEG compared to its laboratory counterpart, such as the potential for noisier data and the lack of temporally precise stimulation, all of these can be overcome and will surely be overcome in near future. And last but not least, some interesting approaches to the mobile measurement of EEG have been outlined in this overview, which provide completely new insights into cognition at the workplace.

- 728 a. **Mobile EEG** provides objectifiable access to mental states and cognitive
729 processing during work
- 730 b. **Recent developments** both with respect to hardware and data processing
731 techniques allow concept-based research in almost any natural environment.
- 732 c. Measures of brain activity, however, need to be carefully adjusted to the
733 mental concepts addressed.
- 734
- 735
- 736
- 737

738 References

- 739
- 740 Ahn, J. W., Ku, Y., & Kim, H. C. (2019). A Novel Wearable EEG and ECG Recording System for
741 Stress Assessment. *Sensors*, 19(9).
- 742 Ahn, S., Nguyen, T., Jang, H., Kim, J. G., & Jun, S. C. (2016). Exploring Neuro-Physiological
743 Correlates of Drivers' Mental Fatigue Caused by Sleep Deprivation Using
744 Simultaneous EEG, ECG, and fNIRS Data. *Frontiers in Human Neuroscience*, 10.
- 745 Al-Barrak, L., Kanjo, E., & Younis, E. M. G. (2017). NeuroPlace: Categorizing urban places
746 according to mental states. *Plos One*, 12(9).
- 747 Al-Fahoum, A. S., & Al-Fraihat, A. A. (2014). Methods of EEG signal features extraction using
748 linear analysis in frequency and time-frequency domains. *ISRN Neurosci*, 2014,
749 730218.
- 750 Allison, B. Z., & Polich, J. (2008). Workload assessment of computer gaming using a single-
751 stimulus event-related potential paradigm. *Biological Psychology*, 77(3), 277-283.
- 752 Arico, P., Borghini, G., Di Flumeri, G., Colosimo, A., Bonelli, S., Golfetti, A., . . . Babiloni, F.
753 (2016). Adaptive Automation Triggered by EEG-Based Mental Workload Index: A
754 Passive Brain-Computer Interface Application in Realistic Air Traffic Control
755 Environment. *Frontiers in Human Neuroscience*, 10.
- 756 Arnau, S., Loffler, C., Rummel, J., Hagemann, D., Wascher, E., & Schubert, A. L. (2020). Inter-
757 trial alpha power indicates mind wandering. *Psychophysiology*, 57(6), e13581.
- 758 Arnau, S., Wascher, E., & Kuper, K. (2019). Age-related differences in reallocating cognitive
759 resources when dealing with interruptions. *Neuroimage*, 191, 292-302.
- 760 Aspinall, P., Mavros, P., Coyne, R., & Roe, J. (2015). The urban brain: analysing outdoor
761 physical activity with mobile EEG. *British Journal of Sports Medicine*, 49(4), 272-U291.
- 762 Baek, H., & Min, B. K. (2015). Blue light aids in coping with the post-lunch dip: an EEG study.
763 *Ergonomics*, 58(5), 803-810.
- 764 Banaei, M., Hatami, J., Yazdanfar, A., & Gramann, K. (2017). Walking through Architectural
765 Spaces: The Impact of Interior Forms on Human Brain Dynamics. *Frontiers in Human
766 Neuroscience*, 11.
- 767 Barham, M. P., Clark, G. M., Hayden, M. J., Enticott, P. G., Conduit, R., & Lum, J. A. G. (2017).
768 Acquiring research-grade ERPs on a shoestring budget: A comparison of a modified
769 Emotiv and commercial SynAmps EEG system. *Psychophysiology*, 54(9), 1393-1404.
- 770 Bateson, A. D., Baseler, H. A., Paulson, K. S., Ahmed, F., & Asghar, A. U. R. (2017).
771 Categorisation of Mobile EEG: A Researcher's Perspective. *Biomed Research
772 International*.
- 773 Berg, P., & Davies, M. B. (1988). Eyeblink-related potentials. *Electroencephalogr Clin
774 Neurophysiol*, 69(1), 1-5.
- 775 Berger, H. (1929). Über das Elektrenkephalogramm des Menschen. *Archiv für Psychiatrie und
776 Nervenkrankheiten*, 87(1), 527-570.
- 777 Berka, C., Levendowski, D. J., Cvetinovic, M. M., Petrovic, M. M., Davis, G., Lumicao, M. N., . .
778 . Olmstead, R. (2004). Real-time analysis of EEG indexes of alertness, cognition, and
779 memory acquired with a wireless EEG headset. *International Journal of Human-
780 Computer Interaction*, 17(2), 151-170.
- 781 Berka, C., Levendowski, D. J., Ramsey, C. K., Davis, G., Lumicao, M. N., Stanney, K., . . . Stibler,
782 K. (2005). Evaluation of an EEG workload model in an Aegis simulation environment.
783 In J. A. Caldwell & N. J. Wesensten (Eds.), *Biomonitoring for Physiological and
784 Cognitive Performance during Military Operations* (Vol. 5797, pp. 90-99).

Blankertz, B., Tangermann, M., Vidaurre, C., Fazli, S., Sannelli, C., Haufe, S., . . . Muller, K. R. (2010). The Berlin Brain-Computer Interface: Non-Medical Uses of BCI Technology. *Front Neurosci*, 4, 198.

Bleichner, M. G., & Debener, S. (2017). Concealed, Unobtrusive Ear-Centered EEG Acquisition: cEEGrids for Transparent EEG. *Frontiers in Human Neuroscience*, 11.

Bleichner, M. G., Lundbeck, M., Selisky, M., Minow, F., Jager, M., Emkes, R., . . . De Vos, M. (2015). Exploring miniaturized EEG electrodes for brain-computer interfaces. An EEG you do not see? *Physiological Reports*, 3(4).

Blum, S., Jacobsen, N. S. J., Bleichner, M. G., & Debener, S. (2019). A Riemannian Modification of Artifact Subspace Reconstruction for EEG Artifact Handling. *Frontiers in Human Neuroscience*, 13.

Bonfiglio, L., Olcese, U., Rossi, B., Frisoli, A., Arrighi, P., Greco, G., . . . Carboncini, M. C. (2013). Cortical source of blink-related delta oscillations and their correlation with levels of consciousness. *Human Brain Mapping*, 34(9), 2178-2189.

Bonfiglio, L., Sello, S., Andre, P., Carboncini, M. C., Arrighi, P., & Rossi, B. (2009). Blink-related delta oscillations in the resting-state EEG: a wavelet analysis. *Neuroscience Letters*, 449(1), 57-60.

Borghini, G., Astolfi, L., Vecchiato, G., Mattia, D., & Babiloni, F. (2014). Measuring neurophysiological signals in aircraft pilots and car drivers for the assessment of mental workload, fatigue and drowsiness. *Neurosci Biobehav Rev*, 44, 58-75.

Botvinick, M. M. (2007). Conflict monitoring and decision making: Reconciling two perspectives on anterior cingulate function. *Cognitive Affective & Behavioral Neuroscience*, 7, 356-366.

Brechet, L., Brunet, D., Birot, G., Gruetter, R., Michel, C. M., & Jorge, J. (2019). Capturing the spatiotemporal dynamics of self-generated, task-initiated thoughts with EEG and fMRI. *Neuroimage*, 194, 82-92.

Brouwer, A. M., Zander, T. O., van Erp, J. F., Korteling, J. E., & Bronkhorst, A. W. (2015). Using neurophysiological signals that reflect cognitive or affective state: six recommendations to avoid common pitfalls. *Frontiers in Neuroscience*, 9.

Cavanagh, J. F., & Frank, M. J. (2014). Frontal theta as a mechanism for cognitive control. *Trends in Cognitive Sciences*, 18(8), 414-421.

Cavanagh, J. F., & Shackman, A. J. (2015). Frontal midline theta reflects anxiety and cognitive control: meta-analytic evidence. *J Physiol Paris*, 109(1-3), 3-15.

Cavanagh, J. F., Zambrano-Vazquez, L., & Allen, J. J. (2012). Theta lingua franca: a common mid-frontal substrate for action monitoring processes. *Psychophysiology*, 49(2), 220-238.

Chang, C. Y., & Chen, P. K. (2005). Human Response to Window Views and Indoor Plants in the Workplace. *HortScience*, 40, 1354-1359.

Cinel, C., Valeriani, D., & Poli, R. (2019). Neurotechnologies for Human Cognitive Augmentation: Current State of the Art and Future Prospects. *Frontiers in Human Neuroscience*, 13.

Cohen, M. X. (2014). *Analyzing Neural Time Series Data: Theory and Practice*. Cambridge, MA: The MIT press.

Colzato, L. S., Slagter, H. A., Spape, M. M. A., & Hommel, B. (2008). Blinks of the eye predict blinks of the mind. *Neuropsychologia*, 46(13), 3179-3183.

Compton, R. J., Gearinger, D., & Wild, H. (2019). The wandering mind oscillates: EEG alpha power is enhanced during moments of mind-wandering. *Cognitive, Affective, & Behavioral Neuroscience*, 19(5), 1184-1191.

- Cooper, N. R., Croft, R. J., Dominey, S. J. J., Burgess, A. P., & Gruzelier, J. H. (2003). Paradox lost? Exploring the role of alpha oscillations during externally vs. internally directed attention and the implications for idling and inhibition hypotheses. *International Journal of Psychophysiology*, 47, 65-74.
- Cowan, N. (2000). The magical number 4 in short-term memory: A reconsideration of mental storage capacity. *Behavioral and Brain Sciences*, 24, 87-185.
- Craig, A., Tran, Y., Wijesuriya, N., & Nguyen, H. (2012). Regional brain wave activity changes associated with fatigue. *Psychophysiology*, 49(4), 574-582.
- Cruz-Garza, J. G., Brantley, J. A., Nakagome, S., Kontson, K., Megjhani, M., Robleto, D., & Contreras-Vidal, J. L. (2017). Deployment of Mobile EEG Technology in an Art Museum Setting: Evaluation of Signal Quality and Usability. *Frontiers in Human Neuroscience*, 11.
- Dash, D., Hernandez-Ronquillo, L., Moien-Afshari, F., & Tellez-Zenteno, J. F. (2012). Ambulatory EEG: a cost-effective alternative to inpatient video-EEG in adult patients. *Epileptic Disorders*, 14(3), 290-297.
- Dehais, F., Dupres, A., Di Flumeri, G., Verdiere, K., Borghini, G., Babiloni, F., & Roy, R. N. (2018). *Monitoring pilot's cognitive fatigue with engagement features in simulated and actual flight conditions using an hybrid fNIRS-EEG passive BCI*. Paper presented at the 2018 IEEE International Conference on Systems, Man, and Cybernetics (SMC).
- Dehais, F., Lafont, A., Roy, R., & Fairclough, S. (2020). A Neuroergonomics Approach to Mental Workload, Engagement and Human Performance. *Frontiers in Neuroscience*, 14.
- Dehais, F., Somon, B., Mullen, T., & Callan, D. E. (2020). *A neuroergonomics approach to measure pilot's cognitive incapacitation in the real world with EEG*. Paper presented at the AHFE 2019 International Conference on Neuroergonomics and Cognitive Engineering.
- Di Flumeri, G., Arico, P., Borghini, G., Sciaraffa, N., Di Florio, A., & Babiloni, F. (2019). The Dry Revolution: Evaluation of Three Different EEG Dry Electrode Types in Terms of Signal Spectral Features, Mental States Classification and Usability. *Sensors*, 19(6).
- Dirican, A. C., & Göktürk, M. (2011). Psychophysiological measures of human cognitive states applied in human computer interaction. *Procedia Computer Science*, 3, 1361-1367.
- Djebbara, Z., Fich, L. B., Petrini, L., & Gramann, K. (2019). Sensorimotor brain dynamics reflect architectural affordances. *Proceedings of the National Academy of Sciences of the United States of America*, 116(29), 14769-14778.
- Dorneich, M. C., Ververs, P. M., Mathan, S., & Whitlow, S. D. (2005). *A joint human-automation cognitive system to support rapid decision-making in hostile environments*. . Paper presented at the IEEE International Conference on Systems, Man and Cybernetics.
- Dorneich, M. C., Whitlow, S. D., Mathan, S., Ververs, P. M., Erdogmus, D., Adami, A., . . . Lan, T. (2007). Supporting real-time cognitive state classification on a mobile individual. . *Journal of Cognitive Engineering and Decision Making*, 1, 240-270.
- Fairclough, S. H., & Venables, L. (2006). Prediction of subjective states from psychophysiology: A multivariate approach. *Biological Psychology*, 71, 100-110.
- Fan, X., Zhou, Q., Liu, Z., & Xie, F. (2015). Electroencephalogram assessment of mental fatigue in visual search. *Biomed Mater Eng*, 26 Suppl 1, S1455-1463.
- Fogarty, C., & Stern, J. A. (1989). Eye-Movements and Blinks - Their Relationship to Higher Cognitive-Processes. *International Journal of Psychophysiology*, 8(1), 35-42.

- Freeman, F. G., Mikulka, P. J., Prinzl, L. J., & Scerbo, M. W. (1999). Evaluation of an adaptive automation system using three EEG indices with a visual tracking task. *Biological Psychology*, 50(1), 61-76.
- Frey, A., Lemaire, B., Vercueil, L., & Guerin-Dugue, A. (2018). An Eye Fixation-Related Potential Study in Two Reading Tasks: Reading to Memorize and Reading to Make a Decision. *Brain Topography*, 31(4), 640-660.
- Frey, J., Mühl, C., Lotte, F., & Hachet, M. (2014). *Review of the Use of Electroencephalography as an Evaluation Method for Human-Computer Interaction*. Paper presented at the Proceedings of the International Conference on Physiological Computing Systems - Volume 1: PhyCS.
- Funke, M. E., Warm, J. S., Matthews, G., Funke, G. J., Chiu, P. Y., Shaw, T. H., & Greenlee, E. T. (2017). The Neuroergonomics of Vigilance: Effects of Spatial Uncertainty on Cerebral Blood Flow Velocity and Oculomotor Fatigue. *Human Factors*, 59(1), 62-75.
- Gale, J., Signal, T. L., Garden, A. L., & Gander, P. H. (2007). Electroencephalography artifacts in workplace alertness monitoring. *Scand J Work Environ Health*, 33(2), 148-152.
- Gateau, T., Ayaz, H., & Dehais, F. (2018). In silico vs. Over the Clouds: On-the-Fly Mental State Estimation of Aircraft Pilots, Using a Functional Near Infrared Spectroscopy Based Passive-BCI. *Frontiers in Human Neuroscience*, 12.
- Getzmann, S., Arnau, S., Karthaus, M., Reiser, J. E., & Wascher, E. (2018). Age-Related Differences in Pro-active Driving Behavior Revealed by EEG Measures. *Frontiers in Human Neuroscience*, 12, 321.
- Gevins, A., Smith, M. E., McEvoy, L. K., & Yu, D. (1997). High-resolution EEG Mapping of Cortical Activation Related to Working Memory: Effects of Task Difficulty, Type of Processing, and Practice. *Cereb Cortex*, 7, 174-385.
- Giraudet, L., Imbert, J. P., Berenger, M., Tremblay, S., & Causse, M. (2015). The neuroergonomic evaluation of human machine interface design in air traffic control using behavioral and EEG/ERP measures. *Behavioural Brain Research*, 294, 246-253.
- Gramann, K., Fairclough, S. H., Zander, T. O., & Ayaz, H. (2017). Editorial: Trends in Neuroergonomics. *Frontiers in Human Neuroscience*, 11.
- Gramann, K., Ferris, D. P., Gwin, J., & Makeig, S. (2014). Imaging natural cognition in action. *International Journal of Psychophysiology*, 91(1), 22-29.
- Gramann, K., Gwin, J. T., Bigdely-Shamlo, N., Ferris, D. P., & Makeig, S. (2010). Visual evoked responses during standing and walking. *Frontiers in Human Neuroscience*, 4, 202.
- Gramann, K., Jung, T. P., Ferris, D. P., Lin, C. T., & Makeig, S. (2014). Toward a new cognitive neuroscience: modeling natural brain dynamics. *Frontiers in Human Neuroscience*, 8.
- Guerin-Dugue, A., Roy, R. N., Kristensen, E., Rivet, B., Vercueil, L., & Tcherkassof, A. (2018). Temporal Dynamics of Natural Static Emotional Facial Expressions Decoding: A Study Using Event- and Eye Fixation-Related Potentials. *Frontiers in Psychology*, 9.
- Guo, Z. Z., Pan, Y. F., Zhao, G. Z., Cao, S., & Zhang, J. (2018). Detection of Driver Vigilance Level Using EEG Signals and Driving Contexts. *Ieee Transactions on Reliability*, 67(1), 370-380.
- Haegens, S., Handel, B. F., & Jensen, O. (2011). Top-down controlled alpha band activity in somatosensory areas determines behavioral performance in a discrimination task. *Journal of Neuroscience*, 31(14), 5197-5204.
- Hancock, P. A. (2019). Neuroergonomics: Where the Cortex Hits the Concrete. *Frontiers in Human Neuroscience*, 13.

926 Hankins, T. C., & Wilson, G. F. (1998). A comparison of heart rate, eye activity, EEG and
 927 subjective measures of pilot mental workload during flight. *Aviation Space and*
 928 *Environmental Medicine*, 69(4), 360-367.

929 Hanslmayr, S., Gross, J., Klimesch, W., & Shapiro, K. L. (2011). The role of alpha oscillations in
 930 temporal attention. *Brain Research Reviews*, 67(1-2), 331-343.

931 Hari, R., & Salmelin, R. (1997). Human cortical oscillations: a neuromagnetic view through
 932 the skull. *Trends Neurosci*, 20(1), 44-49.

933 Helfrich, R. F., & Knight, R. T. (2016). Oscillatory Dynamics of Prefrontal Cognitive Control.
 934 *Trends in Cognitive Sciences*, 20(12), 916-930.

935 Helton, W. S., & Warm, J. S. (2008). Signal salience and the mindlessness theory of vigilance.
 936 *Acta Psychol (Amst)*, 129(1), 18-25.

937 Heuser-Link, M., Dirlich, G., Berg, P., Vogl, L., & Scherg, M. (1992). Eyeblinks evoke potentials
 938 in the occipital brain region. *Neuroscience Letters*, 143(1-2), 31-34.

939 Hiebel, H., Ischebeck, A., Brunner, C., Nikolaev, A. R., Hofler, M., & Korner, C. (2018). Target
 940 probability modulates fixation-related potentials in visual search. *Biological*
 941 *Psychology*, 138, 199-210.

942 Hogervorst, M. A., Brouwer, A. M., & van Erp, J. B. E. (2014). Combining and comparing EEG,
 943 peripheral physiology and eye-related measures for the assessment of mental
 944 workload. *Frontiers in Neuroscience*, 8.

945 Hopfinger, J. B., Buonocore, M. H., & Mangun, G. R. (2000). The neural mechanisms of top-
 946 down attentional control. *Nature Neuroscience*, 3, 284-291.

947 Huang, K. C., Jung, T. P., Chuang, C. H., Ko, L. W., & Lin, C. T. (2012). Preventing Lapse in
 948 Performance using a Drowsiness Monitoring and Management System. *2012 Annual*
 949 *International Conference of the Ieee Engineering in Medicine and Biology Society*
 950 *(Embc)*, 3336-3339.

951 Hwang, S., Jebelli, H., Choi, B., Choi, M., & Lee, S. (2018). Measuring Workers' Emotional
 952 State during Construction Tasks Using Wearable EEG. *Journal of Construction*
 953 *Engineering and Management*, 144(7).

954 Jebelli, H., Hwang, S., & Lee, S. (2018). EEG-based workers' stress recognition at construction
 955 sites. *Automation in Construction*, 93, 315-324.

956 Jungnickel, E., & Gramann, K. (2016). Mobile Brain/Body Imaging (MoBI) of Physical
 957 Interaction with Dynamically Moving Objects. *Frontiers in Human Neuroscience*, 10.

958 Just, M. A., & Carpenter, P. A. (1992). A Capacity Theory of Comprehension: Individual
 959 Differences in Working Memory. *Psychological Review*, 99, 122-149.

960 Kahnemann, D. (1973). *Attention and Effort*. Englewood Cliffs, New Jersey: Prentice-Hall Inc.

961 Kamienkowski, J. E., Ison, M. J., Quiroga, R. Q., & Sigman, M. (2012). Fixation-related
 962 potentials in visual search: A combined EEG and eye tracking study. *Journal of Vision*,
 963 12(7).

964 Kamienkowski, J. E., Varatharajah, A., Sigman, M., & Ison, M. J. (2018). Parsing a mental
 965 program: Fixation-related brain signatures of unitary operations and routines in
 966 natural visual search. *Neuroimage*, 183, 73-86.

967 Karson, C. N. (1983). Spontaneous eye-blink rates and dopaminergic systems. *Brain*, 106 (Pt
 968 3), 643-653.

969 Karthaus, M., Wascher, E., & Getzmann, S. (2018). Proactive vs. reactive car driving: EEG
 970 evidence for different driving strategies of older drivers. *Plos One*, 13(1), e0191500.

971 Kaunitz, L. N., Kamienkowski, J. E., Varatharajah, A., Sigman, M., Quiroga, R. Q., & Ison, M. J.
 972 (2014). Looking for a face in the crowd: Fixation-related potentials in an eye-
 973 movement visual search task. *Neuroimage*, 89, 297-305.

974 Keum, N. H., Lee, T., Lee, J. B., & In, H. P. (2018). Measuring the Degree of Content
 975 Immersion in a Non-experimental Environment Using a Portable EEG Device. *Journal*
 976 *of Information Processing Systems*, 14(4), 1049-1061.

977 Khushaba, R. N., Wise, C., Kodagoda, S., Louviere, J., Kahn, B. E., & Townsend, C. (2013).
 978 Consumer neuroscience: Assessing the brain response to marketing stimuli using
 979 electroencephalogram (EEG) and eye tracking. *Expert Systems with Applications*,
 980 40(9), 3803-3812.

981 Klimesch, W., Sauseng, P., & Hanslmayr, S. (2007). EEG alpha oscillations: the inhibition-
 982 timing hypothesis. *Brain Research Reviews*, 53(1), 63-88.

983 Kobald, S. O., Wascher, E., Heppner, H., & Getzmann, S. (2019). Eye blinks are related to
 984 auditory information processing: evidence from a complex speech perception task.
 985 *Psychol Res*, 83(6), 1281-1291.

986 Kok, A. (2001). On the utility of P3 amplitude as a measure of processing capacity.
 987 *Psychophysiology*, 38(3), 557-577.

988 Kothe, C. (2014). Lab Streaming Layer (LSL). . <https://github.com/sccn/labstreaminglayer>.

989 Kramer, A. F., Trejo, L. J., & Humphrey, D. (1995). Assessment of Mental Workload with Task-
 990 Irrelevant Auditory Probes. *Biological Psychology*, 40(1-2), 83-100.

991 Kramer, A. F., Wickens, C. D., & Donchin, E. (1985). Processing of stimulus properties:
 992 evidence for dual-task integrality. *Journal of Experimental Psychology, HUMAN*
 993 *Perception and PERFORMANCE*, 11, 383-408.

994 Kuziek, J. W. P., Shienh, A., & Mathewson, K. E. (2017). Transitioning EEG experiments away
 995 from the laboratory using a Raspberry Pi 2. *Journal of Neuroscience Methods*, 277,
 996 75-82.

997 Ladouce, S., Donaldson, D. I., Dudchenko, P. A., & Ietswaart, M. (2016). Understanding
 998 Minds in Real-World Environments: Toward a Mobile Cognition Approach. *Frontiers*
 999 *in Human Neuroscience*, 10, 694.

1000 Ladouce, S., Donaldson, D. I., Dudchenko, P. A., & Ietswaart, M. (2019). Mobile EEG identifies
 1001 the re-allocation of attention during real-world activity. *Sci Rep*, 9(1), 15851.

1002 Lal, S. K. L., & Craig, A. (2001). A critical review of the psychophysiology of driver fatigue.
 1003 *Biological Psychology*, 55(3), 173-194.

1004 Lin, C. T., Chuang, C. H., Huang, C. S., Tsai, S. F., Lu, S. W., Chen, Y. H., & Ko, L. W. (2014).
 1005 Wireless and Wearable EEG System for Evaluating Driver Vigilance. *Ieee Transactions*
 1006 *on Biomedical Circuits and Systems*, 8(2), 165-176.

1007 Liu, C. C., Ghosh Hajra, S., Cheung, T. P. L., Song, X., & D'Arcy, R. C. N. (2017). Spontaneous
 1008 Blinks Activate the Precuneus: Characterizing Blink-Related Oscillations Using
 1009 Magnetoencephalography. *Frontiers in Human Neuroscience*, 11, 489.

1010 Liu, N. H., Chiang, C. Y., & Hsu, H. M. (2013). Improving Driver Alertness through Music
 1011 Selection Using a Mobile EEG to Detect Brainwaves. *Sensors*, 13(7), 8199-8221.

1012 Llanos, C., Rodriguez, M., Rodriguez-Sabate, C., Morales, I., & Sabate, M. (2013). Mu-rhythm
 1013 changes during the planning of motor and motor imagery actions. *Neuropsychologia*,
 1014 51(6), 1019-1026.

1015 Lohani, M., Payne, B. R., & Strayer, D. L. (2019). A Review of Psychophysiological Measures
 1016 to Assess Cognitive States in Real-World Driving. *Frontiers in Human Neuroscience*,
 1017 13.

1018 Luck, S. J. (2014). *An introduction to the event-related potential technique*. Cambridge, MA:
 1019 MIT Press.

1020 Makeig, S., Gramann, K., Jung, T. P., Sejnowski, T. J., & Poizner, H. (2009). Linking brain, mind
 1021 and behavior. *International Journal of Psychophysiology*, 73(2), 95-100.

- Matthews, G., Reinerman-Jones, L. E., Barber, D. J., & Abich, J. (2015). The Psychometrics of Mental Workload: Multiple Measures Are Sensitive but Divergent. *Human Factors*, 57(1), 125-143.
- Mavros, P., Austwick, M. Z., & Smith, A. H. (2016). Geo-EEG: Towards the Use of EEG in the Study of Urban Behaviour. *Applied Spatial Analysis and Policy*, 9(2), 191-212.
- McKendrick, R., Parasuraman, R., Murtza, R., Formwalt, A., Baccus, W., Paczynski, M., & Ayaz, H. (2016). Into the Wild: Neuroergonomic Differentiation of Hand-Held and Augmented Reality Wearable Displays during Outdoor Navigation with Functional Near Infrared Spectroscopy. *Frontiers in Human Neuroscience*, 10.
- McKeown, C. (2014). Neuroergonomics: a cognitive neuroscience approach to human factors and ergonomics. *Ergonomics*, 57(1), 137-138.
- McLean, T., Scanlon, J., Singhal, A., & Mathewson, K. (2017). Your Brain in the World: Investigating the N1 and P2 for Ecological Stimuli. *Psychophysiology*, 54, S75-S75.
- Mehta, R. K., & Parasuraman, R. (2013). Neuroergonomics: a review of applications to physical and cognitive work. *Frontiers in Human Neuroscience*, 7.
- Michel, C. M., & Koenig, T. (2018). EEG microstates as a tool for studying the temporal dynamics of whole-brain neuronal networks: A review. *Neuroimage*, 180, 577-593.
- Mijovic, P., Kovic, V., De Vos, M., Macuzic, I., Jeremic, B., & Gligorijevic, I. (2016). Benefits of Instructed Responding in Manual Assembly Tasks: An ERP Approach. *Frontiers in Human Neuroscience*, 10.
- Mijovic, P., Kovic, V., De Vos, M., Macuzic, I., Todorovic, P., Jeremic, B., & Gligorijevic, I. (2017). Towards continuous and real-time attention monitoring at work: reaction time versus brain response. *Ergonomics*, 60(2), 241-254.
- Milz, P., Faber, P. L., Lehmann, D., Koenig, T., Kochi, K., & Pascual-Marqui, R. D. (2016). The functional significance of EEG microstates-Associations with modalities of thinking. *Neuroimage*, 125, 643-656.
- Munoz, Y., Gallego, F. L., Salazar, A. A., & Rodriguez, M. S. (2019). Selling of Products: The Use of Single-Electrode Wireless EEG in Consumer Behavior. *International Journal of Psychological Research*, 12(1), 57-65.
- Nakano, T., Yamamoto, Y., Kitajo, K., Takahashi, T., & Kitazawa, S. (2009). Synchronization of spontaneous eyeblinks while viewing video stories. *Proceedings of the Royal Society B-Biological Sciences*, 276(1673), 3635-3644.
- Neuper, C., Wörtz, M., & Pfurtscheller, G. (2006). ERD/ERS patterns reflecting sensorimotor activation and deactivation. *Prog Brain Res*, 159, 211-222.
- Nigbur, R., Ivanova, G., & Sturmer, B. (2011). Theta power as a marker for cognitive interference. *Clinical Neurophysiology*, 122(11), 2185-2194.
- Nikolaev, A. R., Nakatani, C., Plomp, G., Jurica, P., & van Leeuwen, C. (2011). Eye fixation-related potentials in free viewing identify encoding failures in change detection. *Neuroimage*, 56(3), 1598-1607.
- Nordin, A. D., Hairston, W. D., & Ferris, D. P. (2018). Dual-electrode motion artifact cancellation for mobile electroencephalography. *Journal of Neural Engineering*, 15(5).
- Onton, J., Delorme, A., & Makeig, S. (2005). Frontal midline EEG dynamics during working memory. *Neuroimage*, 27(2), 341-356.
- Packheiser, J., Schmitz, J., Pan, Y., El Basbasse, Y., Friedrich, P., Güntürkün, O., & Ocklenburg, S. (2020). Using Mobile EEG to Investigate Alpha and Beta Asymmetries During Hand and Foot Use. *Front Neurosci*, 14, 109.

- Papadelis, C., Chen, Z., Kourtidou-Papadeli, C., Bamidis, P. D., Chouvarda, L., Bekiaris, E., & Maglaveras, N. (2007). Monitoring sleepiness with on-board electrophysiological recordings for preventing sleep-deprived traffic accidents. *Clinical Neurophysiology*, 118(9), 1906-1922.
- Parasuraman, R. (2003). Neuroergonomics: Research and practice. *Theoretical Issues in Ergonomics Science*, 4(1-2), 5-20.
- Parasuraman, R. (2011). Neuroergonomics: Brain, Cognition, and Performance at Work. *Current Directions in Psychological Science*, 20(3), 181-186.
- Pattyn, N., Neyt, X., Henderickx, D., & Soetens, E. (2008). Psychophysiological investigation of vigilance decrement: boredom or cognitive fatigue? *Physiology & Behavior*, 93(1-2), 369-378.
- Perrier, J., Jongen, S., Vuurman, E., Bocca, M. L., Ramaekers, J. G., & Vermeeren, A. (2016). Driving performance and EEG fluctuations during on-the-road driving following sleep deprivation. *Biological Psychology*, 121, 1-11.
- Pizzamiglio, S., Naeem, U., Abdalla, H., & Turner, D. L. (2017). Neural Correlates of Single- and Dual-Task Walking in the Real World. *Frontiers in Human Neuroscience*, 11.
- Pratt, N., Willoughby, A., & Swick, D. (2011). Effects of working memory load on visual selective attention: behavioral and electrophysiological evidence. *Frontiers in Human Neuroscience*, 5.
- Rahman, M., Karwowski, W., Fafrowicz, M., & Hancock, P. A. (2019). Neuroergonomics Applications of Electroencephalography in Physical Activities: A Systematic Review. *Frontiers in Human Neuroscience*, 13.
- Reiser, J. E., Wascher, E., & Arnau, S. (2019). Recording mobile EEG in an outdoor environment reveals cognitive-motor interference dependent on movement complexity. *Sci Rep*, 9(1), 13086.
- Reiser, J. E., Wascher, E., Rinkenauer, G., & Arnau, S. (2020). Cognitive motor interference in the wild: Assessing the effects of movement complexity on task switching using mobile EEG. *European Journal of Neuroscience*, 1-21.
- Ries, A. J., Touryan, J., Ahrens, B., & Connolly, P. (2016). The Impact of Task Demands on Fixation-Related Brain Potentials during Guided Search. *Plos One*, 11(6).
- Roberts, H., Soto, V., Tyson-Carr, J., Kokmotou, K., Cook, S., Fallon, N., . . . Stancak, A. (2018). Tracking Economic Value of Products in Natural Settings: A Wireless EEG Study. *Frontiers in Neuroscience*, 12.
- Robinson, D. A. (1965). The mechanics of human smooth pursuit eye movement. *J Physiol*, 180(3), 569-591.
- Rohit, F., Kulathumani, V., Kavi, R., Elwarfalli, I., Kecojevic, V., & Nimbarte, A. (2017). Real-time drowsiness detection using wearable, lightweight brain sensing headbands. *Int Intelligent Transport Systems*, 11(5), 255-263.
- Rosner, M., Arnau, S., Skiba, I., Wascher, E., & Schneider, D. (2020). The spatial orienting of the focus of attention in working memory makes use of inhibition: Evidence by hemispheric asymmetries in posterior alpha oscillations. *Neuropsychologia*, 142, 107442.
- Sargent, A., Watson, J., Ye, H., Suri, R., & Ayaz, H. (2020). Neuroergonomic Assessment of Hot Beverage Preparation and Consumption: An EEG and EDA Study. *Frontiers in Human Neuroscience*, 14, 175.
- Sato, N., & Mizuhara, H. (2018). Successful Encoding during Natural Reading Is Associated with Fixation-Related Potentials and Large-Scale Network Deactivation. *Eneuro*, 5(5).

- Scanlon, J. E. M., Townsend, K. A., Cormier, D. L., Kuziek, J. W. P., & Mathewson, K. E. (2019). Taking off the training wheels: Measuring auditory P3 during outdoor cycling using an active wet EEG system. *Brain Research*, 1716, 50-61.
- Scheer, M., Bulthoff, H. H., & Chuang, L. L. (2016). Steering Demands Diminish the Early-P3, Late-P3 and RON Components of the Event-Related Potential of Task-Irrelevant Environmental Sounds. *Frontiers in Human Neuroscience*, 10.
- Shamay-Tsoory, S. G., & Mendelsohn, A. (2019). Real-Life Neuroscience: An Ecological Approach to Brain and Behavior Research. *Perspect Psychol Sci*, 14(5), 841-859.
- Shaw, E. P., Rietschel, J. C., Hendershot, B. D., Pruziner, A. L., Miller, M. W., Hatfield, B. D., & Gentili, R. J. (2018). Measurement of attentional reserve and mental effort for cognitive workload assessment under various task demands during dual-task walking. *Biological Psychology*, 134, 39-51.
- Shenhav, A., Musslick, S., Lieder, F., Kool, W., Griffiths, T. L., Cohen, J. D., & Botvinick, M. M. (2017). Toward a Rational and Mechanistic Account of Mental Effort. *Annual Review of Neuroscience*, 40(1), 99-124.
- Simola, J., Le Fevre, K., Torniaainen, J., & Baccino, T. (2015). Affective processing in natural scene viewing: Valence and arousal interactions in eye-fixation-related potentials. *Neuroimage*, 106, 21-33.
- Smallwood, J., & Schooler, J. W. (2006). The restless mind. *Psychol Bull*, 132(6), 946-958.
- Smit, A. S., Eling, P. A. T. M., Hopman, M. T., & Coenen, A. M. L. (2005). Mental and physical effort affect vigilance differently. *International Journal of Psychophysiology*, 57(3), 211-217.
- Snyder, K. L., Kline, J. E., Huang, H. J., & Ferris, D. P. (2015). Independent Component Analysis of Gait-Related Movement Artifact Recorded using EEG Electrodes during Treadmill Walking. *Frontiers in Human Neuroscience*, 9.
- So, W. K. Y., Wong, S. W. H., Mak, J. N., & Chan, R. H. M. (2017). An evaluation of mental workload with frontal EEG. *Plos One*, 12(4), e0174949.
- Soto, V., Tyson-Carr, J., Kokmotou, K., Roberts, H., Cook, S., Fallon, N., . . . Stancak, A. (2018). Brain Responses to Emotional Faces in Natural Settings: A Wireless Mobile EEG Recording Study. *Frontiers in Psychology*, 9.
- St John, M., Kobus, D. A., Morrison, J. G., & Schmorrow, D. (2004). Overview of the DARPA augmented cognition technical integration experiment. *International Journal of Human-Computer Interaction*, 17(2), 131-149.
- Symeonidou, E. R., Nordin, A. D., Hairston, W. D., & Ferris, D. P. (2018). Effects of Cable Sway, Electrode Surface Area, and Electrode Mass on Electroencephalography Signal Quality during Motion. *Sensors*, 18(4).
- Thirunavukkarasu, G. S., Abdi, H., & Mohajer, N. (2016). *A smart HMI for driving safety using emotion prediction of EEG signals*. Paper presented at the 2016 IEEE International Conference on Systems, Man, and Cybernetics (SMC).
- Thompson, T., Steffert, T., Ros, T., Leach, J., & Gruzelier, J. (2008). EEG applications for sport and performance. *Methods*, 45(4), 279-288.
- Tran, Y., Craig, A., Craig, R., Chai, R., & Nguyen, H. (2020). The influence of mental fatigue on brain activity: Evidence from a systematic review with meta-analyses. *Psychophysiology*, 57(5).
- Ullsperger, P., Freude, G., & Erdmann, U. (2001). Auditory probe sensitivity to mental workload changes - an event-related potential study. *International Journal of Psychophysiology*, 40(3), 201-209.

- van Ede, F., de Lange, F., Jensen, O., & Maris, E. (2011). Orienting attention to an upcoming tactile event involves a spatially and temporally specific modulation of sensorimotor alpha- and beta-band oscillations. *Journal of Neuroscience*, 31(6), 2016-2024.
- Viviani, P. (1990). Eye movements in visual search: cognitive, perceptual and motor control aspects. *Rev Oculomot Res*, 4, 353-393.
- Wang, D., Chen, J. Y., Zhao, D., Dai, F., Zheng, C. J., & Wu, X. B. (2017). Monitoring workers' attention and vigilance in construction activities through a wireless and wearable electroencephalography system. *Automation in Construction*, 82, 122-137.
- Wang, S. Y., Gwizdka, J., & Chaovalitwongse, W. A. (2016). Using Wireless EEG Signals to Assess Memory Workload in the n-Back Task. *Ieee Transactions on Human-Machine Systems*, 46(3), 424-435.
- Wascher, E., Arnau, S., Reiser, J. E., Rudinger, G., Karthaus, M., Rinkenauer, G., . . . Getzmann, S. (2019). Evaluating Mental Load During Realistic Driving Simulations by Means of Round the Ear Electrodes. *Front Neurosci*, 13, 940.
- Wascher, E., Heppner, H., & Hoffmann, S. (2014a). Towards the measurement of event-related EEG activity in real-life working environments. *International Journal of Psychophysiology*, 91(1), 3-9.
- Wascher, E., Heppner, H., & Hoffmann, S. (2014b). Towards the measurement of event-related EEG activity in real-life working environments. *International Journal of Psychophysiology*, 91(1), 3-9.
- Wascher, E., Heppner, H., Kobald, S. O., Arnau, S., Getzmann, S., & Mockel, T. (2016). Age-Sensitive Effects of Enduring Work with Alternating Cognitive and Physical Load. A Study Applying Mobile EEG in a Real Life Working Scenario. *Frontiers in Human Neuroscience*, 9.
- Wascher, E., Heppner, H., Mockel, T., Kobald, S. O., & Getzmann, S. (2015). Eye-blinks in choice response tasks uncover hidden aspects of information processing. *EXCLI J*, 14, 1207-1218.
- Wascher, E., Rasch, B., Sanger, J., Hoffmann, S., Schneider, D., Rinkenauer, G., . . . Gutberlet, I. (2014). Frontal theta activity reflects distinct aspects of mental fatigue. *Biological Psychology*, 96, 57-65.
- Wilson, G. F. (2002). An analysis of mental workload in pilots during flight using multiple psychophysiological measures. *International Journal of Aviation Psychology*, 12(1), 3-18.
- Wilson, G. F., & Hankins, T. (1994). Eeg and Subjective Measures of Private Pilot Workload. *Proceedings of the Human Factors and Ergonomics Society 38th Annual Meeting, Vols 1 and 2*, 1322-1325.
- Wilson, G. F., & Russell, C. A. (2007). Performance enhancement in an uninhabited air vehicle task using psychophysiological determined adaptive aiding. *Human Factors*, 49(6), 1005-1018.
- Wöstmann, M., Herrmann, B., Maess, B., & Obleser, J. (2016). Spatiotemporal dynamics of auditory attention synchronize with speech. *Proc Natl Acad Sci U S A*, 113(14), 3873-3878.
- Xiao, H., Duan, Y. G., Zhang, Z. B., & Li, M. (2018). Detection and estimation of mental fatigue in manual assembly process of complex products. *Assembly Automation*, 38(2), 239-247.
- Yokota, Y., Tanaka, S., Miyamoto, A., & Naruse, Y. (2017). Estimation of Human Workload from the Auditory Steady-State Response Recorded via a Wearable

- Electroencephalography System during Walking. *Frontiers in Human Neuroscience*, 11.
- Zakrzewska, M. Z., & Brzezicka, A. (2014). Working memory capacity as a moderator of load-related frontal midline theta variability in Sternberg task. *Frontiers in Human Neuroscience*, 8, 399.
- Zander, T. O., & Jatzev, S. (2009). *Detecting affective covert user states with passive brain-computer interfaces*. Paper presented at the 3rd International Conference on Affective Computing and Intelligent Interaction and Workshops.
- Zhang, X. L., Li, J. L., Liu, Y. G., Zhang, Z. T., Wang, Z. J., Luo, D. Y., . . . Wang, C. B. (2017). Design of a Fatigue Detection System for High-Speed Trains Based on Driver Vigilance Using a Wireless Wearable EEG. *Sensors*, 17(3).
- Zhang, Z. T., Luo, D. Y., Rasim, Y., Li, Y. J., Meng, G. J., Xu, J., & Wang, C. B. (2016). A Vehicle Active Safety Model: Vehicle Speed Control Based on Driver Vigilance Detection Using Wearable EEG and Sparse Representation. *Sensors*, 16(2).
- Zhou, X., Yao, D., Zhu, M. K., Zhang, X. L., Qi, L. F., Pan, H. Y., . . . Zhang, Z. T. (2018). Vigilance detection method for high-speed rail using wireless wearable EEG collection technology based on low-rank matrix decomposition. *Intelligent Transport Systems*, 12(8), 819-825.

- 1232 Edmund Wascher is scientific director at the Leibniz Research Centre for Working Environments and Human Factors and
1233 professor for Ergonomics at the Technical University of Dortmund. He earned his PhD in Psychology in 1992 from the
1234 University of Graz (Austria). His research interests include the study of mental fatigue and mental load as well as basic
1235 principles of the application of EEG measures in Ergonomics and Cognitive Science.
- 1236 Julian Elias Reiser is a PhD student at the Leibniz Research Centre for Working Environment and Human Factors. He earned
1237 his M.Sc. in Psychology with a focus on Human Factors at the University of Ulm. In his research he investigates the
1238 influence of naturalistic environments and tasks on cognitive processes and workload using neurophysiological methods. He
1239 is also interested in new advances in technology and how these impact the human mind and behavior.
- 1240 Gerhard Rinkenauer is senior researcher at the Leibniz Research Centre for Working Environments and Human Factors, head
1241 of the research area of work design at the department of ergonomics and associate professor of Cognitive Psychology at the
1242 Technical University of Dortmund. He earned his PhD in psychology from the University of Wuppertal in 1999. His
1243 research interests include the investigation and modeling of cognitive performance and learning ability as well as human
1244 resilience during the interaction and cooperation with modern technical working environments and smart devices.
- 1245 Mauro Larra is a post-doc at the Leibniz Research Centre for Working Environments and Human Factors. He earned his PhD
1246 in Psychobiology in 2015 from the University of Trier (Germany). His research focusses on the neurophysiological
1247 mechanisms underlying the elicitation, modulation and acute effects of the human stress
- 1248 Felix A. Dreger is researcher and PhD candidate at the Department of Ergonomics of the Leibniz Research Centre for
1249 Working Environments and Human Factors. He received his M.Sc. in psychology from the University of Tübingen in 2016.
1250 His background comprises economic psychology, general psychology, and computer science. His current research activities
1251 focus on the human machine interface design of forestry harvesters as well as human robot collaboration.
- 1252 Daniel Schneider is a research group leader at the Leibniz Research Centre for Working Environments and Human Factors.
1253 He earned his doctoral degree (Dr. rer. nat) in Psychology in 2012 from Ruhr University Bochum (Germany). His research
1254 concentrates on inter- and intra-individual differences in the capacity of human information processing, with a special focus
1255 on the EEG-based investigation of working memory and selective attention.
- 1256 Melanie Karthaus is research assistant at the Leibniz Research Centre for Working Environment and Human Factors. She
1257 earned her PhD in Psychology in 2008 from the University of Trier (Germany). Her research interests include the cross-
1258 sectional and longitudinal study of cognition, aging and mobility (driving) with behavioral and neurophysiological methods.
- 1259 Stephan Getzmann is head of the Networking Group Aging at the Leibniz Research Centre for Working Environments and
1260 Human Factors. He earned his PhD in Psychology in 2004 from the Ruhr-University Bochum and qualified 2010 as a
1261 university lecturer at the Technical University of Dortmund. His main research interests are neurophysiological mechanisms
1262 of healthy aging
- 1263 Marie Gutberlet is the owner and CEO of BlindSight GmbH, a company specializing in the development of biosignal
1264 devices, accessories and related analysis methods, with special emphasis on EEG, ExG and fMRI. She earned her PhD in
1265 Physiological Psychology in 1994 from the University of Trier (Germany). Her research interests include affective and
1266 cognitive neuroscience and lately also the neurophysiological basis of gender formation and expression.
- 1267 Stefan Arnau is a post doctoral researcher at the Leibniz Research Centre for Working Environments and Human Factors at
1268 the Technical University of Dortmund. He obtained the doctorate degree Dr. rer. nat. from the Ruhr University Bochum in
1269 2019. His research interests include cognitive engagement, mental fatigue, and cognitive resource management.
- 1270
1271