A PHYSICAL STUDY OF THE EFFECT OF GROUNDWATER SALINITY ON THE COMPRESSIBILITY OF THE SEMARANG-DEMAK AQUITARD, JAVA ISLAND

Dwi Sarah ^{1,2*}, Lambok M Hutasoit ¹, Robert M Delinom ², Imam A Sadisun¹, and Taufiq Wirabuana ³.

¹ Faculty of Earth Science and Technology, Institut Teknologi Bandung, Bandung 40132, Indonesia

² Research Center for Geotechnology, Indonesian Institute of Sciences (LIPI), Bandung 40135, Indonesia

³ Center for Groundwater Resource and Environmental Geology, Indonesian Geological Agency, Bandung, Indonesia

* Correspondence: sarahpr28@gmail.com;

Academic Editor: name

Received: date; Accepted: date; Published: date

Abstract: Semarang-Demak and other cities along the coast of North Java are vulnerable to land subsidence. The presence of saline groundwater in the coastal region is thought to affect the high subsidence rate, in this case the compressibility of the aquitard layer. We aimed to analyze the effects of groundwater salinity on the compression characteristics of the Semarang-Demak clay using physical analysis. Methods included the determination of groundwater salinity, clay mineralogy and fabrics, and consolidation tests under various salinity conditions. The Semarang-Demak clay is dominated by smectite of high activity and saline clay exists at the depth of 10 to 35 m. Consolidation tests reveals that the increase of salinity increases the average consolidation rate and hydraulic conductivity up to 42% and 37.5%, respectively. Clay fabric analysis showed that the groundwater salinity modified the interconnectivity of pores by changing the fabric into parallel alignments, facilitating faster porewater dissipation, hence the clay is more readily compressed. These findings are useful for explaining the mechanism of the fast-subsiding coastal plains of North Java.

Keywords: groundwater; salinity; clay, compressibility, Semarang- Demak

1. Introduction

The sinking of land surfaces is threatening coastal areas all over the world, and affects almost half a billion people living on or near the coast [1]. Land subsidence is defined as the gradual settling of the earth's surface by subsurface movement of earth materials [2]. Over 150 areas across the world are affected by contemporary land subsidence, most of these areas are located in the coastal regions [3], such as Shanghai [4], Hanoi [5], Bangkok [6], Mekong delta- Vietnam [7], and more. The coastal areas of Indonesia are also susceptible to land subsidence, particularly in the most densely populated island of Java. Large cities in the northern coast of Java are experiencing land subsidence at different rates, Jakarta and Semarang-Demak (1.0 to > 10.0 cm/year) [8–10], Pekalongan (4.8 cm/year)[10], and Surabaya (2.0 cm/year) [11]. The high rate of land subsidence in the coastal area is primarily related to the aquifer-aquitard system compaction due to the abstraction of groundwater [2,12–14], although other factor such as natural compaction could coexist [15,16]. Exploitation of the confined groundwater reduces the piezometric pressure of the aquifer. As the piezometric pressure drops, the total stress of the aquifer-aquitard system remains constant hence the effective stress is increasing. The increase of the effective stress causes the compaction of the aquifer-aquitard system

leading to land subsidence. Aquitard is particularly prone to large compaction because of its high compressibility. The compressibility of the aquitard is several orders of magnitude higher than that of an aquifer. Accordingly, aquitard compressibility controls the compaction of the aquifer-aquitard system and accounts for most of the subsidence [13,17]. Therefore, it is important to understand the compressibility behavior of aquitard to understand the land subsidence process.

The clay-rich soil in aquitards has notable characteristics of low hydraulic conductivity, high compressibility, relatively soft consistency and high affinity for water. The engineering behavior of clay is controlled by the water adsorbed in the clay surface (diffuse double-layer). Diffuse double-layer water is the water adsorbed as a result of the induced electrical force of the negatively charged clay particles and the concentration of exchangeable cations near the particle surface [18]. During land subsidence process, the compaction of the aquifer-aquitard system is largely derived from the clay consolidation. The effective stress increase of the aquifer due to the piezometric head lowering induces the slow drainage of clay porewater, causing consolidation settlement of the clay. Literature study reveals that, apart from the mechanical factor, the clay consolidation process is also influenced by the clay mineralogy and porewater chemistry [18,19]. Previous studies have showed that inorganic salt solution has a strong impact on the compressibility of clay [20–25], which is mainly due to the change of the diffuse double layer thickness at different electrolyte concentration. The rate of change of the double layer water thickness varies with the type of clay mineral, with smectite being the most reactive. Most of the previous studies used a single type of clay mineral or artificial soils, except [21,24] that used natural marine clay. The introduction of saline pore fluid to clay affects the hydro-mechanical properties of single type smectite soils [20,22,23]. However, the effect of salinity on the compressibility of natural clays showed different reactions. The increase of salinity on Boom clay [21] had an almost negligible effect on compressibility indices, while for Lianyungang clay [24], the opposite effect occurred.

The coastal aquifer-aquitard system has variable groundwater quality from fresh to saline, depending on its former environmental conditions [26]. Some marine clays with saline porewater are known to be soft and vulnerable to excessive settlements, posing threats to construction and maintenance of infrastructure, for example the marine clays from Bangkok [27,28], Shanghai [29,30], Pusan [31], and Kansai [32]. Land subsidence of marine clays had been widely analyzed in the light of one dimensional consolidation theory [5,14,33,34], however the effect of the groundwater salinity to the subsidence process (e.g. consolidation parameters) tends to be overlooked. To address this knowledge gap, it is important to understand the effect of groundwater salinity to the compressive characteristics of marine clay. The marine clay of North Java coastal plain is generally soft and highly compressible [35–37], hence prone to subside. The high rate of land subsidence in the coastal cities of North Java raises the question of whether the groundwater quality affects the compressibility characteristics of the aquitard. This study aims to analyze the effects of groundwater salinity on the compressive characteristics of saline clay using physical analysis. Clay samples from the subsiding Semarang- Demak plain were analyzed to understand the consolidation properties when exposed to different salinity conditions. We examine the correlation between groundwater salinity and clay consolidation indices (compression and swelling indexes, oedometer modulus, consolidation rate, hydraulic conductivity) and validate the experimental results with the clay fabric analysis, thus emphasizing the importance of groundwater salinity effect to the land subsidence mechanisms in the study area and in other North Java cities.

2. Geology and Hydrogeology of Study Location

The study area is located between 6.8–7.0°S and 110.4–110.6°E, consisting of the coastal lowland morphology in the north and hilly area in the south. The Semarang-Demak coastal plain in the north is overlain by surficial alluvium (Qa), and the south hilly topography consists of Quaternary volcanic rock (QTd), and Tertiary rock (TmPk) (Figure 1). The Kalibeng Formation (TmPk) consists of marl with tuffaceous sandstone and limestone intercalations. The Damar Formation (QTd) consists of tuffaceous sandstone, conglomerate, and volcanic breccia. The surficial alluvium lies unconformably on top of the Damar Formation. [38] stated that the coastal plain of Semarang – Demak is formed by alluvial deposit of thick layers of calcareous and shell bearing clay, with thin intercalations of sand, and occasionally gravel or cemented gravel deposited in a marine environment. Van Bemmelen (1941) in [38] estimated the thickness of the alluvial deposit to be 50 m near the south hills and along the coast of about 90 m. The latest tectonic activity in Semarang was in Plio-Pleistocene, forming thrust fault separating the Quaternary Damar Formation and the Tertiary rock (TmPk) [39].

Figure 1. Geology of study location (modified from [39,40])

Recent sedimentation processes influenced the Semarang-Demak plain to a great extent. The sea level rise during the Pleistocene caused submersion of this area, and sedimentation of the

Semarang-Demak alluvial plain started at the beginning of the Holocene [38]. The fluctuation of global sea level during the Holocene caused transgression and regression, forming the silting up of the Semarang- Demak plain. Van Bemmelen (1941) in [41] noted that 300 years ago, the Semarang port was in Bergoto which is about 5 km south of the present coastline and the Semarang-Demak plain was a sea up until 500 years ago [42]. The sedimentation of the study area is fairly recent, previous studies [42–44] reported that during 1695–1991 the shoreline in the study area progressed rapidly towards the sea at an average rate of 8.0 m/year.

Hydrogeologically the Semarang- Demak plain consists of unconfined and confined aquifers. The unconfined aquifer is formed by alluvial deposit of clayey sand to sand, with fluctuative water table, depending on the recharge from precipitation. The annual rainfall of the Semarang-Demak plain is 1,500-3,000 mm, with dry months from May to October and wet months from November to April [45]. The confined aquifers are the Quaternary deposit aquifers and the Damar Formation aquifer [45]. The Quaternary deposit aquifers are divided into the Garang deltaic aquifer of freshwater and the Quaternary marine aquifer of saline water. The Garang deltaic aquifer consists of medium to coarse sand, and the Quaternary marine aquifers consists of clayey sand, and fine to coarse, shell-bearing sand. The Damar aquifer is the main aquifer in the Semarang - Demak plain that contains freshwater of volcanic rocks. West- East section from compiled borehole and CPTu sounding data provide a typical subsurface profile of the study area (Figure 2).

Figure 2. Typical subsurface profile of the Semarang- Demak plain

Figure 2 shows that the bulk of the Semarang-Demak plain sediment consists of thick aquitard layers of clay and silty clay, intercalated with lenses of sand and gravels. The thickness of the clay layer is 25 to 80 m, and becomes thicker towards the east (Demak). From the grain size distribution in Figure 2, it can be seen that the Garang deltaic aquifer exists at the depth of 60 to 90 m, and the Quaternary marine aquifer occurs at the shallower depths (less than 60 m). The Garang deltaic aquifer and Quaternary marine aquifer were possibly formed during regression and transgression during the Holocene. Specific study on the the Semarang- Demak plain Quaternary deposition is not yet available, therefore the detailed information on its depositional history is largely unknown. The

Quaternary aquifers mostly exist as lenses which contain freshwater and saline water of limited yield, therefore utilization of these aquifers is limited. The most exploited groundwater comes from the Damar Formation, and the piezometric contour of this aquifer shows some depressions related to groundwater utilization at industrial estates (Figure 3). The lowering of piezometric pressure due to groundwater exploitation exerts additional pressure on the overlying aquitard. The compaction of the thick, compressible upper clay of the study area is thought to contribute to the land subsidence.

Figure 3. Piezometric contour of the Damar Formation aquifer (in m a.s.l)

3. Materials and Methods

In this study, clay samples and water samples were taken from subsidence areas in the Semarang-Demak plain. Clay samples were taken from four boreholes: SMG01 and SMG02 (Semarang City), and JTK and GEM (Demak Regency), and water samples were taken from nearby dug and bored wells (Figure 1). A Shelby thin-walled tube sampler was used to retract relatively undisturbed samples. The samples were then tested for compressibility, index properties, clay mineralogy and were used for porewater extraction. Laboratory investigations of geotechnical index properties of clay (natural water content, density, specific gravity, Atterberg limits, and grain size distribution) were carried out according to ASTM D 2216, D 7263, D 854-02, D 4318, and D 422, respectively.

Identification of clay mineralogy requires separation of clay fraction from the bulk soil. About ten grams of clay were taken from each stratum, and dispersed in distilled water using a high speed stirrer, followed by centrifugation to obtain a fraction of < 0.002 mm. Two oriented glass slides were prepared for each sample, one for an air-dried oriented slide and the other slide was dropped with ethylene glycol. All slides were exposed to Cu- K α radiation on an XRD Shimadzu-6000 at scanning speed of 2° per minute, from 2° to $30^\circ 2\theta$. A semi quantitative estimation of clay minerals was carried out from the peak area (I) using the formula [46,47]:

$$\% \text{ of clay minerals} = 100 \times [I \text{ clay minerals} / \Sigma I \text{ all clay minerals in the sample}] \quad [1]$$

The peaks used for semi-quantitative analysis were : 15- 17 Å (smectite), 10 Å (illite) and 7.1 Å (kaolinite and chlorite). Due to the absence of heat treatment, kaolinite and chlorite are not distinguishable in this analysis. We stress the presence of smectite and illite as they have higher activity[48] in response to the changes of physicochemical properties.

Extraction of clay porewater was carried out by leaching, adapting the procedures from [49]. Clay samples were mixed with de-ionized water at a solid to liquid ratio of 1:5. Clay solutions were homogenized using a magnetic stirrer and agitated for 3 hours using a laboratory shaking bath (Julabo SW23) at 200 rpm. After leaching, the clay suspensions were centrifuged in 50 ml tubes using a Heraeus Labofuge I bench-top centrifuge at a speed of 2000 rpm for 20 minutes. Following centrifugation, the aliquots were filtrated using Whatman filter paper no. 42 to remove any clay particles present. Aliquots of the clay suspension, and groundwater samples from dug and bored wells, were tested for electrical conductivity, pH, sodium ion, and chloride ion concentrations. Electrical conductivity and pH were measured using a portable electrical conductivity/pH meter (WM-32EP, DKK-Toa.co). Chloride concentration was determined by argentometric titration (APHA, 4500 Cl-) using the Titroline alpha apparatus (Schott GmbH, Germany) and Na cation by the atomic absorption spectrophotometer (AAS Shimadzu 7000). All measurements were carried out in triplicate.

To study the porewater salinity effect on the compressive behavior of clay, laboratory oedometer tests (ASTM D 2435) were performed. Replacement of porewater was achieved by soaking the sample with de-ionized water, and NaCl solutions of 1,000 mg/L, 3,000 mg/L, and 6,000 mg/L concentrations during consolidation process. The clay compressibility behavior was evaluated from the compression index (c_c), coefficient of consolidation (c_v), hydraulic conductivity (k), oedometer modulus (E_{odo}), and coefficient of swelling (c_s). The compression index (c_c), swelling index (c_s), and oedometer modulus (E_{odo}) were determined from the logarithmic curve of applied stress against void ratio; and the coefficient of consolidation (c_v) was computed using the Casagrande time-square method (t_{90}), which indicated the rate of clay sample compression required to achieve 90% of consolidation (in $m^2/year$)[50]. The hydraulic conductivity (k) was calculated by:

$$k = c_v \rho_w g / E_{odo} \quad [2]$$

where ρ_w is the density of water (1.00 g/cm³ and 1.01 g/cm³ for NaCl solutions), g is the gravitational acceleration (9.8 m/s²) and E_{odo} is oedometer modulus (kPa).

Fabric of the marine clays was examined using a scanning electron microscope (SEM, Jeol-JSM-6510). Samples were prepared by oven drying at constant temperature of 30^o C and cut perpendicular to the their horizontal bedding plane. Clay samples were examined under their natural condition to observe the original fabric, and were re-observed after porewater replacement with saline waters to study the fabric change caused by changes in porewater salinity.

4. Results and Discussion

4.1. Geotechnical index properties of clay

The laboratory results are presented in Figures 4, 5, and 6. Figure 4 shows that the natural water content of the clay ranges between 41.6 to 87.5%, bulk density between 12.7 to 18.3 kN/m³ and specific gravity of 2.45 to 2.90. Degree of saturation, calculated from the preceding results, varies from 90.0 to 124.0%, showing saturation state of the clay. The grain size distribution curves of

Semarang- Demak clays are quite similar, showing high clay content (particle size less than 0.002 mm) of more than 50% (Figure 5). Atterberg limit test results show that the Semarang- Demak clay is mostly highly plastic (CH) (Figure 6a). Semarang clay has medium to high activity and Demak clay has high to very high activity (Figure 6b). The higher the activity of clay, the influence of the clay fraction on its engineering behavior is more pronounced and it is more susceptible to changes in pore fluid composition [51]. The high activity of clay is also related to greater smectite presence [28].

Figure 4. Water content, bulk density and specific gravity of Semarang- Demak clay

Figure 5. Grain size distribution of Semarang- Demak clay

Figure 6. (a) Plasticity chart; (b) Clay activity chart [52]

4.2. Mineralogy of Semarang- Demak clay

Figure 7 shows the XRD patterns for air dried and glycolated samples of Semarang-Demak clay. The presence of smectite is identified at 2θ of 7.1° ($12 \text{ \AA}$) to 5.8° ($15.2 \text{ \AA}$) (air dried) and 2θ of 5.7° ($15.5 \text{ \AA}$) to 5.1° ($17 \text{ \AA}$) (glycolated). The peaks of $7.1 \text{ \AA}$, $10 \text{ \AA}$ and $3.31 \text{ \AA}$ are due to kaolinite or chlorite, illite, and quartz, respectively. Relative percentage of clay minerals (Table 1) shows the significant amount of smectite. The higher activity of Demak clay, compared to Semarang clay, is confirmed by the higher amount of smectite.

Figure 7. XRD diffractograms: (a) Semarang clay; (b) Demak clay

Table 1. Result of semi quantitative analysis of Semarang- Demakclay

Borehole	Clay mineralogy (%)
SMG-01	Smectite (31.0%), illite (29.0%), kaolinite/chlorite (40.0%)
SMG-02	Smectite (37%), illite (22.0%), kaolinite/chlorite (38.0%)
GEM	Smectite (58.9%), illite (14.3%), kaolinite/chlorite (24.9%)
JTK	Smectite (52.6%), illite (12.7%), kaolinite/chlorite (33.4%)

4.3. Groundwater Salinity of Semarang- Demak plain

Concentrations of Na^+ and Cl^- ions, electrical conductivity and pH of the porewater and groundwater from wells are shown in Figure 8. The chloride concentration in the upper 10 m is less than 500 ppm, and increases to 1,100– 6,300 ppm at the depths of 10 to 35 m. Chloride concentration at the depths of 40 –180 m is well below 400 ppm. The pH of the waters ranges from 6.7 to 8.4. The variation of Na^+ ion concentration and electrical conductivity with depth is similar to that of the chloride concentration. It is revealed that saline water exists at the depth of 10 to 35 m, and most likely the saline water was formed during the sediment deposition. Figure 8 indicates that the Quaternary marine aquifer system occurs at depth of 10 to 35 m, and the freshwater below this depth comes from either the Garang deltaic aquifer or the Damar Formation aquifer. From this result, we use the term saline clay for clay with saline porewater (chloride concentration of more than 1,000 ppm), and freshwater clay for clay with fresh porewater.

Figure 8. Concentrations of Na^+ and Cl^- ions, electrical conductivity, and pH of Semarang-Demak groundwater

4.4. Compressibility of Semarang- Demak clay

Consolidation tests (1-D) were performed for saline clay samples from Semarang City and Demak Regency. Compression curves for the Semarang-Demak clays under various salinity conditions (Figure 9) show that increasing the salt concentration in the porewater decreases the void ratio throughout the loading range. The effects of increasing salinity are thus noticeable even at the initial loading (30 kPa). The Semarang and Demak clays experience different changes in compressibility index and oedometer modulus as a result of increased salt concentration during loading, and different changes in the swelling index with unloading, as detailed in Table 2.

Figure 9. Compression curves: (a) Semarang clay; (b) Demak clay

Table 2. Compression index, swelling index and oedometer modulus of Semarang-Demak clay

Salt concentration (mg/L)	c_c		c_s		E_{odo} (kPa)	
	Semarang	Demak	Semarang	Demak	Semarang	Demak
0	0.434	0.827	0.140	0.155	1468.81	1231.08
1,000	0.402	0.768	0.120	0.360	1495.62	1298.97
3,000	0.379	0.690	0.099	0.216	1586.52	1427.45
6,000	0.360	0.630	0.094	0.167	1716.44	1615.13

The average compression index (c_c) for the Semarang-Demak clay (Table 2) shows a slight decreasing trend as the salt concentration increases. The decrease in the compression index is attributed to the reduction of the double-layer thickness as the pore fluid concentration increases. Swelling of the clay sample occurs during the unloading process, as indicated by the swelling index

(c_s). The physicochemical condition of the porewater affects the swelling behavior in terms of osmosis [53]. The intake of water that is held by the clay during unloading is the result of the osmotic gradient between the more concentrated pore fluid within the clay matrix and the less concentrated ambient porewater. The effect of salt concentration on swelling is more evident in saline water. The osmotic pressure difference for the saline water decreases as the concentration increases, and thus causes less swelling of the saline clay. The computed coefficient of consolidation (c_v) and hydraulic conductivity (k) for various porewater salinities are shown in Figures 10 and 11.

Figure 10. Changes of coefficient of consolidation (c_v) versus porewater salt concentration for (a) Semarang clay, and (b) Demak clay

Figure 10 shows that during loading the c_v values increase as the concentration of NaCl solution increases. It can be seen that during loading of greater than 124 kPa the rate of increase in c_v diminishes. Figure 10 also shows that the c_v value for the Demak clay is higher than that of the Semarang clay. The calculated hydraulic conductivity versus void ratio graphs for the Semarang and Demak clays are presented in Figures 11a and 11b, respectively.

Figure 11. Changes in hydraulic conductivity (k) during compression at various porewater salt concentrations for (a) Semarang clay, and (b) Demak clay.

Figure 11 shows that the hydraulic conductivity increases as the concentration of NaCl solution increases; at lower void ratios this increase is small. The pattern of increases in the coefficient of consolidation and hydraulic conductivity are the result of reduced increases in salt concentration at certain stress levels and void ratios. The effect of double-layer water on the geomechanical properties of the clay depends on the mechanical stress and chemical concentration level [18]. Figures 6 and 7 show that at higher stress levels (or lower void ratios) the increase rates of the coefficient of consolidation and the hydraulic conductivity are reduced. To observe the approximate change of c_v and k due to the increase of salt concentration, average values of C_v and K are calculated (Table 3).

Table 3. Average coefficient of consolidation (C_v) and hydraulic conductivity (k) of Semarang-Demak clay

Salt concentration (mg/L)	Average c_v (m ² /year)		Average k (x10 ⁻⁹ m/s)	
	Semarang	Demak	Semarang	Demak
0	0.226	1.040	6.547	0.240
1,000	0.184	1.250	7.522	0.259
3,000	0.276	1.400	9.286	0.304
6,000	0.319	1.590	8.692	0.375

Table 3 shows that the increase of salt concentration raises the average c_v values of 17.0 to 42.0%, and the k values of 7.0 to 37.5%. The higher the salt concentration, the higher the hydraulic conductivity, which causes the compression rate (c_v) to increase. Mathematically, linear relationship exists between logarithm of hydraulic conductivity (k) and the void ratio (e) for clays [54]; for the Semarang-Demak clay it is shown in Figure 12. This relationship is useful to predict the change of hydraulic conductivity of the clay over increasing stress state (i.e void ratio) at various groundwater salinity. Higher change of hydraulic conductivity due to higher groundwater salinity is observed in Demak clay (Figure 12b), indicating higher activity of the clay.

Figure 12. Mathematical relationship of hydraulic conductivity to void ratio for : (a) Semarang clay; (b) Demak clay.

4.5. Fabric analysis of Semarang- Demak clay

Features observed in the Semarang-Demak clays show that two distinct fabrics of natural clay of fresh porewater and saline clay are present (Figure 13). Freshwater clay is dominated by edge-to-face (E-F) flocculation (Figure 13a) and the saline clay is dominated by dispersed parallel (face to face) (F-F) alignment with some edge-to-edge (E-E) flocculation (Figure 13b).

Figure 13. (a) Fabric of freshwater clay; (b) Fabric of saline clay

The change in porewater salinity affected the initial clay fabrics for both freshwater and saline clays, as shown in Figures 14 and 15. The initial clay fabrics changed because of porewater replacement. Alteration of porewater chemistry changes the electrical interparticle forces between clay and the double-layer water, and results in fabric change [55]. Figures 14 and 15 also show that increasing salinity causes changes to the clay fabric that result in a more dispersed parallel fabric. The parallel fabric facilitates faster porewater movement; consequently, the hydraulic conductivity increases as salinity increases. This observation is supported by the hydraulic conductivity measurements (Figure 11 and Table 3). The test results show that the Semarang-Demak aquitard is dominated by saturated high plasticity clay of medium to very high activity, containing considerable amounts of smectite (Table 2). The compressive behavior of such clay is governed by the state of the adsorbed double-layer water. The introduction of saline porewater immediately reduces the void ratio, and consequently decreases the compression index (c_c) and swelling index (c_s), and increases the clay stiffness (E_{odo}). Similar behavior is found in pure smectite soil [22,23] and in the Lianyungang natural clay [24]. The average change in the compression index (c_c) for smectite soil is 77% [22], which is comparable to that of the Semarang-Demak clay (76%–82%). Saline clay has a higher coefficient of consolidation (c_v) than freshwater clay, which indicates that the saline clay compresses faster than freshwater clay. The increase in the consolidation rate is 1.5 to 1.7 times for the Semarang-Demak clay. In comparison, the increased rate of consolidation is 2.5–3 times for smectite soil and Lianyungang clay [23,24]. The increase in the consolidation rate can be explained by the increase in the hydraulic conductivity (k) caused by the clay fabric change. The observed fabric change for the Semarang-Demak clay is similar to that of pure Ponza bentonite when exposed to saline fluids [20].

(a)

(b)

(c)

Figure 14. Change of fabric caused by porewater replacement: **a)** initial freshwater clay fabric; **b)** parallel fabric after porewater replacement with 1,000 mg/L NaCl solution; **c)** denser parallel fabric after porewater replacement with 6,000 mg/L NaCl solution.

(a)

(b)

(c)

Figure 15. Change of fabric caused by porewater replacement: **a)** initial saline clay fabric; **b)** parallel fabric after porewater replacement with 1,000 mg/L NaCl solution; **c)** denser parallel fabric after porewater replacement with 6,000 mg/L NaCl solution.

The test results show that the effect of saline fluid on the compressibility behavior of Semarang-Demak clay is similar to that of pure smectite soil. The natural clay of Boom [21] is not affected by salinity changes because of its low smectite content (<20%). The Semarang-Demak clay (30%–50% smectite) and Lianyugang clay (44%–57% illite/smectite) [24] have high smectite content, and therefore, tends to react similarly to the pure smectite soil when affected by salinity. The influence in porewater salinity increases with smectite content. The Demak clay has higher smectite content, and higher c_v and k values, and shows a higher rate of change with increasing porewater salinity.

In the case of land subsidence in the study area, the saline clay (at 10 to 35 m depth) compresses faster due to both overburden load and increase of effective stress from the lowering of piezometric pressure. Excess pore pressure developed on the saline clay is dissipated faster due to the higher consolidation rate (c_v) and hydraulic conductivity (k), which is confirmed by the parallel alignment of the clay fabric making ease of groundwater flow movement. The parallel clay fabric is also mechanically more favourable to compression, showing the saline clay is readily compressed. These findings help to explain the mechanism of land subsidence from the physical perspective. The compression parameters of saline clay are useful inputs for land subsidence numerical models.

5. Conclusions

The effect of groundwater salinity on the compressibility characteristics of the Semarang-Demak aquitard was examined based on physical analysis. Aquitard of the study area consists of high plasticity clay with medium to high activity. Groundwater salinity profile of the Semarang-Demak plain shows the existence of saline water at 10 to 35 m depth, and the clay aquitard is predominantly consists of smectite. Analysis of the effect of groundwater salinity to compressibility shows that the increase of salinity decreases the compression and swelling indexes, and increases the stiffness of clay due to the reduction of double layer water by physicochemical reaction. The increase of salinity increases the average consolidation rate and hydraulic conductivity up to 42% and 37.5%, respectively. The increase of groundwater salinity modified the interconnectivity of pores by changing the clay fabric into parallel alignments, facilitating faster porewater dissipation. The dissipation of porewater is faster in saline clay than in freshwater clay as a result of improved hydraulic conductivity, and thus consolidation is achieved more quickly (i.e. a faster rate of subsidence). These findings are useful to understand the mechanism of the fast-subsiding coastal plains of North Java and be used for numerical modeling input.

Acknowledgements: Borehole cores of Semarang-Demak plain were provided by the Research Center for Geotechnology, the Indonesian Institute of Sciences (LIPI) and the Center for Groundwater Resource and Environmental Geology, Indonesian Geological Agency. The support from a P3MI grant (Institut Teknologi Bandung) for field and laboratory works is gratefully acknowledged.

Author Contributions: Dwi Sarah performed this study and wrote this paper in the framework of her Ph.D project at Institut Teknologi Bandung. Lambok Hutasoit, Robert Delinom and Imam Sadisun provided guidance and support throughout the study and revised the manuscript. Taufiq Wirabuana and Dwi Sarah carried out the field work in Semarang- Demak, and he performed the index properties tests.

Conflicts of Interest: The authors declare no conflict of interest.

366 **References**

- 367 (1) Syvitski, J. P. M.; Kettner, A. J.; Overeem, I.; Hutton, E. W. H.; Hannon, M. T.; Brakenridge, G. R.; Day,
368 J.; Vörösmarty, C.; Saito, Y.; Giosan, L.; Nicholls, R. J. Sinking Deltas due to Human Activities. *Nat.*
369 *Geosci.* **2009**, 2 (10), 681–686 DOI: 10.1038/ngeo629.
- 370 (2) Galloway, D.; Jones, D. R.; Ingebritsen, S. E. *Land Subsidence in the United States*; US Geological Survey,
371 1999.
- 372 (3) Barends, F. B., Brouwer, F. J., & Schröder, F. H. Land Subsidence: Natural Causes, Measuring
373 Techniques, the Groningen Gasfields. In *Proceedings of the Fifth International Symposium on Land*
374 *Subsidence, The Hague, Netherlands 16-20 October 1995*; 1995.
- 375 (4) Xu, Y.-S.; Shen, S.-L.; Ren, D.-J.; Wu, H.-N. Analysis of Factors in Land Subsidence in Shanghai: A
376 View Based on a Strategic Environmental Assessment. *Sustainability* **2016**, 8 (6), 573 DOI:
377 10.3390/su8060573.
- 378 (5) Phi, T. H.; Strokova, L. A. Prediction Maps of Land Subsidence Caused by Groundwater Exploitation
379 in Hanoi, Vietnam. *Resour. Technol.* **2015**, 1 (2), 80–89 DOI: 10.1016/j.refit.2015.09.001.
- 380 (6) Phien-wej, N.; Giao, P. H.; Nutalaya, P. Land Subsidence in Bangkok, Thailand. *Eng. Geol.* **2006**, 82 (4),
381 187–201 DOI: 10.1016/j.enggeo.2005.10.004.
- 382 (7) Erban, L. E.; Gorelick, S. M.; Zebker, H. A. Groundwater Extraction, Land Subsidence, and Sea-Level
383 Rise in the Mekong Delta, Vietnam. *Environ. Res. Lett.* **2014**, 9 (8) DOI: 10.1088/1748-9326/9/8/084010.
- 384 (8) Abidin, H. Z.; Andreas, H.; Gumilar, I.; Gamal, M. Land Subsidence and Urban Development in
385 Jakarta (Indonesia) Land Subsidence and Urban Development in Jakarta (Indonesia). No. October
386 2009, 19–22.
- 387 (9) Abidin, H. Z.; Andreas, H.; Gumilar, I.; Sidiq, T. P.; Fukuda, Y. Land Subsidence in Coastal City of
388 Semarang (Indonesia): Characteristics, Impacts and Causes. *Geomatics, Nat. Hazards Risk* **2013**, 4 (3),
389 226–240 DOI: 10.1080/19475705.2012.692336.
- 390 (10) Chaussard, E.; Amelung, F.; Abidin, H.; Hong, S.-H. Sinking Cities in Indonesia: ALOS PALSAR
391 Detects Rapid Subsidence due to Groundwater and Gas Extraction. *Remote Sens. Environ.* **2013**, 128,
392 150–161 DOI: 10.1016/j.rse.2012.10.015.
- 393 (11) Aditiya, A.; Takeuchi, W.; Aoki, Y. Land Subsidence Monitoring by InSAR Time Series Technique
394 Derived from ALOS-2 PALSAR-2 over Surabaya City, Indonesia. *IOP Conf. Ser. Earth Environ. Sci.* **2017**,
395 98 (1) DOI: 10.1088/1755-1315/98/1/012010.
- 396 (12) Bakr, M. Influence of Groundwater Management on Land Subsidence in Deltas. *Water Resour. Manag.*
397 **2015**, 29 (5), 1541–1555 DOI: 10.1007/s11269-014-0893-7.
- 398 (13) Shen, S. L.; Ma, L.; Xu, Y. S.; Yin, Z. Y. Interpretation of Increased Deformation Rate in Aquifer IV due
399 to Groundwater Pumping in Shanghai. *Can. Geotech. J.* **2013**, 50 (11), 1129–1142 DOI:

- 400 10.1139/cgj-2013-0042.
- 401 (14) Xu, Y. S.; Yuan, Y.; Shen, S. L.; Yin, Z. Y.; Wu, H. N.; Ma, L. Investigation into Subsidence Hazards due
402 to Groundwater Pumping from Aquifer II in Changzhou, China. *Nat. Hazards* **2015**, 78 (1), 281–296
403 DOI: 10.1007/s11069-015-1714-x.
- 404 (15) Gambolati, G.; Teatini, P.; Tomasi, L.; Gonella, M. Coastline Regression of the Romagna Region, Italy,
405 due to Natural and Anthropogenic Land Subsidence and Sea Level Rise. *Water Resour. Res.* **1999**, 35 (1),
406 163–184 DOI: 10.1029/1998WR900031.
- 407 (16) Teatini, P.; Tosi, L.; Strozzi, T. Quantitative Evidence That Compaction of Holocene Sediments Drives
408 the Present Land Subsidence of the Po Delta, Italy. *J. Geophys. Res. Solid Earth* **2011**, 116 (8), 1–10 DOI:
409 10.1029/2010JB008122.
- 410 (17) Holzer, T. L.; Galloway, D. L. Impacts of Land Subsidence Caused by Withdrawal of Underground
411 Fluids in the United States. *Rev. Eng. Geol.* **2005**, 16, 87–99 DOI: 10.1130/2005.4016(08).
- 412 (18) Schmitz, R. M. Can the Diffuse Double Layer Theory Describe Changes in Hydraulic Conductivity of
413 Compacted Clays ? *Geotech. Geol. Eng.* **2006**, 24, 1835–1844 DOI: 10.1007/s10706-005-3365-2.
- 414 (19) Meade, R. H. *Rearrangement of Particles During the Compaction of Clayey Sediments - Review*; Mechanics of
415 Aquifer Systems; Geological Survey Professional Paper 497-B; Washington, 1964.
- 416 (20) Di Maio, C. Exposure of Bentonite to Salt solution: Osmotic and Mechanical Effects. *Geotechnique* **1996**,
417 46 (4), 695–707.
- 418 (21) Deng, Y.; Cui, Y.; Tang, A. M.; Nguyen, X.; Deng, Y.; Cui, Y.; Tang, A. M.; Nguyen, X.; Li, X.
419 Investigating the Pore-Water Chemistry Effects on the Volume Change Behaviour of Boom Clay. *Phys.*
420 *Chem. Earth, Elsevier* **2011**, 36 (17–18), 1905–1912.
- 421 (22) Tiwari, Binod; Ajmera, B. Effects of Saline Fluid on Compressibility of Clay Minerals. *Environ. Geotech.*
422 **2014**, 1 (EG2), 108–120.
- 423 (23) Dutta, J.; Mishra, A. K. Applied Clay Science Consolidation Behaviour of Bentonites in the Presence of
424 Salt Solutions. *Appl. Clay Sci.* **2016**, 120, 61–69 DOI: 10.1016/j.clay.2015.12.001.
- 425 (24) Deng, Y. F.; Yue, X. B.; Cui, Y. J.; Shao, G. H.; Liu, S. Y.; Zhang, D. W. Effect of Pore Water Chemistry
426 on the Hydro-Mechanical Behaviour of Lianyungang Soft Marine Clay. *Appl. Clay Sci.* **2014**, 95
427 (February 2016), 167–175 DOI: 10.1016/j.clay.2014.04.007.
- 428 (25) Maio, C. Di; Santoli, L.; Schiavone, P. Volume Change Behaviour of Clays: The Influence of Mineral
429 composition, Pore Fluid Composition and Stress State. **2004**, c, 435–451 DOI:
430 10.1016/S0167-6636(03)00070-X.
- 431 (26) Post, V. E. Fresh and Saline Groundwater Interaction in Coastal Aquifers: Is Our Technology Ready for
432 the Problems Ahead? *Hydrogeol. J.* **2005**, 13, 120–123 DOI: 10.1007/s10040-004-0417-2.

- 433 (27) Bergado, D. T.; Ahmed, S.; Sampaco, C. L.; Balasubramaniam, A. S. Settlements of Bagna-Bangpakong
434 Highway on Soft Bangkok Clay. *J. Geotech. Eng.* **1990**, *116* (1), 136–155.
- 435 (28) Wu, Chao-jun; Ye, Guan-lin; Zhang, Lu-lu; Bishop, Daniel; Wang, J. Depositional Environment and
436 Geotechnical Properties of Shanghai Clay : A Comparison with Ariake and Bangkok Clays. *Bull. Eng.*
437 *Geol. Environ.* **2015**, *74*, 717–732 DOI: 10.1007/s10064-014-0670-0.
- 438 (29) Xu, Y. S.; Shen, S. L.; Du, Y. J. Geological and Hydrogeological Environment in Shanghai with
439 Geohazards to Construction and Maintenance of Infrastructures. *Eng. Geol.* **2009**, *109* (3–4), 241–254
440 DOI: 10.1016/j.enggeo.2009.08.009.
- 441 (30) Luo, C. Y.; Shen, S. L.; Han, J.; Ye, G. L.; Horpibulsuk, S. Hydrogeochemical Environment of Aquifer
442 Groundwater in Shanghai and Potential Hazards to Underground Infrastructures. *Nat. Hazards* **2015**,
443 *78* (1), 753–774 DOI: 10.1007/s11069-015-1727-5.
- 444 (31) Chung, S. G.; Giao, P. H.; Kim, G. J.; Leroueil, S. Geotechnical Properties of Pusan Clays. *Can. Geotech. J.*
445 **2002**, *39* (5), 1050–1060 DOI: 10.1139/T02-055.
- 446 (32) Puzrin, A.M; Alonso, E.E; Pinyol, N. . Chapter 2 Unexpected Excessive Settlements: Kansai
447 International Airport, Japan. In *Geomechanics of Failures*; Springer Science+Business Media B.V, 2010; pp
448 23–43.
- 449 (33) Shen, S.-L.; Xu, Y.-S. Numerical Evaluation of Land Subsidence Induced by Groundwater Pumping in
450 Shanghai. *Can. Geotech. J.* **2011**, *48* (9), 1378–1392 DOI: 10.1139/t11-049.
- 451 (34) Hung, W.-C.; Hwang, C.; Liou, J.-C.; Lin, Y.-S.; Yang, H.-L. Modeling Aquifer-System Compaction and
452 Predicting Land Subsidence in Central Taiwan. *Eng. Geol.* **2012**, *147–148*, 78–90 DOI:
453 10.1016/j.enggeo.2012.07.018.
- 454 (35) Barry, A J, Satriyo Budi, Daud Suhaimi, F. R. The Soft Soils of Semarang The Soft Soils of Semarang. In
455 *Symposium on Soft Ground Improvement and Geosynthetic Applications 22 to 23 November 2001*; 2001.
- 456 (36) Tirta, B. A.; Nugroho, M. A.; Parahita, B.; Focks, D. J. Observational Method for More Reliable
457 Settlement Prediction for Reclamation on the Holocene Marine Clay Deposit in Jakarta Bay. **2018**, *7007*,
458 1–9.
- 459 (37) Irsyam, M.; Krisnanto, S.; Wardhani, S. P. R. Instrumented Full Scale Test and Numerical Analysis to
460 Investigate Performance of Bamboo Pile-Mattress System as Soil Reinforcement for Coastal
461 Embankment on Soft Clay. *Liu H., Deng A., Chu J. Geotech. Eng. Disaster Mitig. Rehabil.* **2008**, 165–170
462 DOI: 10.1007/978-3-540-79846-0_11.
- 463 (38) Van Schaeck Mathon, F. M. A. ANALYSIS OF GROUNDWATER CONDITIONS ON THE BASIS OF
464 EXISTING DATA: A Study of the East Semarang- Demak Plain Central Java; Surabaya, 1975.
- 465 (39) Thaden, Robert E; Sumardirdja, Harli; Richards, P. W. Geological Map of Magelang and Semarang
466 Quadrangles, Java, Scale 1:100.000. Geological Research and Development Centre: Bandung 1996.

- 467 (40) Suwarti, T; Wikarno, S. Geological Map of Kudus Quadrangle, Java, Scale 1:100.000. Geological
468 Research and Development Centre: Bandung 1992.
- 469 (41) Marsudi. Prediksi Laju Amblesan Tanah Di Dataran Aluvial Semarang, Propinsi Jawa Tengah, Institut
470 Teknologi Bandung (ITB), 2001.
- 471 (42) Bemmelen, R. W. Van. *The Geology of Indonesia v. 1*; Martinus Nijhoff, The Hague, 1949.
- 472 (43) Tobing, M.H.L; Syarief, E A; Murdohardono, D. *Penyelidikan Geologi Teknik Amblesan Tanah Daerah*
473 *Semarang Dan Sekitarnya, Propinsi Jawa Tengah.*; 2000.
- 474 (44) Marfai, M. A.; Almohammad, H.; Dey, S.; Susanto, B.; King, L. Coastal Dynamic and Shoreline
475 Mapping: Multi-Sources Spatial Data Analysis in Semarang Indonesia. *Environ. Monit. Assess.* **2008**, 142
476 (1–3), 297–308 DOI: 10.1007/s10661-007-9929-2.
- 477 (45) Taufik Nz, A. *Penelitian Hidrogeologi Daerah Imbuhan Airtanah Dengan Metode Isotop Dan Hidrokimia Di*
478 *Cekungan Airtanah Semarang- Demak Provinsi Jawa Tengah*; Bandung, 2009.
- 479 (46) Brown, G., Brindley, G. W. X-Ray Diffraction Procedures for Clay Mineral Identificatio. In *Crystal*
480 *Structures of Clay Minerals and their X-ray Identification*; Brindley, GW; Brown, G., Ed.; Mineralogical
481 Society London, 1980; pp 305–360.
- 482 (47) Deepthy, R.; Balakrishnan, S. Climatic Control on Clay Mineral Formation : Evidence from
483 Weathering Profiles Developed. *J. Earth Syst. Sci.* **2005**, 114 (5), 545–556.
- 484 (48) Skempton, A. W. The Consolidation of Clays by Gravitational Compaction. *Q. J. Geol. Soc.* **1970**, 125,
485 373–411.
- 486 (49) Bradbury, Michael H; Baeyens, B. A Physicochemical Characterisation and Geochemical Modelling
487 Approach for Determining Porewater Chemistries in Argillaceous Rocks. *Geochim. Cosmochim. Acta*
488 **1998**, 62 (5), 783–795.
- 489 (50) Das, B. M. *Advanced Soil Mechanics*, Third Edit.; Taylor& Francis: London and New York, 2008; Vol. 66.
- 490 (51) Mitchell, James K; Soga, K. *Fundamentals of Soil Behavior*, Third Edit.; John Wiley & Sons, Inc.: Hoboken,
491 New Jersey, 2005; Vol. 40.
- 492 (52) Merwe, V. Der; Mechanics, S.; Engineering, F. THE WEATHERING OF SOME BASIC IGNEOUS AND
493 THEIR ENGINEERING PROPERTIES. *Trans. South African Inst. Civ. Eng.* **1964**, 6 (December), 213–222.
- 494 (53) Wong, R. C. K. Swelling and Softening Behaviour of La Biche Shale. *Can. Geotech. J.* **1998**, 35, 206–221.
- 495 (54) Ren, X.; Zhao, Y.; Deng, Q.; Kang, J.; Li, D.; Wang, D. A Relation of Hydraulic Conductivity — Void
496 Ratio for Soils Based on Kozeny-Carman Equation. *Eng. Geol.* **2016**, 213, 89–97 DOI:
497 10.1016/j.enggeo.2016.08.017.
- 498 (55) Ren, X. W.; Santamarina, J. C. The Hydraulic Conductivity of Sediments : A Pore Size Perspective. *Eng.*

© 2017 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).