Embedded Generation (EG) optimization planning and EG caused disturbances.

Tonye Irims

Founder & CEO at [WiSolar](#)

January, 2021

Research Summary

The objective of this study is twofold. First, it reviews and discusses the optimization of Embedded Generation rapid cycles of industrialization and population growth have contributed to a rise in energy use. Small areas and poor development in network growth have also contributed to high load densities in areas. This can contribute to problems of power quality and reliability of voltage. In future electrical systems, thus, embedded output is expected to play a growing role.

The incorporation of embedded output in a distribution system would increase network efficiency in terms of increased voltage profile, decrease in line losses and enhanced power quality if properly designed. This will reduce the pressure from the grid so that the feeders linking the network to the grid could be improved. The optimum delivery means that current assets are better used and the cost-effectiveness of the EG penetration is improved. Capacity generation through the buses should be delegated so that no technological limits are violated and capacity maximized.

The Objective Function (OF) is to be maximized according to the constraints. The constraints are Thermal Restriction, Transformer Capacity: (The amount of generation attached minus the summer valley load does not surpass the rating of the transformer at the higher voltage. The relation between induction generator and high impedance circuitry can also lead to voltage instability issues if SCR is not held under reasonable constraints (the amount of generator attached minus the summer valley load does not surpass that of the transformer at the high voltage). In order to address system planning, operation and pricing, we are evaluating and addressing several traditional optimization approaches, including gradient methods, linear programming, quadratic and dynamic programming.

The second objective of this study was to discuss the main disturbances caused by EG. We find and discuss that there exist some disturbances. First, the transients. This is due to the significant current shifts when the turbines are attached or disconnected. The second disturbance we are concerned about is the difference in voltage. This is due to the cyclical change in the output power of the engine. The third disturbance we have discussed is the interference in the waveform that is caused primarily by the transmitters linking the generators to the distribution network. Again, the

long-duration difference in voltage induced by changes in active and reactive power generators is another disruption. In addition, as another disturbance, generators may affect background waveform disruptions in another manner, directly connected with the distribution system.

References:

- [1] Y. Qu, Y. Chen, J. Huang, and Y. Xie, "Enhanced PIX2PIX dehazing network," in *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2019.
- [2] T. Miyato and M. Koyama, "Cgans with projection discriminator," *arXiv*. 2018.
- [3] M. M. T. Chakravarty, G. Keller, S. Lee, T. L. McDonell, and V. Grover, "Accelerating Haskell array codes with multicore GPUs," in *DAMP'11 - Proceedings of the 6th ACM Workshop on Declarative Aspects of Multicore Programming*, 2011.
- [4] D. Stock, A. G. W. Leslie, and J. E. Walker, "Molecular architecture of the rotary motor in ATP synthase," *Science (80-.)*, 1999.
- [5] T. Magradze, "TAX ADMINISTRATION IN THE RUSSIAN FEDERATION: CURRENT PROBLEMS AND DEVELOPMENT PROSPECTS," in *Colloquium-journal*, 2020, no. 5 (57).
- [6] M. Tengiz, "APPLICATION OF GAME THEORY SIMULATION IN ENTERPRISE MANAGEMENT," in *Colloquium-journal*, 2020, no. 8 (60).
- [7] M. Tengiz, "NEW METHODOLOGY OF EVALUATING THE EFFICIENCY OF MANAGERIAL DECISION-MAKING," in *Colloquium-journal*, 2020, no. 8 (60).
- [8] T. Magradze, "MATHEMATICAL MODELING IN THE ENTERPRISE MANAGEMENT," in *Colloquium-journal*, 2020, no. 7 (59).
- [9] D. JAPARIDZE and T. MAGRADZE, "OPTIMAL PLANNING OF OPERATIVE RESERVE OF ACTIVE POWER IN POWER SYSTEM UNDER CONDITIONS OF UNCERTAINTY," 2020.
- [10] E. D. Castronuovo and J. A. P. Lopes, "Optimal operation and hydro storage sizing of a wind-hydro power plant," *Int. J. Electr. Power Energy Syst.*, 2004.
- [11] E. Arroyo and A. Badel, "Electromagnetic vibration energy harvesting device optimization by synchronous energy extraction," *Sensors Actuators, A Phys.*, 2011.
- [12] G. Dorini, P. Pinson, and H. Madsen, "Chance-constrained optimization of demand response to price signals," *IEEE Trans. Smart Grid*, 2013.
- [13] S. Mazzola, M. Astolfi, and E. Macchi, "The potential role of solid biomass for rural electrification: A techno economic analysis for a hybrid microgrid in India," *Appl. Energy*, 2016.
- [14] A. De Roo, H. Sözer, L. Bergmans, and M. Akşit, "MOO: An architectural framework for runtime optimization of multiple system objectives in embedded control software," *J. Syst. Softw.*, 2013.

- [15] S. A. Li, C. C. Hsu, C. C. Wong, and C. J. Yu, "Hardware/software co-design for particle swarm optimization algorithm," *Inf. Sci. (Ny)*, 2011.
- [16] H. Kanchev, B. Francois, and V. Lazarov, "Unit commitment by dynamic programming for microgrid operational planning optimization and emission reduction," in *International Aegean Conference on Electrical Machines and Power Electronics, ACEMP 2011 and Electromotion 2011 Joint Conference*, 2011.
- [17] C. B. Williams and R. B. Yates, "Analysis of a micro-electric generator for microsystems," *Sensors Actuators, A Phys.*, 1996.
- [18] V. Fischer and M. Drutarovský, "True random number generator embedded in reconfigurable hardware," *Lect. Notes Comput. Sci. (including Subser. Lect. Notes Artif. Intell. Lect. Notes Bioinformatics)*, 2003.
- [19] H. Kanchev, D. Lu, F. Colas, V. Lazarov, and B. Francois, "Energy management and operational planning of a microgrid with a PV-based active generator for smart grid applications," *IEEE Trans. Ind. Electron.*, 2011.
- [20] P. Kohlbrenner and K. Gaj, "An embedded true random number generator for FPGAs," in *ACM/SIGDA International Symposium on Field Programmable Gate Arrays - FPGA*, 2004.
- [21] R. Pena, J. C. Clare, and G. M. Asher, "Doubly fed induction generator using back-to-back PWM converters and its application to variable speed wind-energy generation," *IEE Proc. Electr. Power Appl.*, 1996.
- [22] J. Mattingley and S. Boyd, "CVXGEN: A code generator for embedded convex optimization," *Optim. Eng.*, 2012.
- [23] M. Yildirim, X. A. Sun, and N. Z. Gebraeel, "Sensor-Driven Condition-Based Generator Maintenance Scheduling - Part I: Maintenance Problem," *IEEE Trans. Power Syst.*, 2016.